

1. Identification

Product Identifier Pig Out – Premium Spotter

Other means of identification TMF-89113

Product code

Recommended use Paint, oil, and grease remover.

Recommended restrictions Professional use only.

Manufacturer/supplier/distributor/importer information

Company name Truck Mount Forums

Address 1728 South Park Ct., Chesapeake VA 23320 USA

Telephone (800) 949-7726

Emergency phone number PERS (800) 633-8253

24-hour Emergency (800) 633-8253

2. Hazard(s) Identification

Physical hazardsFlammable LiquidsCategory 4Health hazardsAcute toxicity, oral
Skin irritantCategory 4Eye damageCategory 1Aspiration HazardCategory 2Environmental hazardsHazardous to theCategory 4

aquatic environment

OSHA defined hazards None

Label elements





Signal word DANGER

Hazard statement Combustible liquid.

May be harmful if swallowed.

Causes skin irritation.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Keep away from flames and hot surfaces. No smoking. Wear protective gloves/eye protection/face protection. Wash hands and exposed skin thoroughly after handling. Avoid release to the environment.

Response In case of fire: Use water fog, foam or carbon dioxide (CO2) to extinguish. Call a POISON CENTER/doctor/medical professional if you feel unwell.

IF ON SKIN: Wash with plenty soap and water for 15 minutes. Specific treatment (see section 4 on the Safety Data Sheet). If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor/medical professional.

IF SWALLOWED: Immediately call a POISON CENTER/doctor/medical professional. Do NOT induce vomiting.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Material Name: Pig Out Spot Remover Page 1 of 7 SDS US



Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazard(s) not otherwise

None.

classified (HNOC)

Supplemental information

None

3. Composition/information on ingredients

Mixtures Component(s)			
Chemical name	CAS number	%	
Pentyl acetate	528-63-7	30-50	
Alcohols, C9-11, ethoxylated	68439-46-3	20-30	
C9-C15 Cycloalkanes	Vixture	10-20	
C9-C15 Alkanes	Vixture	10-20	
2-butoxyethanol	111-76-2	1-10	
Other components below reportable levels		1-20	

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Rinse with water for at least 15 minutes. Remove contact lenses if present and easy to do Eye contact

so. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Only induce vomiting at the

Dermatitis. Rash. May cause an allergic skin reaction.

instruction of medical personnel.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and

special treatment needed

Provide general support measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to the hospital. Keep victim under

observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions

to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, sand, or earth may be used

for small fires only.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a

source or ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and

grounding procedures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for

firefighters

Self-contained breathing apparatus and full protecting clothing must be worn in case of fire.

Fire-fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if

you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SDS US Material Name: Pig Out Spot Remover Page 2 of 7



General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Remove all sources of ignition. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources. Use only non-sparking tools. Take precautionary measures against static discharge. Keep combustibles away from spilled material.

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small spills: Absorb with earth, sand, or other non-combustible material and transfer to container for later disposal. Clean surface thoroughly to remove residual contamination. Never return spills to original container for re-use. For waste disposal, see section 13 of the SDS

Avoid release to the open environment. Avoid discharge into surface waterways and other areas not consistent with package labeling.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Do not smoke. Use explosion proof equipment and non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Keep away from heat, sparks and open flame. Ground/bond container and equipment.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Ground/bond container and equipment. Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits
US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Components Type Value
2-butoxyethanol PEL 50 ppm
US ACGIH Threshold Limit Values
Components Type Value
2-butoxyethanol STEL 20 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components Value Determinant Species Sampling Time
2-butoxyethanol 200 mg/g Creatinine Urine End of shift.

Appropriate engineering Good general ventilation (typically 10 air changes per hour) should be used. Ventilation **controls** rates should be matched to conditions. If applicable, use process enclosures, local exhaust

Material Name: Pig Out Spot Remover Page 3 of 7 SDS US



ventilation, or other engineering controls to maintain airborne levels below recommended

exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection The use of gloves impervious to the specific material handled is advised to prevent skin

contact. Users should check with manufacturers to confirm the breakthrough performance of their products. Depending on exposure and use conditions, additional protection may be

necessary to prevent skin contact including use of items such as chemical-resistant boots,

aprons, arm covers, hoods, coveralls, or encapsulated suits. Suggested protective

materials: Nitrile and PVC rubber.

Other Wear appropriate chemical-resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene When using do not smoke or use chewing tobacco. Always observe good personal hygiene **considerations** measures, such as washing after handling the material and before eating, drinking, and/or

smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical State Liquid.

Color Light yellow translucent

Odor Characteristic.
Odor threshold Not available.
pH Not applicable.
Melting/freezing point Not available.

Initial boiling point and

300-410°F (148.9-210°C) estimated.

boiling range Flash point

150°F (66°C) estimated.

Evaporation rate Not available. Flammability Not available.

Flammability Limits

Upper6% (estimated)Lower0.8% (estimated)Vapor pressureNot available.Vapor densityNot available.

Specific gravity (water=1) 0.90
Solubility in water Insoluble.
Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

Not available.

Decomposition temperature Not available.

Viscosity Not available.

10. Stability and reactivity

Reactivity This product is stable and non-reactive under normal conditions of use.

Material Name: Pig Out Spot Remover Page 4 of 7 SDS US



Chemical stability Material is stable under normal conditions. Store in a cool dark place.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding

Incompatible materials the flash point. Contact with incompatible materials.

Hazardous decomposition

Oxidizing agents, acids.

products

Carbon dioxide, carbon monoxide.

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be low ingestion hazard.

Inhalation Prolonged inhalation may be harmful.

Skin contact May cause skin irritation.

Eye contact Causes serious eye damage. Wear eye/face protection.

Symptoms related to the Dermatitis. Rash.

physical, chemical and

toxicological characteristics

Acute toxicity May be harmful if swallowed.

Product Pig Out (CAS mixture)		
Exposure Classification Route and Species LD50 /LC50		
Acute Oral, rat 2,500 mg/kg (estimated)		
Acute Dermai, rat > 10,400 mg/kg (estimated)		
*Estimates for product may be based on additional component data not shown		

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

Respiratory sensitization Not available.

Skin sensitization Not available.

Germ cell mutagenicity No data available to indicate product or any

components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not expected to be a carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not Listed

Reproductive toxicity This product is not expected to cause reproductive or

developmental effects.

Specific target organ toxicity – single exposure Not classified.

Specific target organ toxicity – repeated exposure Not classified.

Aspiration hazard May be harmful or fatal if product enters airways.

12. Ecological information

Ecotoxicity		
Product Pig Out (CAS mixture)		
Aquatic Receptor Species		Test Thresholds
Fish Fathead minnow		LC50 = 23 mg/L (estimated)
Crustacea Daphnia Magna		EC50 = 14 mg/L (estimated)
Fish Western mosquitofish		EC50 = 72 mg/L – 92-hr (estimated)
*Estimates for product may be based of	on additional component data not shown	•



Persistence and

No data available. The listed classes of chemicals within this product are not known to

degradability persist in an open aerobic environment

Bio-accumulative potential Potential to bioaccumulation is expected to be low.

Mobility in soil No data available. Mixture chemicals are expected to exhibit moderate to high level of

mobility in saturated and semi-saturated soil matrices

Other adverse effects

Harmful to aquatic life in elevated concentrations. May cause long-lasting harmful effects

to aquatic life with repeated exposure.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose

of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the

waste disposal company. As packaged, this product may meet criteria defining RCRA ignitable (D001) hazardous wastes when disposed. (40 CFR Part 261, Subpart C). Before selecting disposal method, ensure that the waste materials have been properly assessed

and, as necessary, tested to confirm regulatory status

Waste from residues/unused

product

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

(see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal. Since emptied containers may contain product residue, follow label warnings

even after container is emptied.

14. Transport information

Not regulated as a hazardous material

15. Regulatory information

US federal regulations .

SARA 302 Extremely hazardous substance Not listed.

SARA 304 Emergency release notification Not listed.

SARA 311/312 Hazard Categories

Immediate Hazard - Yes

Delayed Hazard - No

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

SARA 313 (TRI reporting) 2-butoxyethanol (Glycol Ether Category)

California Proposition

<u>/!\</u>

5 WARNING: This product can expose you to Ethylene Oxide, which is known to the State of

California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Material Name: Pig Out Spot Remover Page 6 of 7 SDS US



16. Other information, including date of preparation or last revision

 Issue date
 5/28/2019

 Revision date
 10/23/2019

Version #

HMIS® ratings Health: 2

Flammability: 2 Physical hazard: 0



NFPA ratings Health: 2

Flammability: 2 Instability: 0



Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

and have been obtained from resources believed to be reliable. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified by

the text.

Revision information 10/23/2019 Add HMIS and NFPA 704 pictograms.