THY

SAFETY DATA SHEET

1. Identification

Product Identifier Rob's Solvent Sealer

Other means of identification

TMF-89360

Product code

Recommended use Solvent based sealer for stone and grout.

Recommended restrictions

Professional use only.

Manufacturer information

Company name Truck Mount Forums
Address 5045 Admiral Wright Rd.

Suite 109

Virginia Beach, VA 23462

Telephone (800) 949-7726

Emergency phone number PERS 24-hour Emergency

2. Hazard(s) Identification

Physical hazardsFlammable LiquidsCategory 3Health hazardsAspiration HazardCategory 1

None.

Environmental hazards Not classified.

OSHA defined hazards

Label elements



Signal word DANGER

Hazard statement Flammable liquid and vapor.

May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/ hot surfaces. No smoking. Keep container

tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/ eye protection/ face protection. Wash hands and exposed skin thoroughly after handling.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for

extinction.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

IF SWALLOWED: Immediately call a POISON CENTER/doctor/medical professional. Do

NOT induce vomiting.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

None.

Hazard(s) not otherwise

classified (HNOC)

Supplemental information

Material Name: Rob's Solvent Sealer Page 1 of 7 SDS US



3. Composition/information on ingredients

Mixture Component(s)				
Chemical Name	CAS number	%		
Naphtha (petroleum), heavy alkylate	64741-65-7	90-100		
Tert-Butyl acetate	540-88-5	1-10		
Other components below reportable levels		1-5		

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water for at least 15 minutes. Remove contact lenses if present and easy to do

so. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Only induce vomiting at the Ingestion

Dermatitis. Rash. May cause an allergic skin reaction.

instruction of medical personnel. If vomiting occurs keep head low to prevent stomach

contents entering the lungs

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed Provide general support measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to the hospital. Keep victim under

observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions

to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Carbon dioxide (CO₂). Dry chemical powder, sand, or earth may be used

for smothering small fires only.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source or ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for

firefighters

Self-contained breathing apparatus and full protecting clothing must be worn in case of

fire.

Fire-fighting

equipment/instructions

area if you can do so without risk.

Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

In case of fire and/or explosion do not breathe vapors/fumes. Move containers from fire

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Remove all sources of ignition. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources. Use only non-sparking tools. Take precautionary measures against static discharge. Keep combustibles away from spilled material.

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small spills: Absorb with earth, sand, or other non-combustible material and transfer to container for later disposal. Clean surface thoroughly with detergent and water to remove residual contamination. Place collected residual material in a properly labeled container and secure for proper disposal

Never return spills to original container for re-use. For waste disposal, see section 13 of the

Environmental precautions

Avoid release to the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Avoid discharge into areas not consistent with package labeling.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Do not smoke. Use explosion proof equipment and non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Ground/bond container and equipment. Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US OSHA Table Z-2 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
Naphtha (petroleum), heavy alkylate	PEL/TWA	100 ppm
Tertiary butyl acetate	PEL	200 ppm
ACGIH Recommended Exposure		
Component(s)		
Tertiary butyl acetate	TWA	200 ppm
NIOSH REL Values (US)		
Components	Туре	Value
Naphtha (petroleum), heavy alkylate	REL	100 ppm

Biological limit values

No information.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Page 3 of 7 SDS US Material Name: Rob's Solvent Sealer



Skin protection

Hand protection The use of gloves impervious to the specific material handled is advised to prevent skin

contact. Users should check with manufacturers to confirm the breakthrough performance of their products. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Suggested protective materials: Nitrile and PVC rubber.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is

recommended.

Respiratory protection In case of insufficient ventilation, wear suitable NIOSH-approved respiratory protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygieneConsiderations
When using do not smoke or use chewing tobacco. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or

measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical State Clear liquid.

Color Colorless to pale amber.

Odor Characteristic.
Odor threshold Not available.
pH Not available.
Melting/freezing point Not available.

Initial boiling point and

boiling range

300-410°F (148.9-210°C) estimated.

Flash point 129°F (54°C) estimated.

Evaporation rate Not available.
Flammability Not available.

Flammability Limits

Upper 6% (estimated)
Lower 0.7% (estimated)
Vapor pressure Not available.
Vapor density Not available.

Specific gravity (water=1) 0.758

Solubility in water Insoluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature <649°F (343°C) Estimated

Decomposition temperature Not available. **Viscosity** Not available.

10. Stability and reactivity

ReactivityThis product is stable and non-reactive under normal conditions of use. **Chemical stability**Material is stable under normal conditions. Store in a cool dark place.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding

the flash point. Contact with incompatible materials.



Incompatible materials Oxidizing agents, acids.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products should

products not be produced.

11. Toxicological information

Information on likely routes of exposure

IngestionExpected to be low ingestion hazard.InhalationProlonged inhalation may be harmful.

Skin contact May cause mild skin irritation.

Eye contact Causes serious eye irritation. Wear eye/face protection.

Dermatitis. Rash.

Symptoms related to the physical, chemical and

toxicological characteristics

Acute toxicity Not established.

Product Rob's Solvent Sealer (CAS mixture)				
Exposure Classification	Route and Species	LD50		
Acute	Oral, rat	>5,000 mg/kg estimated		
Acute	Dermal, rabbit	>5,000 mg/kg (Literature)		
*Estimates for product may be based on additional component data not shown				

Skin corrosion/irritationNot classified.Serious eye damage/ irritationNot available.Respiratory sensitizationNot available.Skin sensitizationNot available.

Germ cell mutagenicity

No data available to indicate product or any components

present at greater than 0.1% are mutagenic or

genotoxic.

Carcinogenicity This product is not expected to be a carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not Listed.

Reproductive toxicityThis product is not expected to cause reproductive or

developmental effects.

Specific target organ toxicity – single exposureNot classified.Specific target organ toxicity – repeated exposureNot classified.

Aspiration hazard May be harmful or fatal if product enters airways.

12. Ecological information

Ecotoxicity					
Product Rob's Solvent Sealer (CAS mixture)					
Aquatic Receptor	Species	Test Thresholds			
Crustacea	Daphnia	EC ₅₀ (48-hr): 200 mg/L (estimated)			
Fish	Fathead minnow (Pimephales promelas)	LC ₅₀ (96-hr): 90 mg/L (estimated)			
*Estimates for product may be based on additional component data not shown					

Persistence and No data available.

degradability

Bioaccumulative potential Potential to bioaccumulation is expected to be low.

Mobility in soil No data available. This class of chemical mixture is expected to exhibit limited mobility in

saturated and semi-saturated soils. Due to oleophilic natural of a primary component,



some level of phase separation can be expected with the oleophilic recoverable as a LNAPL

at the piezometric surface of the water table

Other adverse effects May cause long lasting harmful effects to aquatic life.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose

of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

As packaged, this product may meet criteria defining RCRA ignitable (D001) hazardous

wastes when disposed. (40 CFR Part 261, Subpart C). Before selecting disposal method, ensure that the waste materials have been properly assessed and, as necessary, tested to

confirm regulatory status.

Waste from residues/unused

product

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

(see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal. Since emptied containers may contain product residue, follow label warnings

even after container is emptied.

14. Transport information

USDOT

UN number UN1993

UN proper shipping name Flammable liquids, n.o.s. (petroleum distillates, butyl acetates)

Transport hazard class(es)

Class 3 Subsidiary risk -

Packaging group III

Special precautions for

user

Read safety instructions, SDS, and emergency procedures before handling.

Marine pollutant No

Special precautions for user

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

USDOT Label/Placard

This product is not intended to be transported in bulk.



15. Regulatory information

US federal regulations

SARA 302 Extremely hazardous substance Not listed.
SARA 304 Emergency release notification Not listed.

SARA 311/312 Hazard Categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 313 (TRI reporting) Not listed.

TSCA – All chemical components used to manufacture this product comply with the Toxic Substances Control Act (TSCA) registry requirements and are either listed within, or exempted from, the current TSCA 8(b) inventory.

California Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986

This product is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65 at levels which would be subject to

threshold determination and Safe Harbor notification (1/2019)

16. Other information, including date of preparation or last revision

Issue date 7/27/202

Revision date

Version #

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

and have been obtained from resources believed to be reliable. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

by the text.

Revision information First issue