Field of View:	56°
Display Screen:	2" IPS LCD
Display Screen Resolution:	480*360
Send Mode:	Photo , Video , Photo + Video
Image Resolution:	4M, 8MP
Image Aspect Ratio:	16:9
Transmitted Image Thumbnails:	800 * 480 (Normal) or 1376 * 768 (Large)
HD Image (Upon request):	2688 * 1520 (4MP), 3840 * 2160 (8MP)
Photo Burst:	1-3 Photos
Video Resolution:	WVGA (800 * 480), 720p (1280 * 720), 1080p (1920 * 1080)
Video Frame Rate:	30 fps
Video Aspect Ratio:	16:9
Video Transmission Length:	5 Sec, 10 Sec, 15 Sec, 20 Sec, 25 Sec, 30Sec
Live Streaming:	Supported
Live Stream Resolution:	WVGA (800 * 480)
Live Stream Bitrate:	200 kbps – 1Mbps, auto adjusted
Live Stream Frame Rate:	10 fps – 30 fps, auto adjusted
Video Sound:	Available
Image & Video Color:	Color by day, monochrome by night
Image Trigger Speed:	0.45s
Video Trigger Speed:	0.4s
Trigger Interval:	0s – 60min
Time-lapse:	30s – 24 hours
Illumination:	Invisible Blackout IR LED
Illumination Range:	Up to 60 feet
Illumination Power:	Auto adjusted
GPS & Mapping:	Supported
Camera Tracker:	Available
SIM Card Pre-installed:	Yes
Internal Power Supply:	Built-in Lithium-ion cell, 5300mAh

External Power Supply:	12 x AA (1.2v-1.5v ea.) , 12V DC , 12V Lead acid
Solar Supported:	Direct-connect solar panel supported
External Power Connection:	Included
Product Warranty:	2 years upon registration
Dimensions:	5.29"H x 4.5"W x 2.5"D (13.44x11.43x6.35 cm)
Weight:	540g
Operating Temperature:	-4 to 140 Fahrenheit (-20 to 60 Celsius)
IP Rating:	IP65
Operation Humidity:	5% - 90%
PIR Type:	Multi-zone
PIR Sensitivity:	Off , Low , Normal , High
PIR Detection Range:	Up to 80 feet (24 meters)
Scheduled Events:	Send Status report , Take a Photo , Batch Sending
Workday:	Adjustable
Periodic Surveillance:	Two Start-Stop Time settings
SD Card Overwrite:	Supported
SD Card Type:	Standard Size, Class 10, Up to 128GB
Camera Password:	Supported
Mounting:	Tripod , Mounting Strap , Python Lock