SECTION 1. IDENTIFICATION

Product identifier used on the label

: Aerolon Speedcoat

Product Code(s) : None reported.

Recommended use of the chemical and restrictions on use

Aircraft Paint Protectant

Restriction on use: None known

Chemical family : Mixture

Name, address, and telephone number of

of the supplier: the manufacturer: California Detailing Inc. Refer to supplier

dba Aerolon 340 Fell Street

San Francisco, CA, USA

94102

Supplier's Telephone # : 415-722-1011

24 Hr. Emergency Tel # : 24 Hr. Emergency Tel. # 800-255-3924

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Semi viscous, off white cream with a bubble gum odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Hazard classification:

Flammable Liquid - Category 4

Label elements

Hazard pictogram(s)

None required under U.S. OSHA Hazcom 2012 and Canadian WHMIS 2015 regulations.

Signal Word

Warning!

Hazard statement(s)

Combustible liquid.

Precautionary statement(s)

Keep away from flames and hot surfaces. - No smoking.

Wear protective gloves and eye/face protection.

In case of fire: Use water fog, dry chemical, CO2 or 'alcohol' foam to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Other hazards which do not result in classification:

Ingestion may cause irritation of the mouth, throat and stomach. May cause respiratory irritation. Contact with eyes may cause irritation. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Environmental precautions:

Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SAFETY DATA SHEET

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	Common name and synonyms	CAS#	Concentration (% by weight)
Hydrotreated light distillate	Isoparaffinic petroleum distillate Kerosene (petroleum), hydrotreated	64742-47-8	5.0 - 15.0
Alkanes, C12-14, iso-	Not available.	68551-19-9	1.0 - 5.0
Solvent naphtha (petroleum) heavy aliphatic	Heavy aliphatic solvent naphtha	64742-96-7	1.0 - 5.0
Ammonium hydroxide	Aqueous Ammonia	1336-21-6	<1

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion : If swallowed: Immediately call a poison center/doctor. Do not induce vomiting. Rinse

mouth thoroughly. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of

aspiration.

Inhalation: Immediately remove person to fresh air. If breathing has stopped, give artificial

respiration. If breathing is difficult, give oxygen by qualified medical personnel only.

Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact: Wash affected areas with soap and water. Take off contaminated clothing and wash

before re-use. Get medical attention if irritation develops and persists.

Eye contact : Flush with large amounts of water for 15 minutes. Remove contact lenses, if present

and easy to do. If irritation or symptoms develop, seek medical attention.

Most important symptoms and effects, both acute and delayed

: Inhalation of high concentrations may cause dizziness, disorientation, incoordination, narcosis, nausea or narcotic effects. Direct eye contact may cause temporary redness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Indication of any immediate medical attention and special treatment needed

: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

: Combustible liquidClosed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Vapour can travel considerable distance and flashback to a source of ignition. Vapours are heavier than air and collect in confined and low-lying areas.

Flammability classification (OSHA 29 CFR 1910.106)

: Flammable Liquid - Category 4

Hazardous combustion products

: Carbon dioxide and carbon monoxide. Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. A full-body chemical resistant suit should be worn.

Special fire-fighting procedures

SAFETY DATA SHEET

: Evacuate personnel to safe areas. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Dike for water control. Avoid release to the environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.

Environmental precautions

Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up

Ventilate the area. Prevent further leakage or spillage if safe to do so. Dike for water control. Use only non-sparking tools and equipment in the clean-up process. Spilled material will create slippery surfaces. Clean up promptly. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contact the proper local authorities.

Special spill response procedures

: If a spill/release in excess of the EPA reportable quantity is made into the environment. immediately notify the national response center in the United States (phone: 1-800-424-8802).

US CERCLA Reportable quantity (RQ): None reportable.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Use only outdoors or in a well-ventilated area. Wear suitable protective equipment. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep away from flames and hot surfaces. - No smoking. Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting/equipment. Take precautionary measures against static discharges. Bond and ground transfer containers and equipment to Label containers appropriately. Wash thoroughly after avoid static accumulation. handling. Keep containers closed when not in use.

Conditions for safe storage : Store locked up. Store in a cool, dry, well-ventilated area. Keep container tightly closed. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks.

Incompatible materials

: Strong oxidizers (e.g. Chlorine, Peroxides, etc.).

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:				
Chemical Name	ACGIH	I TLV	OSHA F	<u>'EL</u>
	TWA	STEL	<u>PEL</u>	<u>STEL</u>
Hydrotreated light distillate	200 mg/m³ (as total hydrocarbon vapour)	N/Av	N/Av	N/Av
Alkanes, C12-14, iso-	N/Av	N/Av	N/Av	N/Av
Solvent naphtha (petroleum) heavy aliphatic	N/Av	N/Av	500 ppm (2000 mg/m³)	N/Av
Ammonium hydroxide	25 ppm (Ammonia)	35 ppm (Ammonia)	50 ppm (Ammonia)	N/Av

Exposure controls

SAFETY DATA SHEET

: Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapours below their respective threshold limit value. Use

explosion-proof electrical and ventilating equipment.

Respiratory protection : Respiratory protection is required if the concentrations exceed the TLV. Use a NIOSH

approved dust respirator if dust levels exceed exposure limits. Seek advice from

respiratory protection specialists.

Skin protection: Wear protective gloves. The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye / face protection : Wear eye/face protection. Wear safety glasses with side shields.

Other protective equipment : Wear appropriate protective clothing to prevent skin contact, such as coveralls or long

sleeved shirt, long pants, and shoes and socks. An eyewash station and safety shower should be made available in the immediate working area. Other equipment

may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Semi-viscous, off white cream

Odour : Bubble gum

Odour threshold : No information available.

pH : Not available.Melting/Freezing point : Not available.

Initial boiling point and boiling range

: Not available.

Flash point : 61°C

Flashpoint (Method) : Tag closed cup

Evaporation rate (BuAe = 1) : <1

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.)

: Not available.

Upper flammable limit (% by vol.)

: Not available.

Oxidizing properties : None known.

Explosive properties : Not explosive

Vapour pressure : Not available.

Vapour density : >1(Air = 1)

Relative density / Specific gravity

: 0.97 @ 70°F

Solubility in water : Insoluble.

Other solubility(ies) : No information available.

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: Not available.

Auto-ignition temperature : 220°C (500°F)

Decomposition temperature : No information available.

Viscosity : 16,700-28,700 cps

Volatiles (% by weight) : Not available.

Volatile organic Compounds (VOC's)

: No information available.

Absolute pressure of container

: N/Ap

Flame projection length : N/Ap Other physical/chemical comments

: None known or reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not normally reactive.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerization does not occur.

Conditions to avoid : Keep away from heat, sparks and flame. Ensure adequate ventilation, especially in

confined areas. Avoid contact with incompatible materials.

Incompatible materials : See Section 7 (Handling and Storage) for further details.

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption

: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: Inhalation of high vapour concentrations may cause symptoms like headache,

dizziness, tiredness, nausea and vomiting.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin : Direct skin contact may cause slight or mild, transient irritation.

Sign and symptoms eyes : Direct eye contact may cause slight redness.

Potential Chronic Health Effects

: Prolonged exposure can cause redness, swelling, itching, cracking of the skin,

dermatitis and sensitization.

Mutagenicity: Not expected to be mutagenic in humans.

Carcinogenicity : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: Not expected to have other reproductive effects.

Sensitization to material : Not expect Specific target organ effects : This material

Not expected to be a skin or respiratory sensitizer.

This material is not classified as hazardous under U.S. OSHA regulations (29CFR)

1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products

Regulations) (WHMIS 2015).

Medical conditions aggravated by overexposure

Pre-existing skin, eye and respiratory disorders.

Synergistic materials : No information available.

Toxicological data : There is no available data for the product itself, only for the ingredients. See below for

individual ingredient acute toxicity data.

	LC ₅₀ (4hr)	LD50		
Chemical name	inh, rat	(Oral, rat)	(Rabbit, dermal)	
Hydrotreated light distillate	> 5.2 mg/L (aerosol) (No mortality)	> 5000 mg/kg	> 2000 mg/kg (No mortality)	
Alkanes, C12-14, iso-	5.3 mg/L	>5000 mg/kg	>2000 mg/kg	
Solvent naphtha (petroleum) heavy aliphatic	> 6 mg/L	> 5000 mg/kg	> 2000 mg/kg	
Ammonium hydroxide	3670 ppm (rat) (Ammonia) 2115 ppm (mouse) (Ammonia)	350 mg/kg	N/Av	

Other important toxicological hazards

: See Section 2 for additional information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Not expected to be harmful to aquatic organisms. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. See the following tables for the substance's ecotoxicity data. Do not allow this material to drain into sewers/water supplies.

Ecotoxicity data:

<u>Ingredients</u>		Toxicity to Fish				
	CAS No	LC50 / 96h	NOEC / 21 day	M Factor		
Hydrotreated light distillate	64742-47-8	20 mg/L (Rainbow trout) (Read-across)	N/Av	None.		
Alkanes, C12-14, iso-	68551-19-9	>10000 mg/L	N/Av	None.		
Solvent naphtha (petroleum) heavy aliphatic	64742-96-7	N/Av	N/Av	None.		
Ammonium hydroxide	1336-21-6	8.2 mg/L (Fathead minnow)	N/Av	None.		

<u>Ingredients</u>	CAS No	Toxicity to Daphnia				
		EC50 / 48h	NOEC / 21 day	M Factor		
Hydrotreated light distillate	64742-47-8	40 - 89 mg/L (Daphnia magna) (Read-across)	0.48 mg/L (Read-across)	None.		
Alkanes, C12-14, iso-	68551-19-9	>100 mg/L (Daphnia magna)	N/Av	None.		
Solvent naphtha (petroleum) heavy aliphatic	64742-96-7	1.4 mg/L (Daphnia magna)	0.48 mg/L	None.		
Ammonium hydroxide	1336-21-6	0.66 mg/L (Daphnia magna)	N/Av	1		

<u>Ingredients</u>	CAS No	Toxicity to Algae				
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor		
Hydrotreated light distillate	64742-47-8	6.2 mg/L/96hr (Green algae) (Read-across)	0.4 mg/L/96hr (Read-across)	None.		
Alkanes, C12-14, iso-	68551-19-9	>100 mg/L (Green algae)	N/Av	None.		
Solvent naphtha (petroleum) heavy aliphatic	64742-96-7	N/Av	N/Av	None.		
Ammonium hydroxide	1336-21-6	N/Av	N/Av	None.		

SAFETY DATA SHEET

Persistence and degradability

: No data is available on the product itself.

Bioaccumulation potential: No data is available on the product itself.

<u>Components</u>	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
Hydrotreated light distillate (CAS 64742-47-8)	5.1 - 8.8	N/Av

Mobility in soil

This material has low solubility and floats, and is expected to migrate from water to the land.

Other Adverse Environmental effects

: No data is available on the product itself.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle waste according to recommendations in Section 7. Empty containers may contain hazardous residues.

Methods of Disposal

Dispose in accordance with all applicable federal, state, provincial and local

regulations.

RCRA

If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	None.	Not regulated.	not regulated	none	\bigotimes
TDG Additional information	None.				
49CFR/DOT	None.	Not regulated.	not regulated	none	\bigotimes
49CFR/DOT Additional information	None.				

Special precautions for user : Appropriate advice on safety must accompany the package. Keep away from flames

and hot surfaces. - No smoking.

Environmental hazards : This substance does not meet the criteria for an environmentally hazardous substance

according to the IMDG Code. See Section 12 for more environmental information.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: This information is not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

		TSCA	CERCLA Reportable	SARA TITLE III: Sec. 302, Extremely	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical		
<u>Ingredients</u>	CAS#	Inventory	Quantity(RQ) (40 CFR 117.302):	nantity(RQ) (40 Hazardous Substance, 40	Toxic Chemical	de minimus Concentration	
Hydrotreated light distillate	64742-47-8	Yes	None.	None.	No	N/Ap	
Alkanes, C12-14, iso-	68551-19-9	Yes	N/Ap	N/Av	No	N/Ap	
Solvent naphtha (petroleum) heavy aliphatic	64742-96-7	Yes	N/Ap	N/Av	No	N/Ap	
Ammonium hydroxide	1336-21-6	Yes	1000 lb/ 454 kg	N/Ap	No	N/Ap	

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Physical hazards: Flammable .Health hazards None.

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS#	Cas # California Proposition 65		State "Right to Know" Lists					
	CAS#	Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Hydrotreated light distillate	64742-47-8	No	N/Ap	No	No	No	No	No	No
Alkanes, C12-14, iso-	68551-19-9	No	N/Ap	No	No	No	No	No	No
Solvent naphtha (petroleum) heavy aliphatic	64742-96-7	No	N/Ap	No	No	No	No	No	No
Ammonium hydroxide	1336-21-6	No	N/Ap	Yes	Yes	No	Yes	Yes	No

No ingredient regulated by CA Prop 65 present.

Canadian Information:

All ingredients are present on the DSL. WHMIS Classification: See Section 2.

International Information:

Components listed below are present on the following International Inventory list:

SAFETY DATA SHEET

<u>Ingredients</u>	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Hydrotreated light distillate	64742-47-8	265-149-8	Present	Present	(9)-1700	KE-12550	Present	May be used as a single component chemical under an appropriate group standard.
Alkanes, C12-14, iso-	68551-19-9	271-369-5	Present	Present	Present	KE-00534	Present	No data available.
Solvent naphtha (petroleum) heavy aliphatic	64742-96-7	265-200-4	Present	Present	Not listed	KE-31655	Present	May be used as a single component chemical under an appropriate group standard.
Ammonium hydroxide	1336-21-6	215-647-6	Present	Present	(1)-314	KE-01688	Present	HSR001526, HSR001517, HSR001516, HSR001563 (dilution)

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

of 1980

CFR: Code of Federal Regulations CNS: Central Nervous System DOT: Department of Transportation EPA: Environmental Protection Agency

EINECS: European Inventory of Existing Commercial chemical Substances

IARC: International Agency for Research on Cancer

IBC: Intermediate Bulk Container

IMDG: International Maritime Dangerous Goods

Inh: Inhalation

LC: Lethal Concentration

LD: Lethal Dose N/Ap: Not Applicable N/Av: Not Available

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

: 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2016

- 2. International Agency for Research on Cancer Monographs, searched 2017
- 3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases,

2017(Chempendium, HSDB and RTECs).

- 4. Material Safety Data Sheets from manufacturer.
- 5. US EPA Title III List of Lists 2017 version.
- 6. California Proposition 65 List 2017 version.
- 7. OECD The Global Portal to Information on Chemical Substances -

eChemPortal,2017.

References

SAFETY DATA SHEET

Preparation Date (mm/dd/yyyy)

: 06/22/2018

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Prepared for:

California Detailing Inc. dba Aerolon 340 Fell Street San Francisco, CA 94102 Telephone: 415-722-1011

Prepared by:

ICC The Compliance Center Inc.

Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)

http://www.thecompliancecenter.com



DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by California Detailing Inc. and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and California Detailing Inc. expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and California Detailing Inc..

END OF DOCUMENT