4" LED ARCHITECTURAL CAN & FRAME IN KIT



Project:	
Type:	
Catalog#:	

STANDARD











The Energy Star CLADL4 series is a 4" commercial grade architectural can & frame in kit. Built for commercial use with architectural frames and a deep cone reflector for precision light. This highefficiency luminaire provides long life - offered two wattages and color temperatures.

FEATURES


- · Architectural frames
- C channel and flat hanger bars for tie down to ceiling grids.
- 21 Watt available in 3000K.
- 28 Watt available in 4000K.
- Junction box is mounted on the frame for easy wiring, driver access for installation, and replacement.
- Diecast aluminum heatsink dissipates heat from the LED board.
- Self-flanged aluminum reflector with a frosted lens to shield direct view of LEDs.
- Universal 120-277 AC voltage (50/60Hz)
- 0-10V dimming
- Color rendering index ≥ 80.
- Long life LEDs up to 50,000hours.
- Operation Temp. -30°C~40°C (-22°F~104°F).




Image shown with trim & frame.

WARRANTY & LISTINGS

- cULus Listed.
- Energy star listed.
- Suitable for wet locations (not suitable for coastal/salt water areas).
- Suitable for damp locations.
- RoHS compliant.
- · 5-year warranty of all electronics and housing.





11 1/2"

ORDERING INFORMATION

Trim Models

IIIII Wodels					
Model	Color Temperature	Luminaire Lumens	Luminaire Watts	Lumens/Watt	
CLADL4-2130-T	3000k	1590	21	76	
CLADL4-2840-T	4000k	1940	28	69	

Frame Models

Luminaire Wattage	Frame Required		
21	CLADL4-2130-F		
28	CLADL4-2840-F		