


# CLSMR9

## 9" SURFACE MOUNT DISC LIGHT CCT FIELD SELECTABLE



Shown with brushed nickel finish



Weight: 2 pounds



MODEL	SIZE & NOMINAL LUMEN OUTPUT	COLOR TEMPERATURE (KELVIN FIELD SELECTABLE)	HOUSING COLOR	
CLSMR9	18 = 1,100 LM	27 = 2700K	WH BN BZ	White Brushed Nickel Bronze
		30 = 3000K		
		35 = 3500K		
		40 = 4000K		
		50 = 5000K		

### FEATURES

- Field selectable 2700k (soft white), 3000k (warm white), 3500k (warm/neutral white), 4000k (neutral white), and 5000k (cool white) color temperatures.\*
- Long-life LEDs provide at least 70% of initial lumen output ( $L_{70}$ ) for 119,000 hours of operation.\*\*
- Color rendering index ( $R_a$ ) > 90.
- 1,100 nominal lumens.
- 18 nominal watts.
- Input voltage = 120V 60Hz.
- Power factor > 0.90.
- Triac dimming.
- Aluminum housing.
- White, nickel, or bronze housing color.
- Glass lens.
- Easy installation in new construction or remodel applications.
- This device is not intended for use with emergency exits.

### WARRANTIES & LISTINGS

- cETLus listed for damp locations in ambient temperatures of -15°C to 40°C (5°F to 104°F).
- Energy Star qualified.
- Title 24 qualified.
- Complies with FCC Part 15, class B.
- Input transient protection = 2.5kV.
- 5-year warranty of all electronics and housing.

### COMPATIBLE DIMMERS

MANUFACTURER/SERIES	MODEL NUMBER
LUTRON DIVA	DVCL-153PR-WH
LUTRON DIVA	CTCL-153PDH-WH
LUTRON DIVA	TGCL-153PH-WH
LUTRON DIVA	MACL-153MH-WH
LUTRON DIVA	P-PKG1W-WH-R
LEVITON	R62-06674-P0W
LEVITON	R12-06672-1LW
LEVITON	R50-IPL06-10M
EATON	SAL06P-LA-K

\* Contact factory for other color temperatures and lumen packages.

\*\*  $L_{70}$  hours are IES TM-21-11 calculated hours.