

Catalog Number			
Project Number			
Туре			

DESCRIPTION

LED-GIMBAL-PRO Series lights are bright, energy efficient and elegantly designed. They are an ideal solution for commercial and residential applications requiring compact shape, superior quality and visual aesthetics. This 8W light produces 696-784Lm (depending on the CCT). At 1.77" tall and 2.48" round they can fit into tight spaces that a traditional recessed can light can't, such as ceilings with ductwork/piping/obstructions, hot-roof ceilings with limited vertical clearance, and tight soffits. It comes in Black, White and Brushed Nickel Finishes. Each light can be set at 3000K, 4000K or 5000K CCT (Adjustable). These lights feature an easily adjustable LED face (Gimbal) that can be pointed straight downward, making them compatible with sloped ceilings.

Lifespan: 39,000 hrs

Certifications: ETL, CE, RoHS

Warranty: 5 years

ELECTRICAL

Lumen output: 696-784 lm

Wattage: 8 watts

CCT (adjustable): 3000K, 4000K, 5000K Operating voltage: 110-130 VAC

Dimming: Dimmable

MATERIAL / OPTICS

Finish: White, black, brushed nickel

Interchangeable trim ring Light direction: Downlight Beam angle: 40 degrees

Catalog Number
Project Number
Туре

3" RECESSED DIMMABLE ADJUSTABLE CCT LIGHT RCTG-7W-3IN





Diameter	Height		
Module - 2.48 in (63 mm) Trim - 3.34 in (85 mm) Cutout (min) - 2.75 in (70 mm) Cutout (max) - 2.88 in (73 mm)	1.77 in (45 mm)		

Example: RCTG-7W-3IN-WH

Model	Power	Voltage	Trim Size	Finish	
RCTG	7W 696-784 lm	110-130 VAC	3IN	WH White	
				B Black	
				N Brushed Nick	kel



TRIM OPTIONS



BRUSHED NICKEL BLACK WHITE

RECESSED LIGHT AND DRIVER





PHOTOMETRICS

