

CALCILANE BADIGEON (WASH)



L I M E W A S H

APPLICATION

- Stir well before use

TRADITIONAL FINISH (matt brushed)

- Apply **CALCILANE BADIGEON** a fresco (on fresh render) or a secco (on dried render), diluted with 10% to 30% water (according to the desired consistency), using a brush with long natural bristles, in at least 2 cross-lapped coats applied with approximately 12 hours between coats.
- The 1st coat is always more dilute than the second.

In order to maintain the matt finish, do not apply too thickly and avoid over-working the product.

OLD-LOOK FINISH (decoratively structured, brushed, sponged, stamped, tooled surfaces, etc.)

- Over the dry traditional finish, apply a 3rd coat with a mixture of 1 volume of **CALCILANE BADIGEON** diluted with 5 volumes of **CALCILANE FOND** and adjust the consistency with water according to the desired texture and effect.

The subtle effects obtained are a natural characteristic for which lime coatings are renowned.

PATINATED FINISH for harmonised hues and an appearance of chromatic depth

- Dilute **CALCILANE BADIGEON** with a mixture of 1 volume of **CALCILANE FOND** to 1 volume of water until you achieve the desired consistency and transparency.

Superimposing different colours increases the chromatic depth.

FINISHING ON LIME AND GYPSUM MORTAR

• A fresco (on fresh render):

Apply **CALCILANE BADIGEON** within 48 hours of the finishing coat of render, which should be evenly dampened prior to covering.

The product is brushed on in two cross-lapped coats with 24 hours between coats according to the weather conditions. The first coat will be diluted to 50% and the second to 20%.

• A secco (on dry render):

After preparing the substrate, brush on in two cross-lapped coats applied with at least 24 hours between coats.

The first coat will be diluted to 50% and the second to 20%. In dry, sunny and/or windy weather, it may be necessary to dampen the first coat slightly.

CONSUMPTION

- **Approximately 0.4 kg/m² for 2 coats applied by brush, varying according to the condition of the substrate and the desired appearance.**
- **Approximately 0.09 kg/m² for a patinated effect.**

INSTRUCTIONS FOR USE

- Clean off any splashes of the product immediately to prevent the risk of lime stains.
- Prior to application and throughout the works, protect joinery, metal parts and glass.
- Protect face walls from wind, rain, fog and spray during the entire duration of works and for at least 3 days after application.
- Product is sensitive to moisture, fog and condensation which promote the formation of efflorescence and cause colours to fade.
- Application temperature of between 5°C and 30°C. Do not apply in hot, dry winds, in rainy or foggy weather or onto substrates affected by frost.
- Irritant: wear gloves and protective glasses. In the event of accidental contact with the eyes or skin, wash IMMEDIATELY with copious amounts of clean water and consult a specialist.

PACKAGING

25 kg bucket.
5 kg bucket.

SHELF LIFE

12 months from the date of manufacture in its original packaging, unopened, and stored protected from the damp.

WARRANTY

■ Manufacturer's P.L.

The purpose of this data sheet is to provide information on the properties of the product. The information herein is based on our current knowledge. It is up to the user to check on the suitability of the product for the desired usage and to check whether this sheet has been replaced by a more recent edition.

TECHNICAL ASSISTANCE: ParexGroup S.A. provide information and assistance to companies that request it for starting a project in order to clarify specific requirements for the implementation of the product (or process). This assistance cannot be assimilated into either the design stage of the project, or the acceptance of the substrates, or to a check on the implementation rules.

2012 Technical Documentation

PAREXGROUP S.A. / Facade Department - 19 place de la Résistance - 92446 Issy les Moulineaux Cedex
Tel. (33) 01 41 17 45 45 - Fax (33) 01 41 17 19 55

PAREXLANKO