



### Features:

- Interchangeable AC Heads
- DOE Level VI Efficiency
- Overcurrent Protection
- Short circuit Protection
- RoHs Compliant
- EN62368 Approved
- 1 year Warranty

Model	ECM-65-12	ECM-65-24	ECM-65-48	
<b>Output</b>	DC Voltage	12vdc	24vdc	48vdc
	Rated Current	5amp	2.5amp	1.25amp
	Current Range	0-5amp	0-2.5amp	0-1.25amp
	Rated Power	60 Watt	60 Watt	60 Watt
	Ripple & Noise	240mVp-p max	240mVp-p max	240mVp-p max
	Output Regulation	±5%	±5%	±5%
	Output Connector	2.1x5.5x12mm C+ve	2.1x5.5x12mm C+ve	2.1x5.5x12mm C+ve
<b>Input</b>	Voltage Range	90-264vac	90-264vac	90-264vac
	Frequency Range	47-63Hz	47-63Hz	47-63Hz
	Input Current	1.2amp Max	1.2amp Max	1.2amp Max
	Inrush Current	40amp Max	40amp Max	40amp Max
	Standby Power	0.1W Max	0.1W Max	0.1W Max
	Leakage Current	0.25amp Max	0.25amp Max	0.25amp Max
	Input Connector	UK, EU, US & AUS AC Heads	UK, EU, US & AUS AC Heads	UK, EU, US & AUS AC Heads
<b>Environment</b>	Operating Temp	0°C~40°C	0°C~40°C	0°C~40°C
	Cooling	Convection	Convection	Convection
	Temperature Coefficient	0.05%/°C	0.05%/°C	0.05%/°C
	Humidity	5~95%RH(non-condensing)	5~95%RH(non-condensing)	5~95%RH(non-condensing)
	Storage Temp	-20°C~+80°C	-20°C~+80°C	-20°C~+80°C
<b>Safety &amp; EMC</b>	Safety Standards	UL/CUL 62368-1, GS/TUV EN62368-1, SAA AS/NZ 61558.2		
	EMC Emissions	EN55032,EN55035, FCC Part 15 Class B		

