



# TrueConnect - Termination Loads

## DESCRIPTION:

Provides for the termination of unused ports or connections within an RF system. Different power ratings are available, as well as different connector options

 <table border="1"> <tr> <td>Part Number</td> <td>2-DC3G-TL-NM</td> <td>VSWR</td> <td>≤1.15:1</td> </tr> <tr> <td>Connector</td> <td>N- Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>2</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	2-DC3G-TL-NM	VSWR	≤1.15:1	Connector	N- Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	2	Radiator	Aluminum	 <table border="1"> <tr> <td>Part Number</td> <td>2-DC3G-TL-DM</td> <td>VSWR</td> <td>≤1.15:1</td> </tr> <tr> <td>Connector</td> <td>7/16 DIN Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>2</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	2-DC3G-TL-DM	VSWR	≤1.15:1	Connector	7/16 DIN Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	2	Radiator	Aluminum
Part Number	2-DC3G-TL-NM	VSWR	≤1.15:1																																						
Connector	N- Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	2	Radiator	Aluminum																																						
Part Number	2-DC3G-TL-DM	VSWR	≤1.15:1																																						
Connector	7/16 DIN Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	2	Radiator	Aluminum																																						
 <table border="1"> <tr> <td>Part Number</td> <td>10-DC3G-TL-NM</td> <td>VSWR</td> <td>≤1.15:1</td> </tr> <tr> <td>Connector</td> <td>N- Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>10</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	10-DC3G-TL-NM	VSWR	≤1.15:1	Connector	N- Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	10	Radiator	Aluminum	 <table border="1"> <tr> <td>Part Number</td> <td>10-DC3G-TL-DM</td> <td>VSWR</td> <td>≤1.15:1</td> </tr> <tr> <td>Connector</td> <td>7/16 DIN Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>10</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	10-DC3G-TL-DM	VSWR	≤1.15:1	Connector	7/16 DIN Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	10	Radiator	Aluminum
Part Number	10-DC3G-TL-NM	VSWR	≤1.15:1																																						
Connector	N- Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	10	Radiator	Aluminum																																						
Part Number	10-DC3G-TL-DM	VSWR	≤1.15:1																																						
Connector	7/16 DIN Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	10	Radiator	Aluminum																																						
 <table border="1"> <tr> <td>Part Number</td> <td>10-DC3G-TL-41M</td> <td>VSWR</td> <td>≤1.15:1</td> </tr> <tr> <td>Connector</td> <td>4.1/9.5 - Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>10</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	10-DC3G-TL-41M	VSWR	≤1.15:1	Connector	4.1/9.5 - Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	10	Radiator	Aluminum	 <table border="1"> <tr> <td>Part Number</td> <td>10-DC3G-TL-43M</td> <td>VSWR</td> <td>≤1.15:1</td> </tr> <tr> <td>Connector</td> <td>4.3/10 - Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>10</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	10-DC3G-TL-43M	VSWR	≤1.15:1	Connector	4.3/10 - Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	10	Radiator	Aluminum
Part Number	10-DC3G-TL-41M	VSWR	≤1.15:1																																						
Connector	4.1/9.5 - Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	10	Radiator	Aluminum																																						
Part Number	10-DC3G-TL-43M	VSWR	≤1.15:1																																						
Connector	4.3/10 - Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	10	Radiator	Aluminum																																						
 <table border="1"> <tr> <td>Part Number</td> <td>50-DC3G-TL-NM</td> <td>VSWR</td> <td>≤1.15:1</td> </tr> <tr> <td>Connector</td> <td>N- Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>50</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	50-DC3G-TL-NM	VSWR	≤1.15:1	Connector	N- Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	50	Radiator	Aluminum	 <table border="1"> <tr> <td>Part Number</td> <td>50-DC3G-TL-DM</td> <td>VSWR</td> <td>≤1.15:1</td> </tr> <tr> <td>Connector</td> <td>7/16 DIN Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>50</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	50-DC3G-TL-DM	VSWR	≤1.15:1	Connector	7/16 DIN Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	50	Radiator	Aluminum
Part Number	50-DC3G-TL-NM	VSWR	≤1.15:1																																						
Connector	N- Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	50	Radiator	Aluminum																																						
Part Number	50-DC3G-TL-DM	VSWR	≤1.15:1																																						
Connector	7/16 DIN Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	50	Radiator	Aluminum																																						
 <table border="1"> <tr> <td>Part Number</td> <td>50-DC3G-TL-41M</td> <td>VSWR</td> <td>≤1.15:1</td> </tr> <tr> <td>Connector</td> <td>4.1/9.5 - Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>50</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	50-DC3G-TL-41M	VSWR	≤1.15:1	Connector	4.1/9.5 - Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	50	Radiator	Aluminum	 <table border="1"> <tr> <td>Part Number</td> <td>50-DC3G-TL-43M</td> <td>VSWR</td> <td>≤1.15:1</td> </tr> <tr> <td>Connector</td> <td>4.3/10 - Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>50</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	50-DC3G-TL-43M	VSWR	≤1.15:1	Connector	4.3/10 - Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	50	Radiator	Aluminum
Part Number	50-DC3G-TL-41M	VSWR	≤1.15:1																																						
Connector	4.1/9.5 - Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	50	Radiator	Aluminum																																						
Part Number	50-DC3G-TL-43M	VSWR	≤1.15:1																																						
Connector	4.3/10 - Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	50	Radiator	Aluminum																																						
 <table border="1"> <tr> <td>Part Number</td> <td>100-DC3G-TL-NM</td> <td>VSWR</td> <td>≤1.25:1</td> </tr> <tr> <td>Connector</td> <td>N- Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>100</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	100-DC3G-TL-NM	VSWR	≤1.25:1	Connector	N- Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	100	Radiator	Aluminum	 <table border="1"> <tr> <td>Part Number</td> <td>100-DC3G-TL-DM</td> <td>VSWR</td> <td>≤1.25:1</td> </tr> <tr> <td>Connector</td> <td>7/16 DIN Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>100</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	100-DC3G-TL-DM	VSWR	≤1.25:1	Connector	7/16 DIN Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	100	Radiator	Aluminum
Part Number	100-DC3G-TL-NM	VSWR	≤1.25:1																																						
Connector	N- Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	100	Radiator	Aluminum																																						
Part Number	100-DC3G-TL-DM	VSWR	≤1.25:1																																						
Connector	7/16 DIN Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	100	Radiator	Aluminum																																						
 <table border="1"> <tr> <td>Part Number</td> <td>100-DC3G-TL-41M</td> <td>VSWR</td> <td>≤1.25:1</td> </tr> <tr> <td>Connector</td> <td>4.1/9.5 - Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>100</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	100-DC3G-TL-41M	VSWR	≤1.25:1	Connector	4.1/9.5 - Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	100	Radiator	Aluminum	 <table border="1"> <tr> <td>Part Number</td> <td>100-DC3G-TL-43M</td> <td>VSWR</td> <td>≤1.25:1</td> </tr> <tr> <td>Connector</td> <td>4.3/10 - Male</td> <td>Operating temperature - °F</td> <td>-35 to +185</td> </tr> <tr> <td>Frequency Range</td> <td>DC-3 GHz</td> <td>Inner Plating</td> <td>Silver</td> </tr> <tr> <td>Impedance (Ω)</td> <td>50</td> <td>Body Plating</td> <td>Black</td> </tr> <tr> <td>Power Rating (W)</td> <td>100</td> <td>Radiator</td> <td>Aluminum</td> </tr> </table>	Part Number	100-DC3G-TL-43M	VSWR	≤1.25:1	Connector	4.3/10 - Male	Operating temperature - °F	-35 to +185	Frequency Range	DC-3 GHz	Inner Plating	Silver	Impedance (Ω)	50	Body Plating	Black	Power Rating (W)	100	Radiator	Aluminum
Part Number	100-DC3G-TL-41M	VSWR	≤1.25:1																																						
Connector	4.1/9.5 - Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	100	Radiator	Aluminum																																						
Part Number	100-DC3G-TL-43M	VSWR	≤1.25:1																																						
Connector	4.3/10 - Male	Operating temperature - °F	-35 to +185																																						
Frequency Range	DC-3 GHz	Inner Plating	Silver																																						
Impedance (Ω)	50	Body Plating	Black																																						
Power Rating (W)	100	Radiator	Aluminum																																						