

# TECHNICAL DATASHEET

# 505U000002

Rev.00



## FEATURES:

- Extremely light and encircling
- Elastic structure, extremely flexible and resistant
- New temple for a better ergonomoy
- Optimal comfort and fit thanks to the soft adjustable nosepad
- Neck cord included in the packaging

## FRAME FEATURES:

Frame Typology	<b>Spectacle</b>
PPE field of view	<b>&gt;40°</b>
Temple adjustment	-
Weight (g)	<b>23</b>
Size (mm)	<b>137 117</b>
Material Features	<b>Anallergic</b>

## FEATURES OCULARS/LENSES:

Ocular/Flip-up Material	<b>Polycarbonate</b>
Colour	<b>Smoke</b>
Technical Treatment	<b>Antiscratch</b>
Aesthetic Treatment	-
Thickness [mm](+/- 0.1)	<b>2.3</b>
Curvature	<b>Base 9 Spheric</b>
Optical Class	<b>1</b>
UV Protection	<b>400 nm</b>
Spare Parts	-
VLT% (+/-5%)	<b>16,5</b>

## MARKING DATA:

Standard References	<b>EN166 EN170 EN172</b>
Frame Marking	<b>Mod.505U U EN166 FT CE</b>
Ocular/Flip-up Marking	<b>2C-3/5-3.1 U 1 FT CE</b>

## APPLICATION FIELDS

Protection against high-speed particles 45 m/s - low energy (F); Protection against high-speed particles at extreme temperatures (T)

Notes

