





1. PATTERN AND REPEAT



2. LAYOUT SUGGESTIONS



SPECIFICATIONS

WOOD TILE CONSTRUCTION:

Engineered wood. 4mm wear layer over 9 ply substrate.

THICKNESS:

5/8 inches.

REPEAT:

2 Tiles: .68 SF I Right & I Left.

BOX QUANTITY:

20.4 SF per box. 60 tiles total per box/ 30 repeats.

COVERAGE PER TILE: .34 SF per tile.

INSTALLATION:

Glue down. (See installation guidelines) Wood tiles are NOT provided on mesh or panel backing.

USAGE:

Warranted for Commercial or Residential walls & ceilings. Not suitable for areas exposed to running water: inside showers, etc. Not suitable for outdoor applications.

Not suitable for flooring.

LEADTIME:

6-8 weeks for production. Expedited options available upon request for an upcharge.

PRICING:

Polished Amber

Dolphin

Varies by pattern & wood species. Multiple stain selections do not affect pricing.

Smokey Quartz

FIRE RATING: Class C. (Class B available upon request)

STAINING SYSTEM:

Rubio Monocoat hard oil finish - no VOC. Available unfinished.

LEED CREDITS:

2009 NC/CI MR Credit 5 - Regional Materials 2009 NC/CI IEQ Credit 4.1-4.4 - Low Emitting Finish ***This product may contribute to the achievement of LEED credits, although JBC makes no guarantees of representation of such.

CAD PATTRNS AVAILABLE UPON REQUEST. Contact your local JBC representative.

3. SPECIES





4. STA	INS								
AVAILABLE ON WHITE OAK SPECIES									
	1							AN	
Polished Amber	Dolphin	Smokey Quartz	Black Onyx	Grey Moonstone	Pickled Pearl	Mist	Gris	Slate	Sapphire
AVAILABLE ON WALNUT SPECIES:									
					1 KA				

Grey Moonstone Pickled Pearl

Test I and the second

Mist

Sapphire

Black Onyx