
rustic **PROJECTION COLLECTION FOR WALLS & CEILINGS**



1. PATTERN AND REPEAT

2. LAYOUT SUGGESTIONS







RANDOM

GRADIENT

SPECIFICATIONS

WOOD TILE CONSTRUCTION:

End grain - solid wood split block.

THICKNESS:

4 Depths: 1/2", 5/8", 3/4" and 1"

REPEAT:

4 Tiles: .34 SF I of each depth unless specified otherwise. Not suitable for flooring.

BOX QUANTITY:

17 SF per box. 200 tiles total per box/ 50 repeats.

COVERAGE PER TILE:

.085 SF per tile.

INSTALLATION:

Glue down. (See installation guidelines) Wood tiles are NOT provided on mesh or panel backing.

USAGE:

Warranted for Commercial or Residential walls & ceilings. Not suitable for areas exposed to running water: inside showers, etc. Not suitable for outdoor applications.

LEADTIME:

6-8 weeks for production. Expedited options available upon request for an upcharge.

PRICING:

Varies by pattern & wood species. Multiple stain selections do not affect pricing.

FIRE RATING:

Class A. Documentation available upon request.

STAINING SYSTEM:

Rubio Monocoat hard oil finish - no VOC. Finished on 5 sides. Also available unfinished.

LEED CREDITS:

2009 NC/CI MR Credit 5 - Regional Materials 2009 NC/CI IEQ Credit 4.1-4.4 - Low Emitting Finish NC MR Credit 3/ CI MR Credit 4 - Recycled Content ***This product may contribute to the achievement of LEED credits, although JBC makes no guarantees of representation of such.

CAD PATTRNS AVAILABLE UPON REQUEST. Contact your local JBC representative.

Silver Granite

Pale Parchment

3. END-GRAIN SPECIES





Walnut

White Oak

4. STAINS

AVAILABLE ON ASH, SOUTHERN MAPLE & WHITE OAK SPECIES



Golden Grain