
# sextant






## 1. PATTERN AND REPEAT

# 2. LAYOUT SUGGESTIONS





# SPECIFICATIONS

### WOOD TILE CONSTRUCTION:

Engineered wood.

4mm wear layer over 9 ply substrate.

### THICKNESS:

5/8 inches.

### REPEAT:

N/A

### **BOX QUANTITY:**

22.62 SF per box. 78 tiles total per box.

### COVERAGE PER TILE:

.29 SF per tile.

### INSTALLATION:

Glue down. (See installation guidelines)

Wood tiles are NOT provided on a mesh or panel backing.

Warranted for Commercial or Residential floors, walls &

Not suitable for areas exposed to running water: inside

Not suitable for outdoor applications.

### LEADTIME:

6-8 weeks for production.

Expedited options available upon request for an upcharge.

Varies by pattern & wood species. Multiple stain selections do not affect pricing.

### FIRE RATING:

Class C. (Class B available upon request)

### STAINING SYSTEM:

Rubio Monocoat hard oil finish - no VOC. Available unfinished.

### LEED CREDITS:

2009 NC/CI MR Credit 5 - Regional Materials 2009 NC/CI IEQ Credit 4.1-4.4 - Low Emitting Finish

\*\*\*This product may contribute to the achievement of LEED credits, although JBC makes no guarantees of representation of such.

### CAD PATTERNS AVAILABLE UPON REQUEST.

Contact your local JBC representative.

### 3. SPECIES



Plain White Oak Walnut



Quarter White

## 4. STAINS





Polished Amber

























AVAILABLE ON WALNUT SPECIES:



Dolphin







Smokey Quartz Black Onyx Grey Moonstone Pickled Pearl









Sapphire