

D

DIVINE
FLOORING

T K O



The undefeated champion in dimensional stability.

Outperforming the competition in tests of extreme temperature and humidity. Scoring a knockout in great looks as well, with a hot new colour palette.

COLOUR RANGE

EW7001 Bare Knuckle Maple	EW7004 Lightweight Maple	EW7008 Right Hook Oak	EW7010 Southpaw Oak
EW7002 Haymaker Maple	EW7006 Hammer Fist Oak	EW7009 Sucker Punch Oak	EW7011 Uppercut Oak
EW7003 Left Hook Maple	EW7007 Heavyweight Oak		

DETAILS

Product Category:	Engineered Hardwood	Finish:	Pro-Tect Super Matte
Species:	Oak, Maple	Texture:	Brushed (Oak), Smooth (Maple)
Width:	5" (127 mm)	Gloss Level:	Super Matte (+-10%)
Thickness:	3/4" (18 mm)	Grade Level:	On / Above / Below
Wear Layer Thickness:	2 mm (after sanding), dry, solid sawn veneer	Edge Detail:	4-Sided Micro-V Bevel
Core/back Layer Thickness:	16 mm	Installation:	Nail / Glue / Float
Length:	400 mm (15 3/4") – 1800 mm (70 7/8") 900 mm (35 3/8") average	Over Radiant Heat:	Yes (must follow manufacturer's installation recommendations)
		Warranty:	35 Year Residential (Wear & Structural) 3 Year Commercial Wear (Light)

AVAILABLE MOULDINGS

Nail / Glue Down Installation • Flush Mouldings



SQUARE STAIR NOSE

94"



REDUCER

94"



END-CAP

94"



FLUSH MOUNT VENT

4" x 10"



TOP MOUNT VENT

4" x 10"

Float Installation • Overlap Mouldings



STAIR NOSE

94"



REDUCER

94"



END-CAP

94"



T-MOLD

94"



QUARTER ROUND

94"



TOP MOUNT VENT

4" x 10"