



INTERIOR  
EXTERIOR



# GELCOAT RESTORER

## COLOR RESTORER

<b>Product description</b>	<p>GELCOAT RESTORER is a deep penetrating oil that penetrates deep into gelcoat to re-wet the pigment and so restore the dull, faded look of the gelcoat to its original color and lustre; it then dries to a tough, long lasting and flexible finish. GELCOAT RESTORER eliminates the need for expensive waxes and polishes that sit on the surface and dry out quickly.</p>
<b>Properties</b>	<ul style="list-style-type: none"><li>• Restores original color and dries to a tough flexible finish.</li><li>• Long lasting and penetrates deep into gelcoat.</li><li>• Eliminates the need for waxes and polishes that sit on surfaces and dry out quickly.</li><li>• Easy to apply - easy to maintain.</li></ul>
<b>Basic uses</b>	<ul style="list-style-type: none"><li>• Works on gelcoat, plastic, paint, stone.</li><li>• Horizontal or Vertical surfaces.</li></ul>
<b>Technical data</b>	<p><b>Vehicle Type:</b> Alkyd resins.</p> <p><b>Solvent Type:</b> Solvent.</p> <p><b>Viscosity:</b> Fluid.</p> <p><b>Specific Gravity:</b> 0,857 ± 0,05 (68°F - 20°C).</p> <p><b>Physical State:</b> Liquid.</p> <p><b>Solid Content:</b> 33% ± 2.</p> <p><b>Flammability:</b> Not classified as flammable.</p> <p><b>Flash Point:</b> &gt; 140°F (60°C).</p> <p><b>Shelf Life:</b> 2 years minimum in original unopened packaging.</p> <p><b>Container Size:</b> 0.5L (0.53 U.S. QUART), 1L (1.06 U.S. QUART).</p> <p><b>Color:</b> Amber.</p> <p><b>Dry Time:</b> 24 hours, depending on temperature and humidity.</p> <p><b>VOC:</b> Does not exceed 580 g/l (4.84 lb/gal).</p>
<b>Application tools</b>	<ul style="list-style-type: none"><li>• Brush: High quality, natural or synthetic bristle brush.</li><li>• SOFT cloth.</li></ul>
<b>Good application practice</b>	<ul style="list-style-type: none"><li>• Choose an area that can be managed within five minutes. Excess GELCOAT RESTORER that dries on the surface may be removed with MARINE STRIP* per label instructions.</li><li>• Wear protective clothing and gloves.</li><li>• Cover areas you want to protect.</li><li>• Apply between 41°F (5°C) and 95°F (35°C).</li><li>• Do not apply in direct sunlight.</li><li>• Use as is, do not thin.</li></ul>

<b>Application</b>	<ul style="list-style-type: none"> <li>• Rinse the surface with fresh water. Remove dirt and heavy oxidation by scrubbing with DECK CLEANER* per label instructions. Allow surface to completely dry.</li> <li>• Saturate a SOFT cloth with GELCOAT RESTORER and wipe it on.</li> <li>• With a SOFT cloth, wipe off excess within 10 minutes.</li> <li>• Gently polish with a lint-free cloth to a new sheen.</li> </ul>
<b>Coverage</b>	<ul style="list-style-type: none"> <li>• 193 ft<sup>2</sup> (18 m<sup>2</sup>) per litre.</li> <li>• Actual coverage will vary depending on type, age and texture of surface.</li> </ul>
<b>Clean-up</b>	<p>Clean all tools and equipment with mineral spirits while still wet. If allowed to dry, remove with paint stripper.</p> <p><b>NOTE:</b> Any rags, steel wool etc soaked in GELCOAT RESTORER may spontaneously catch fire if improperly discarded. Rags, steel wool etc must be saturated with water after use or placed in a sealed, water filled metal container, before disposing with household waste.</p>
<b>Storage</b>	<ul style="list-style-type: none"> <li>• Left over GELCOAT RESTORER should be transferred to a smaller, airtight, closed metal or glass container.</li> <li>• Keep from freezing and high temperature.</li> </ul>
<b>General information</b>	<p>Every care is taken to ensure that the information provided in this technical data sheet is accurate. <b>OWATROL COATINGS USA</b> is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advise and information please contact our technical department on (954)-929-3905 or email <a href="mailto:info@deksolje.com">info@deksolje.com</a>.</p> <p>The information above is correct at the date of issue.</p>
<b>Safety</b>	<p>Keep out of the reach of children.</p> <p>MSDS available at <a href="http://www.deksolje.com">www.deksolje.com</a>.</p>
<b>Issue date</b>	<p>November 2011.</p>

\* Same manufacturer

