



MODEL 560/560A

SOFT SERVE FREEZER

TWIN TWIST, FREE STANDING, DIGITAL CONTROL



Ideal for **ultra high footfall outlets** to soft serve ice cream, frozen yogurt, gelato or sorbet. Fully loaded with all standard options.



FAST FREEZE DOWN

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption



DIGITAL CONTROL AND DISPLAY

Digital control provides access to system settings and displays critical system information



AUTO PROGRAMMING

Allows automatic switching of operation modes based on preset schedules



STANDBY

Maintains product temperature in both mix hopper and freezing cylinder below 4.4 $^{\circ}$ C (40 $^{\circ}$ F) overnight



HOPPER AGITATOR

Maintain product consistency and prevent product separation



SOFT SYSTEM START

Slow motor start reduces equipment noise and stress on drive train



DIRECT DRIVE TRANSMISSION

Eliminates consumable moving parts and increases transmission efficiency



SAFETY PROTECTIONS

- Low temperature and motor overload shut-offs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating



DEFROST FOR CLEANING

Increases efficiency during cleaning by heating frozen product in cylinder Automatically prevents product overflow after dispense.

POWERFUL AND VERSATILE TWIN TWIST ULTRA HIGH FREE STANDING MODEL FOR ICE CREAM, FROZEN YOGURT, SORBET AND MUCH MORE


MAXIMISE YOUR PROFITS






MODEL S60/S60A

SOFT SERVE FREEZER MACHINE







SPECIFICATIONS

Flavours		2 + Twist		
Freezing Cylinders		2 x 1.7L / 1.8qt		
Mix Hoppers		2 x 12L (10L for A)		
Output Capacity (80 grams)		450 serves/hr		
Clearance Requirements		152mm/6" on back		
WEIGHT	KG/LB (Gravity)	KG/LB	(Pump)	
Net	210 / 467	220 /	489	
Shipping	230/511	240 /	533	
Volume	0.90 CBM / 2	0.90 CBM / 2 8.85 CBF		
DIMENSIONS	NET (MM/IN)	SHIPPING (MM/IN)		
Width	532 / 20.9	660 / 23.6		
Depth	766 / 30.2	830 / 32.7		
Height	1474 / 58.0	1640 / 64.6		
ELECTRICAL	AMP	VOLT	POWER(KW)	
Single Phase	20	NA	NA	
Single Phase	20	NA	NA	

FEATURES

CONTROL SYSTEMS	TWO, DIGITAL
REFRIGERATED HOPPERS	√
HOPPER AGITATOR, OPTIONAL	✓
TEMPERATURE DISPLAY	<u> </u>
STANDBY MODE	✓
AUTO CLOSING DISPENSING VALVES	<u> </u>
DISPENSING SPEED CONTROL	✓
LOW MIX INDICATOR LIGHT & ALARM	✓
LOW TEMPERATURE PROTECTION	√
MOTOR OVERLOAD PROTECTION	✓
HIGH PRESSURE PROTECTION	√
DEFROST & QUICK REFREEZE	√
SOFT START	V
DIRECT DRIVE PUMP (A ONLY)	✓
S60A: PUMP FEED MODEL, AVAILABLE	√
AIR PUMP OPTION, AVAILABLE	✓
INVERTER SYSTEM	<u> </u>