



## LMU-4220™ GPRS/CDMA/HSPA Series

### Enterprise Location Messaging Unit



### EXPERIENCE THE ADVANTAGE

- GSM/GPRS, CDMA, 1xRTT, or HSPA configurations
- Dual reporting 20,000 buffered message log
- Built-in 3-axis accelerometer for driver behavior, motion sensing, hard braking and impact detection
- High sensitivity GPS
- 32 Built-in geo-fences, plus any combination of circle or polygon zones, up to 5400 points
- Garmin<sup>®</sup>, MDT, and other advanced peripherals support
- 2 1-Wire<sup>®</sup> Interfaces
- Power management sleep modes
- Comprehensive I/O
- Switched power serial ports
- 7 inputs, 5 outputs, 4 A/D Inputs
- Over-the-air configuration and firmware download

CalAmp's flagship LMU-4220 product has the features, expandability, and flexibility with the intelligence to meet all customer's needs in fleet management. The LMU-4220 offers a full set of features, comprehensive I/O system and expandable accessories that make it an industry leading value proposition. The LMU-4220 expandability and flexibility lowers the cost of delivering, supporting, and growing fleet management solutions.

#### COMPETITIVE PRICE, COMPETITIVE TECHNOLOGY, COMPETITIVE EDGE

The LMU-4220 is designed to support customers needing an array of vehicle interfaces. For example, the serial ports supply switchable power at selectable voltages to ease the installation of peripheral data devices. The integrated jPOD™ ECU (Engine Control Unit) interface reads and transmits heavy-duty engine condition and performance data such as engine temperature along with the fault codes to provide the best possible real-time picture of vehicle health. In addition, the LMU-4420 offers a WiFi version as an alternate broadband communication.

#### FLEXIBILITY

The LMU-4220 employs CalAmp's industry leading on-board alert engine, PEG™ (Programmable Event Generator). This advanced engine monitors external conditions and supports customer-defined exception-based rules to help meet the needs of your application. PEG™ continuously monitors the vehicle environment and responds instantaneously to pre-defined threshold conditions related to time, date, motion, location, geo-zone, input and other even combinations. With PEG™, your unique application will meet demanding customer requirements. This behavior can be programmed by CalAmp before shipment, at a customer's facility, or over-the-air once the unit has been fielded.

#### OVER-THE-AIR SERVICEABILITY

The LMU-4220 also leverages CalAmp's industry leading over-the-air device management and maintenance system, PULS™ (Programming, Updates, and Logistics System). Configuration parameters, PEG rules, and firmware can all be updated over-the-air. PULS™ offers out-of-the-box hands free configuration and automatic post-installation upgrades. You can also monitor unit health status across your customers' fleets to quickly identify issues before they become expensive problems.

# LMU-4220 SPECIFICATIONS

## GENERAL

Communication Modes	GPS
Data Support	SMS and UDP packet data
Location Technology	50 channel GPS (With SBAS)
Operating Voltage	12 and 24 volt vehicle systems

## GPS

Location Technology	GPS
Enhancement Technology	SBAS: WAAS, EGNOS, MSAS, GAGAN
Tracking Sensitivity	-162 dBm
Acquisition Sensitivity	-147 dBm
Location Accuracy	2.0m
Kick Start	3 seconds @ -130 dBm
AGPS capable	

## CELLULAR

Data Support	SMS, GPRS, CDMA 1xRTT HSPA packet data	
Operating Bands (MHz)		
GSM/GPRS	850/900/1800/1900	
CDMA/1XRTT	850/1900	
HSPA/UMTS	800(VI)/850(V)/900(VII)/ 1700(IV)/1900(II)/2100(I)	
Transmitter Power		
GSM/GPRS	850/900	32.5 dBm
	1800/1900	29.3 dBm
	850	24 dBm
CDMA/1XRTT	1900	23 dBm
HSPA/UMTS	(all bands)	23 dBm
HSPA data rates	5.6 Mbps upload/ 7.2 Mbps download	
HSPA Fallback	EDGE/GPRS/GSM quad band EDGE MCS1-MCS9 3GPP Release 6	

## COMPREHENSIVE I/O

Digital Ignition Inputs	1 fixed bias
Digital Inputs	7 (high/low selectable 0-30 VDC)
Digital Outputs	5 (open collector relay 150mA)
Current Limited Outputs	2 (20mA)
A/D Inputs	4 (0-30 VDC, +/- 0.1V accuracy)
1-Wire® Interface	2 (driver ID, temperature sensors)
Status LED's	GPS and Cellular

## OPTIONAL CONFIGURATIONS

WiFi	802.11 b/g/i
jPOD™ Truck ECU	J1708, J1939

### About CalAmp

CalAmp Corp. (NASDAQ: CAMP) is a proven leader in providing wireless communications solutions to a broad array of vertical market applications and customers. CalAmp's extensive portfolio of intelligent communications devices streamline otherwise complex machine-to-machine (M2M) deployments. These solutions enable customers to optimize their operations by collecting, monitoring and efficiently reporting business critical data and desired intelligence from high-value remote assets. For more information, please visit [www.calamp.com](http://www.calamp.com).

## ENVIRONMENTAL

Temperature	-30° to +75° C (connected to primary power) -40° to +85° C (storage)
Humidity	95%RH @ 50° C non-condensing
Shock and Vibration	U.S. Military Standards 202G and 810F, SAE J1455
EMC/EMI	SAE J1113

## ELECTRICAL

Input Voltage	7-32 VDC (momentary) 9-30 VDC (start-up, operating)
Power Consumption	3.3mA @ 12V (deep sleep) 25mA @ 12V (radio-active sleep) 28mA @ 12V (SMS+UDP connection, GPS off) 60mA @ 12V (continuous transmit)
Back Up Battery	(Optional) Lithium-Ion 200mAh or 1000mAh (See technical specifications online for operational changes)

## PHYSICAL

Dimensions	3.6" x 3.3" x 1.3", (92 x 83 x 33mm)
Weight	4.5oz, (113g)

## CONNECTORS, SIM ACCESS

SIM Access	Internal
Cellular Ant	SMC (External)
GPS Ant	SMA with tamper monitoring, 3.0V (External)
WiFi Option	RP-SMA
Vehicle Bus Option	DB-15
4-Pin Molex	Power, ground, ignition, A/D
Two 5-Pin Molex 22	Switched power serial
22-Pin Molex	I/O connection

## MOUNTING

Standard tie-wrap, adhesive, velcro, or Screw mounting bracket

## OPTIONAL FEATURES/FUNCTIONS

- External antennas (GPS, cellular, combined GPS/cellular)
- Serial adapter cable RS-232 8-wire (PPP, AT commands, NMEA GPS output)
- Connectorized I/O wiring harnesses
- Built-in backup battery

## CERTIFICATIONS

Fully certified FCC, CE, IC, PTCRB, Applicable Carriers

## DEVELOPMENT SUPPORT OPTIONS

Customized hardware and software development available on request

### CalAmp Corp.

2177 Salk Avenue, Suite 200, Carlsbad, CA 92008

T: 760.438.9010 | F: 760.438.5835

[www.calamp.com](http://www.calamp.com)

CalAmp Corp. | [www.calamp.com](http://www.calamp.com)

© 2015 CalAmp. Rev: 5.27.15

All specifications are typical and subject to change without notice

