

CASAMBI LIGHT CONTROL CBU-PWM4 IP65



CASAMBI
READY

IP65

CE

Technical data	CCT, RGB, RGB+W, 1..4 CH
Part no.	808885
Type	DIBTPRO14 - 144
Power supply input	12..24 Vdc
Radio signal	2,4..2,483 GHz; 4 dBm
Max. output power	72 W
Max. output power	144 W
PWM frequency	~ 400 Hz
Ambient temperature (ta)	20..+45 °C
Rated Max. temp. (tc)	75 °C
Degree of Protection	IP 65
Dimensions	100 x 37 x 24 mm <i>without cable</i>

LED dimmer with IP65 Protection, easily operated by smartphone or tablet (Apple, Android) with the CASAMBI app

For LED strips and other modules for constant voltage

For up to 4 channels (colour mixture or single light sources) freely configurable

Free App from CASAMBI (Apple/Android):

- control of brightness and light colour
- configuration of luminaires and luminaires networks
- creation of scenes and animations (colour gradients)
- automatic detection of new devices
- intelligent timer and gallery functions
- protection settings of your luminaires network ("just me", "with password",...)

You can setup a gateway, but it is not necessary

Integrated antenna

drawing: grey marking, do not cover with metal case)

Fixed rubber connection cables, each 15 cm

Protection class: 3

Pollution degree: 1

Do not insert switches into the secondary circuit!

App for
iOS



App for
Android



* Parameters tolerance +/- 7%