

THE MODBUS ECOSYSTEM



DLD1248-1CV-MODBUS

1Channel
12-48V
Output current: 8A
PWM 300/ 600/ 1200 Hz
MODBUS RTU, Push, 0-10, 1-10,
Potentiometer

DLD1248-4CH-MODBUS

Available both in CV and CC

4 Channels
12-48V
CV Output current: 5A (max 20A TOTAL)
CC Output current: 0,25/0,70 mA (max 2,8A TOTAL)
PWM 300/ 600/ 1200 Hz
MODBUS RTU, Push, 0-10, 1-10, Potentiometer
Dip-switches for an easy configuration

DLD1248-4RL-MODBUS

4 Relay driver output
12-48V
CV Output current: 0,5mA (max 2A TOTAL)
MODBUS RTU, 4x Push, 0-10, 1-10, Potentiometer
Dip-switches for an easy configuration

DLD1248-12CV-MODBUS

12 Channels
12-48V
CV Output current: 2A (max 20A TOTAL)
PWM 300/ 600/ 1200 Hz
MODBUS RTU, Push, 0-10, 1-10, Potentiometer
Dip-switches for an easy configuration

DGM series

Multi-channels
12-48V
Server Gateway
Ethernet, Dali, Dmx, Modbus
Typically custom w/
annex client's web interface