Profile HR-MAX-T

Ref. A01827







- Mounting track
- Easy servicing of the HR-MAX Profile
- For indoor|outdoor ground installation
- Compatibility with the HR-MAX-TW mounting track
- High mechanical resistance

APPLICATION

- makes mounting and service of the HR-MAX profile easy

MOUNTING

- in the ground, with mounting adhesive
- can be easily connected into runs and systems
- possibility to connect to the HR-MAX-TW profile to make a mounting track with sections for cables and accessories at intervals


ADDITIONAL INFORMATION

- in order to protect the lighting fixture during installation, a TECH-35 protective insert should be used
- standard lengths of KLU $\,$ profiles and covers: 1000 mm (tolerance \pm 1.5 mm) and 2005 mm / 3010 mm (tolerance \pm 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance \pm 5 mm)
- when choosing a di erent length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLU



TECHNICAL DRAWING

1:2



TECHNICAL SPECIFICATIONS

Material	aluminum	
Color	silver non anodized	
Profile cross-section	rectangular	
Width	37.6 mm	
Height	29.2 mm	
Building type	Outdoor, Commercial, Retail	
Facility zone	communication routes and corridors, wej cia i bramy, parking i gara , driveways	
Can be easily connected into runs	yes	

Length	Ref				
1000 mm	A01827N_1 C1827NA_1				
2005 mm	A01827N_2 C1827NA_2				
3010 mm	A01827N_3 C1827NA_3				

Wired 4 Signs USA +1 (865) 339 4956 info@w4susa.com 7669 Clinton Highway, Powell, Tennessee, 37849 DISTRIBUTED BY







Ref. arch C1827

SAMPLE PROJECTS



RELATED PROFILES > FOR FLOORS



HR-MAX A01829 Ref. arch C1829

RELATED PROFILES > MOUNTING TRACKS



HR-MAX-TW A01828 Ref. arch C1828

RELATED ACCESSORIES > RELATED END CAPS

NAME			MATERIAL	COLOR	REF.
HR-MAX-T-STN	NEW	. 11	stainless steel	silver	C28021N00 24389

Wired 4 Signs USA +1 (865) 339 4956 info@w4susa.com 7669 Clinton Highway, Powell, Tennessee, 37849





Profile HR-MAX-T Ref. A01827







Ref. arch C1827

CLIP HR-MAX C28059C00 Ref. arch 24416

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > TECHNICAL AND PROTECTIVE INSERTS



PROTECTIVE INSERT TECH-35 C24534C02 Ref. arch 17127



