

COSH SHEET

1	IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY	
1.1	Product	Flexoid, Sizoid Gasket Papers
1.2	Description	A gelatin impregnated paper for use as a jointing material within automotive and industrial applications
1.3	Company	TYM Seals & Gaskets Ltd, Unit A Beacon Business Centre, Hopton Park, Devizes, Wiltshire SN10 2EY Tel: (+44) 01380 734510
1.4	Emergency Contact	Product Safety Manager Tel: (+44) 01380 734510
2	COMPOSITION/INFORMATION ON INGREDIENTS	
2.1	Composition	Approximate Composition
	Cellulose fibre	55-65%
	Diethylene glycol	15-25%
	Gelatine	5-15%
	Sugars	5-15%
	Formaldehyde	<0.04%
3	HAZARDS IDENTIFICATION	
3.1	Health Hazards	This paper is not a hazard under foreseeable conditions of use. There are no known environmental hazards associated with the product. The product will burn if ignited and then behave in the same way as a conventional paper.
3.2	Environment	
3.3	Fire Hazards	
4	FIRST AID MEASURES	
	In the event of a cut to the skin from the edge of paper, wash with water and cover as for a normal cut or abrasion. If the product is ingested, seek medical attention. Exposure of the eyes to dust may give rise to irritation. Under these circumstances, irrigate the eyes with copious amounts of clean water. If any irritation persists, seek medical attention.	
5	FIRE FIGHTING MEASURES	
	Any conventional extinguishing medium can be used, taking into account the location of the fire.	
	Not applicable	

6	ACCIDENTAL RELEASE MEASURES	
	Not applicable.	
7	HANDLING AND STORAGE	
	Keep the product in a cool place and avoid low humidity. Loss of product moisture will impair performance.	
8	EXPOSURE CONTROLS/PERSONAL PROTECTION	
	Respiratory and eye protection is recommended if dust is generated during processing of this product. Normal cotton gloves are advised for hand protection.	
9	PHYSICAL AND CHEMICAL PROPERTIES	
9.1	Appearance	Flexible gasket paper of dark brown appearance
9.2	Odour	Slight damp animal odour
10	STABILITY AND REACTIVITY	
	The product is stable under normal conditions of storage. Avoid contact with strong acids, alkalis and steam. Auto-ignition temperature is 270-300°C. Decomposition products are mainly oxides of carbon and water.	
11	TOXICOLOGICAL INFORMATION	
	This product does not represent a risk to health.	
12	ECOLOGICAL INFORMATION	
	This product is not considered to represent a risk to the environment.	
13	DISPOSAL CONSIDERATIONS	
	Incineration of the product is the preferred means of disposal. It may also be sent to landfill. Incineration should be carried out with an adequate supply of air to ensure complete combustion. NB. The user's attention is drawn to the possible existence of regional or national regulations regarding waste disposal.	



Tel: 01380 734510
Fax: 01380 734511
Email: Sales@tym.co.uk

14	TRANSPORT INFORMATION
	This product is not classified as dangerous according to transport regulations.
15	REGULATORY INFORMATION
	This product is not dangerous to health or the environment and is therefore not required to carry any warning labels according to national or EU regulations.
16	OTHER INFORMATION
	Further information on the safety of the product can be obtained from the Product Safety Manager, TYM Seals & Gaskets Ltd, Unit A Beacon Business Centre, Hopton Park, Devizes, Wiltshire SN10 2EY Tel: (+44) 01380 734510

This product safety data sheet is based on the requirements defined in EC Directive 2001/58/EC. However, the product is not classified as dangerous and does not come within the scope of that Directive.

Legal Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and should be used only as a guide. TYM Seals & Gaskets Ltd shall not be held liable for any damage resulting from handling or contact with the above product.