




CONTENTS












MIRROR HOLE MOUNT **INSTALLATION**




This mount is designed to work with motorcycles that have an available 8mm diameter hole intended for an aftermarket mirror. This includes many BMW Motorcycles.



Warning: Installation of the mount should be performed by a qualified technician. Improper installation may interfere with the safety and proper operation of the product and/or vehicle.

- 1. Place the motorcycle on a center stand.
- 2. Using the 5mm Hex Key, fasten the Mounting Post to the bike's mirror hole with the Post Screw and Post Washer as shown in Figure 1. Make sure that the assembly order is such that the Post Washer is contacting the head of the Post Screw.















3. Using the 5/32" Hex Key, loosen the Positioning Screw as shown in Figure 2.





Figure 2

4. Fasten the accessory device or cradle to the top of the *Mounting Plate* utilizing appropriate hardware. The eight "AMPS" pattern holes (1-8) will accommodate #8 or M4 screws. The larger hole (9) will accommodate a 1/4" or M6 screw. Alternatively, double sided adhesive tape or hook and loop fastener may be used.



Mounting Plate Holes

5. Adjust the mount to the desired position and tighten the *Positioning Screw* to lock the assembly in place.



Warning: Verify that the position of the mount and accessory will not interfere with proper operation of the vehicle.



Warning: Make sure all screws and nuts are securely tightened before each ride so that the assembly will not move during use.

Adaptiv Technologies

1639 11th Street Suite 156 Santa Monica, CA 90404 www.AdaptivTech.com 866-ADAPTIV







