

29" Single Solid Door Reach-in Freezer



SML-29F

FEATURES

- ▶ Holds Temperature Between -8°F to 0°F
- ▶ Adjustable PVC Coated Shelves
- ▶ Stainless Steel Construction
- ▶ Preinstalled Casters with Brakes
- ▶ Self-closing Door with 90° Stay Open Feature
- ▶ Electronic Control System
- ▶ Hydro-Carbon R290 Refrigerant
- ▶ cETLus, ETL-S, NSF

This single door reach-in freezer with 23 cu. ft. capacity features a heavy duty stainless steel construction ensuring many years of dependability in even the most difficult commercial settings. Insulated self-closing lockable doors allow CFD models to hold safe temperatures in the hottest kitchens. Includes 3 wire shelves with a versatile shelf slide design. Fits full-size hotel pans in either orientation. Lockable heavy duty wheels come standard. This unit uses HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.



TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	29"L x 32.2"D x 82.5"H
Interior Dimensions	24.4"L x 27"D x 60.3"H
Packaging Dimensions	30.3"L x 34"D x 84.5"H
Net Volume	23 cu. ft.
Unit Weight	282 lb.
Shipping Weight	321 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	7.1
Plug Type	NEMA 5-15P
Power Cord Length	96"

COOLING

Temperature Range	-8°F - 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/2+

CONSTRUCTION

Exterior Material	430 Stainless Steel
Interior Material	304 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	3 Qty: 20.9"L x 25.2"D
Shelf Material	Epoxy Coated Wire
Shelf Load Capacity	120 lb.

DIAGRAM

