

24" Direct Draw Beer Dispenser



SML-DDB-1

FEATURES

- ▶ All stainless steel construction
- ▶ Exterior construction vinyl on steel in black finish
- ▶ Holds temperatures between 33°F and 41°F
- ▶ Electronic control system
- ▶ Adjustable heavy-duty PVC coated shelves
- ▶ Self-closing doors with locks
- ▶ LED interior lighting
- ▶ Hydro-Carbon R290 refrigerant
- ▶ Removable installation board for easy cleaning



TECHNICAL DATA

DIMENSIONS

| | |
|----------------------|---------------------------|
| Exterior Dimensions | 23.5"W x 30.4"D x 38.75"H |
| Interior Dimensions | 19.5"W x 18"D x 28.6"H |
| Packaging Dimensions | 26"W x 32.25"D x 45"H |
| Faucet Height | 10"H |
| Tap Tower Dimensions | 16"H 3" Diameter |
| Working Height | 35.3" |
| Net Volume | 6.5 cu. ft. |
| Unit Weight | 132 lb. |
| Shipping Weight | 176 lb. |

ELECTRICAL

| | |
|-------------------|------------|
| Voltage | 115 |
| Hertz | 60 |
| Phase | 1 |
| Amps | 1.92 |
| Plug Type | NEMA 5-15P |
| Horsepower | 1/6 |
| Power Cord Length | 84" |

COOLING

| | |
|------------------------|----------------------|
| Temperature Range | 33°F ~ 41°F |
| Temperature Controller | Digital |
| Refrigerant | R-290 (Hydro-Carbon) |
| Max Ambient Temp | 90°F |
| Defrost | Automatic |

CONSTRUCTION

| | |
|---------------------|------------------------------|
| Exterior Material | 430 Series Stainless Steel |
| Interior Material | 304 Series Stainless Steel |
| Insulation Material | Foamed-In-Place Polyurethane |
| Number of Taps | 2 |
| Number of Doors | 1 |
| Shelf Material | Epoxy Coated Steel |
| Shelf Load | 90 lb. |

DIAGRAM

Model No. SML-DDB-1

