SUN MING ENTERPRISES LTD.

Newtop Electric Griddle

Electric griddles are designed to be reliable, efficient and accurate. Each 12" section has its own independent temperature Control providing even cooking of a variety of products at the same time.

Product Specification

- . Operate on 208V/240V service, 50/60Hz. Per 12" section of griddle, 3kW at 208V; 4kW at 240V.
- . Two thickness plate, 3/4" (19mm) and 1" (25mm).
 - 3/4"—SML-EG12, SML-EG24, SML-EG36, SML-EG48.
 - 1" ----SML-EG12H, SML-EG24H, SML-EG36H, SML-EG48H.
- . Temperature controlled by snap-action thermostats from 150°F (66°C) up to 450°F (232°C).
- . One grease drawer on 12" 24" 36" models, two grease drawers on 48" models.
- . Hard-wire to an appropriate electrical connection.
- . Stainless steel front and sides.
- . Supplied with 4" (102 mm) legs that are adjustable up to 1.375" (35 mm).
- . Clearance, Side 1", back 1" with wall.



SML-EG12/EG12H

SPECIFICATIONS, DIMENSIONS & SHIPPING INFORMATION

Model	Voltage	kW	Overall Dimensions	Weight	Shipping Dimensions	Gross weight
SML-EG12	208V/240V	3/4	12"L * 32.3"W * 15.7"H	95 LBS	16.3"L * 36"w * 19.3"H	118 LBS
SML-EG12H	208V/240V	3/4	12"L * 32.3"W * 15.7"H	114LBS	16.3"L * 36"w * 19.3"H	136 LBS

	Phase	Single	phase
12" Electric Griddle	Voltage	208	240
	Rated Wattage	3000	4000
	Wire connect		
	Nominal Amps Per Line	14.44	16.66
	For supple use wire size shown or larger	AWG #14	AWG #14

PLAN VIEW







