

Newtop Electric Griddle

Electric griddles are designed to be reliable, efficient and accurate. Each 12" section has its own independent temperature Control providing even cooking of a variety of products at the same time.

Product Specification

- Operate on 208V/240V service, 50/60Hz. Per 12" section of griddle, 3kW at 208V; 4kW at 240V.
- Two thickness plate, 3/4" (19mm) and 1" (25mm).
- 3/4" —SML-EG12, SML-EG24, SML-EG36, SML-EG48.
- 1" ----SML-EG12H, SML-EG24H, SML-EG36H, SML-EG48H.
- Temperature controlled by snap-action thermostats from 150°F (66°C) up to 450°F (232°C).
- One grease drawer on 12" 24" 36" models, two grease drawers on 48" models.
- Hard-wire to an appropriate electrical connection.
- Stainless steel front and sides.
- Supplied with 4" (102 mm) legs that are adjustable up to 1.375" (35 mm).
- Clearance, Side 1", back 1" with wall.



SML-EG36/EG36H

SPECIFICATIONS, DIMENSIONS & SHIPPING INFORMATION

Model	Voltage	kW	Overall Dimensions	Weight	Shipping Dimensions	Gross weight
SML-EG36	208V/240V	9/12	36"L * 32.3"W * 15.7"H	210 LBS	40.6"L * 36"w * 19.3"H	294 LBS
SML-EG36H	208V/240V	9 /12	36"L * 32.3"W * 15.7"H	263 LBS	40.6"L * 36"w * 19.3"H	346 LBS

36" Electric Griddle	Phase	Three phase						Single phase	
	Voltage	208			240			208	240
	Rated Wattage	9000			12000			9000	12000
	Wire connect	X	Y	Z	X	Y	Z	X-Y	X-Y
	Nominal Amps Per Line	25	25	25	28.9	28.9	28.9	43.3	50
	For supple use wire size shown or larger	AWG #12			AWG #10			AWG #6	AWG #6

PLAN VIEW

