



Reach-in Single Solid Swing Door Freezer (Left Door)



**SML-M27FM
(Left Door)**

-17C° to -13C° (0F to-7F)

- **Finest Stainless steel interior and exterior.**
Matching galvanized steel finished back.
- **CFC free refrigerant and foam**
- **Door features:**
Self-closing; Heavy duty pull handle; Magnetic gasket can be replaced without any tool Heating wire installed in cabinet frame to eliminate any condensation.
- **Shelf:** Adjustable, heavy duty PE coated shelves.
- **Rounded corner inner bottom design** for easier cleaning of inside storage.
- **Standard heavy duty casters** make it easy to move and clean underneath.
- **Bottom mounted condensing unit**, sliding out for easy cleaning & service access.
- **Digital thermostat** for accurate control and easy reading.
- **Highly efficient Fan & Compressor** for best cooling performance and durable usage.

Specifications subject to change without notice
Chart dimensions rounded up to the nearest 1/8"

Rough-In Data

Model	Door	Shelf	Capacity (Cu.ft) (L)	External Dimensions (inches) (mm)			N.W. (Lb) (Kg)	G.W. (Lb) (Kg)	Amps	HP	Voltage/Hz	Cord Length (total ft.) (total m)
				W	D	H						
SML-M27FM	2	3	21	26-7/8	32-3/4	81-1/2	269	307	5.13	1/2+	115/60/1	9.8
			594	680	830	2070	122	139			230-240/50/1	3

Specifications subject to change without notice.
Chart dimensions rounded up to the nearest 1/8".



**Plug type 5-15P
Receptacle**



Made in China

SUNMING ENTERPRISES LTD.

Add: #150-6211 Westminster Hwy., Richmond, B.C. V7C 4V4 CANADA
T: (604) 233-0360 F: (604) 304-3032 E-mail: info@sunming.ca
www.sunming.ca