



# Reach-in Semi Solid Swing Door Refrigerator



**SML-M54RM**

## 0C° to 5C° (33F to 41F)

- **Finest Stainless steel interior and exterior.**  
Matching galvanized steel finished back.
- **CFC free refrigerant and foam**
- **Door features:**  
Self-closing, Heavy duty pull handle; Magnetic gasket can be replaced without any tool.
- **Shelf:** Adjustable, heavy duty PE coated shelves.
- **Rounded corner inner bottom design** for easier cleaning of inside storage.
- **Standard heavy duty casters** make it easy to move and clean underneath.
- **LED light** for bright illumination.
- **Bottom mounted condensing unit**, sliding out for easy cleaning & service access.
- **Digital thermostat** for accurate control and easy reading.
- **Highly efficient Fan & Compressor** for best cooling performance and durable usage.

### Rough-In Data

Model	Door	Shelf	Capacity (Cu.ft) (L)	External Dimensions (inches) (mm)			N.W. (Lb) (Kg)	G.W. (Lb) (Kg)	Amps	HP	Voltage/Hz	Cord Length (total ft.) (total m)
				W	D	H						
<b>SML-M54RM</b>	4	6	45	53-7/8	32-3/4	81-1/2	370	419	2.5	1/2+	115/60/1	9.8
			1274	1370	830	2070	168	190			230-240/50/1	3

Specifications subject to change without notice.  
Chart dimensions rounded up to the nearest 1/8".



**Plug type 5-15P  
Receptacle**



**Made in China**

### SUNMING ENTERPRISES LTD.

Add: #150-6211 Westminster Hwy., Richmond, B.C. V7C 4V4 CANADA  
T: (604) 233-0360 F: (604) 304-3032 E-mail: info@sunming.ca  
www.sunming.ca