


FOOD RISING MINI FARM GROW BOX 2.0 ASSEMBLY INSTRUCTIONS (EXPANSION)

Congratulations on receiving your Mini-Farm Grow Box 2.0! My name is Mike Adams, and I developed this system based on the Non-Circulating Hydroponics principles taught by B.A. Kratky at the University of Hawaii.

This is the vastly improved and redesigned 2.0 version of this system, now with fewer parts and a more reliable self-watering system that avoids potential leaks altogether.

Here's a straightforward guide for assembling your Grow Box. You do not need any special tools to assemble this system.



Net pots

Drip Irrigation Tees

1/4" Solid Poly

Micro Tubing (PE) For Drip Irrigation System



ASSEMBLING THE TUBING:

1. Screw the threaded end of the white valve adaptor into float valve. Thread it all the way in, as far as it will go. Finger-tighten firmly. (Do not tighten with tools or you may break it.)



2. Insert either end of 1/4" black irrigation tubing into the free end of white valve adaptor. Make sure the connection is tight so it will not come loose. This process can be made easier by slightly heating the black irrigation tubing with a lighter for 3-5 seconds to soften it.



3. Feed the free end of black irrigation tube through blue PEX pipe.

Affix the blue PEX pipe snugly over the free end of the white valve adaptor by manually pushing it on. It should fit snugly.







4. Feed the free end of the black irrigation tubing and blue PEX pipe through hole on UNDERSIDE of the grow box lid. It should fit snugly and firmly, with some resistance on the PEX pipe. You can adjust the height of the auto-watering by sliding the PEX pipe up or down, effectively placing the float valve at a different height inside the bin.



- 5. Place the lid on the Grow Box.
- 6. Attach the new drip line you received with the expansion kit to the open nozzle on the tee connector. The other end of this drip line connects to the float valve receiver on your new grow box.
- 7. Remove the drip line clamp you placed on the line, allowing the water to flow freely from the water reservoir to both grow boxes.
- 8. Unwrap the plastic of the coconut coir grow media. Place the coconut coir into a separate container or bin (such as a small pail or bucket) and add a few inches of water to the bottom of the container until the coconut coir expands and loosens. This will take 15 20 minutes for the expansion. Once it is fully expanded, you can loosen it by hand to make loose coconut coir media. This is the media which will host your garden seeds.
- 9. Fill your net pots with coconut coir media. Compress it slightly, but not vigorously. The coconut coir should be filled all the way to the top of the net pots, but should not be too tightly compressed. (Roots need loose media to grow well.)
- **10.** Place the net pots containing coconut coir into the holes of the grow box lid. They should fit snugly. Place the lid to the side for now.

ASSEMBLY IS COMPLETE! You now have one water reservoir feeding two grow boxes with water and nutrients. If you wish, you can expand this system to as many as 10 grow boxes from a single water reservoir.

For best results, grow the same type of plants in all grow boxes that are connected to the same reservoir. Be sure to check the pH and nutrient levels of your water reservoir from time to time, making sure they are within the proper range.

The following URL provides easy instructions:

http://bit.ly/1Q0xOa3



TEST THE WATER FLOW:

The Mini-Farm Grow Box is a self-watering system. You never need to add water or nutrients to the grow bin itself. Instead, you add water and nutrients to the water reservoir (the 3.5 gallon pail). If you wish, you can use a larger pail or other container to create a larger water reservoir. One reservoir can feed water and nutrients to 10+ grow bins! Before planting seeds, it is important to test the gravity flow of automatic watering function of the grow box:

- 1. Confirm that you have the float valve installed with the correct orientation inside the grow bin. The float should actuate vertically (up and down) when you gently lift it with your hand. This simulates the rising of the float as the water level rises in the grow box.
- 2. Confirm you have the 1/4" drip line connected securely to the float valve nozzle, with the other end securely inside the water reservoir (white pail).
- 3. Normally you will want to position the water reservoir a few inches higher than the level of the float valve of your grow box. This allows the water to gravity flow down to the level of the float valve. To accomplish this, you may place a 4" brick or a similar-sized object underneath the water reservoir (white pail).
- **4.** Fill the white pail completely with water. You should now observe a slow trickle of water entering the grow box through the tiny hole in the center of the float valve. This is the desired flow you want to see.
- 5. Allow the water to fill the grow bin until the float valve rises sufficiently to block the incoming water flow. At this point, you should have approximately 2 or 3 inches of water in the bottom of the grow bin, and a much higher water level in your water reservoir. Allow this state to remain for a few hours to make sure your float valve really is blocking off the incoming water. If the water level does not rise higher in the grow bin, then you have confirmed the float valve is working to block the incoming water, just as it is designed to do.
 - **TIP:** If you place your water reservoir too high, it will increase the gravity pressure of the water and may cause excess water to be pushed into your grow bin. Do not raise the water reservoir higher than approximately 6" off the level surface where your grow bin is also placed.
- 6. You have now confirmed the full function of the grow system! If you used a high quality water source to begin with, you may now add nutrients directly to the water in the grow bin (only needed once, at the beginning of each new "crop") and also to the water reservoir.



TIP: Acquire a TDS meter (about \$15 on Amazon.com) to test your water for Total Dissolved Solids (TDS) and Electrical Conductivity (EC).

TIP: As a rule of thumb, you will add plant nutrients and CalMag formulas in about a 1:1 ratio to the water, aiming for a TDS number of approximately 1200 - 1500. For more detailed instructions, see FoodRising.org for a comprehensive guide on hydroponic nutrients for various plants.

- 7. You may now place the lid on the grow bin, making sure the bottom half inch or so of each net pot is immersed in the water being held in the grow bin. This assures water reaches the coconut coir and allows your seeds to sprout. Over time, as the water level drops in the grow bin, your plants will grow roots to follow the water down, extending to the bottom of the grow bin where fresh water and nutrients are fed through the float valve.
- 8. You may now plant your favorite seeds! Make sure the system has adequate sunlight and watch Mother Nature perform its food miracles!

Have a suggestion on how we can improve the system? Email us at csr@healthrangerstore.com



Order supplies, fertilizers and expansion kits at HealthRangerStore.com

To place an order by phone, please call: 1-888-959-6415 (USA & Canada)

For all other business inquiries or international calls, please call: **307-222-0422**