



### WAYFARER™ WFA120KA

#### 1.2m Ka-Band Auto Fly-Away

The Norsat WAYFARER™ commercial 1.2m fly-away antenna is a fast deploying, easy-to-use, and compact SATCOM VSAT. This antenna is an excellent choice for commercial applications in various industries.

The WAYFARER 1.2m fly-away antenna offers excellent rugged and reliable satellite links for remote enterprise, energy, emergency, and media applications.

#### FEATURES

- Easy and intuitive LinkControl™ Interface
- Rugged and lightweight pedestal design
- Lightweight and durable 8 segment carbon fiber reflector
- Fast, simple, tool-free deployment
- Automatic 3-axis acquisition
- 2-case packing solution
- Wide range of Norsat BUC and LNB configurations
- Set up in 5 minutes



#### SPECIFICATIONS

##### ELECTRICAL

Reflector aperture	1.2m
Reflector material	Carbon fiber
Feed configuration	Center
Tx frequency	29.0 to 31.0 GHz
Rx frequency	18.7 to 21.2 GHz
Tx gain	46.4 dBi @ 29.0 GHz
Rx gain	43.3 dBi @ 18.7 GHz
Polarization	Circular
Cross polarization (axial ratio)	1.5 dB
Tx/Rx isolation (port isolation)	Tx ≥ 100 dB
Sidelobe	First sidelobe -14 dB
Azimuth range	± 200°
Elevation range	10° to 90°
Azimuth speed	0.1°/s to 3°/s
Elevation speed	0.1°/s to 3°/s
Polarization speed	0.1°/s to 1°/s
Feed interface	Tx: WR28 Rx: WR42
Power supply	AC110-230V 50/60Hz, rated 200W, 550W max

##### MECHANICAL

Ruggedized weatherproof case

Case 1	Pedestal assembly	Size: 79.5 cm (L) x 51.8 cm (W) x 31 cm (H); Weight: ≤ 32Kg
Case 2	Reflector / feed	Size: 84.5 cm (L) x 62 cm (W) x 49 cm (H); Weight: ≤ 32Kg

##### ENVIRONMENTAL

Wind load - operational	49 km/h
Wind load - survival	100 km/h
Operational Temperature	-30°C to +50°C
Storage Temperature	-50°C to +70°C
Humidity	0-95%
Water ingress	IP 65 (antenna only)



# WAYFARER WFA120KA 1.2M KA-BAND AUTO FLY-AWAY ANTENNA

## HOW TO ORDER

### WFA120KA-NA

KA: Ka-Band

AC POWER PLUG

NA = North America (NEMA 5/15)  
UK = United Kingdom (BS 1363)  
EU = Europe (CEE 7/7)  
IEC = IEC (60320 CIA)  
CN = China (Type I Plug)

#### ACCESSORY OPTIONS

##### BUC OPTIONS

12W  
25W  
50W

##### BUC

ELMTBKA012  
ATOMBKA025  
ATOMBKA050

##### BUC POWER SUPPLY

PS300-AT1(NA/UK/EU/IEC)  
PS300-AT1(NA/UK/EU/IEC)  
PS600-AT1(NA/UK/EU/IEC)

##### BUC M & C CABLE

CABLEM+C-AT10  
CABLEM+C-AT10  
CABLEM+C-AT10

##### BUC MOUNTING BRACKETS

WFA120KUMT-024  
WFA120KUMT-024  
WFA120KUMT-024

##### LNB OPTIONS

LNB

##### SERIES

9000 Series

##### IFL CABLE OPTIONS

IFL Cable (10m)

##### NN-FF

IFL-NN-FF-10

##### NN-NN

IFL-NN-NN-10

##### FN-NN

IFL-FN-NN-10

##### FN-FF

IFL-FN-FF-10

#### MODEM CABLE OPTION (For iDirect product only)

MOD-CABLE

#### INTEGRATION

WF-INT

Assembly, function verification, and pointing test (standard product/RF packages only)



Norsat  
International Inc.

sales@norsat.com  
www.norsat.com