



User Manual

GARDENLINE®
Essentials

50712 **37CC** **PETROL** **CHAINSAW**



Product
Info



+ VIDEO



www.powertoolsupport.com

Read all safety warnings and all instructions
thoroughly before operating this product.

IM ed12; 9/2015

QR codes take you where you want to go quickly and easily

Whether you require product information, spare parts or accessories, details on warranties or aftersales service, or if you want to watch a product demonstration video, our QR codes will take you there in no time at all.

What is a QR code?

A QR-code (QR=Quick Response) is a type of matrix that can be read with a smartphone camera and that contains a link to a website or contact details, for example.

Advantage: You are not required to manually enter a website address or contact details.

How it works

To scan the QR code, all you need is a smartphone with QR codes reader software and an Internet connection*. This type of software can be downloaded for free from your smartphone's app store.

Try it out now

Just scan the QR code with your smartphone and find out more about the Aldi product you have purchased*.

* Depending on your tariff you may be charged for the connection.



For Know How Videos, click on the "Product Assistance" tab, then the "How To Product Videos" link.

Contents

Intended use of the 37cc Petrol Chainsaw	2
Contents of carton	2
Description of Symbols	3
General Safety Warnings	4
Additional Safety Rules for Petrol Chainsaws	7
Parts List	10
Assembly / Installation of the Guide Bar and Chain	12
Filling up with Fuel and Oil	16
Mixing Fuel	17
Fuelling the Chainsaw	18
Adding Chain Oil	18
Starting the Chainsaw	19
Stopping the Chainsaw	20
Checking the Oil supply	20
Adjusting the Carburettor	21
Vibration	22
Re-setting Chain brake	22
Operation Warnings	23
Helpful hints	23
Guard against kickback	24
Chainsaw Applications	25
Bucking Spike	25
Felling a tree	25
Limbing	26
Bucking	27
Pruning	27
Maintenance	28
Replacing Spark Plug	28
Chain Sharpening	29
Guide Bar Wear	30
Guide Bar	29
Air Filter	30
Vents	31
Servicing	31
Transportation & Storage	31
Warranty	32
Environmental Protection	33
What your 3 year warranty means	33
Service Support	33
Accessories	33
Troubleshooting	34
Specifications	35

Pack contents / parts

Congratulations on the purchase of your Gardenline® 37cc Petrol Chainsaw. When you open your packaging, first remove all items and check there are no parts damaged or missing. If you find anything wrong, do not operate the product until the parts have been replaced or the fault has been rectified. Failure to do so could result in serious personal injury.

IMPORTANT INFORMATION.

NOTE: This is a 2 stroke Chainsaw and requires pre-mixing fuel with 2-stroke oil **BEFORE** starting. Fresh unleaded fuel must be used in this unit. Do NOT use Ethanol based fuels.

NOTE: First time users or inexperienced operators pay particular attention to the operation of the Line Trimmer, including details of starting and stopping and correct use of the line trimmer on pages 20 to 26, as well as the maintenance instructions on pages 28-31.

Intended use of the 37cc Petrol Chainsaw

NOTE: This product is for private domestic DIY use only.

It is not suitable for commercial or trade use.

This Chainsaw has been designed for felling small to medium sized trees, cutting firewood and clearing and pruning branches.

Contents of carton

1 x Petrol Chainsaw	1 x Screwdriver
1 x Bucking Spike (fitted)	1 x Sharpening File
1 x 16" Bar and Chain (not fitted)	1 x Instruction Manual
1 x Bar Cover	1 x Quick Start Guide
1 x Fuel Mix Container	1 x Warranty Card & details
1 x Spark Plug / Screwdriver Wrench	1 x Service Agent listing

Description of symbols

The instruction manual, rating plate, or on the product itself, may show these symbols. These represent important information about the product or instructions on its use.



Conforms to relevant standards for electromagnetic compatibility.



Wear hearing protection, eye protection and breathing protection.



Wear safety footwear.



Wear safety gloves.



Warning.



Read these instructions for use carefully.



Choke control



Start position (choke closed).



Run position (choke open).



Use at a distance of at least 15m from other people.



Explosive material.



Extremely hot surface. Do not touch a hot muffler, gear box or cylinder, you may get burned. These parts get extremely hot from operation and remain hot for a short time after the unit is turned off.



Do not put in water.



Fuel Tank



Chain oil tank



Pull recoil starter up and away from unit



Warning! Danger of kickback



Use the chainsaw with 2 hands



Setting the switch to the "O" position will immediately stop the unit.



Chain brake direction



Chain Oil Flow adjustment direction



Noise label rating 85dBA (taken at 7.5 metres)
you must wear ear protection at all times.

General safety warnings



WARNING! Read all safety warnings and all instructions. Failure to follow the warnings and instructions may result in fire and/or serious injury.

The word power tool used in the following warnings and throughout this manual refers to BOTH electrical power tools and ALSO petrol driven power tools.

This unit may not be used by people (including children) with reduced physical, sensory or mental capacities, with a lack of experience and without the appropriate knowledge, unless they are supervised by someone who is responsible for their safety or have been instructed by such a person with regard to how the unit is to be operated. Children should be supervised to ensure that they do not play with the device.

Save all warnings and instructions for future reference

1. Work area safety

- a. **Keep work area clean and well lit.** Cluttered or dark areas invite accidents. Rags, cloths, cord, string and similar items should never be left around the work area.
- b. **Do not operate power tools in explosive environments, such as in the presence of flammable liquids, gases, or dust.** Power tools create sparks, which may ignite the dust or fumes.
- c. **Keep children and bystanders away while operating a power tool.** Distractions can cause the operator to lose control.

2. Personal safety

- a. **Stay alert, watch what you are doing and use common sense when operating a power tool.** Do not use a power tool while you are tired or under the influence of drugs, alcohol or medication. A moment of inattention while operating power tools may result in serious personal injury.
- b. **Use personal protective equipment. Always wear eye protection.** Protective equipment such as dust mask, non-skid safety shoes, hard hat, or hearing protection will reduce personal injuries.
- c. **Prevent unintentional starting.** Ensure the switch is in the “off” position before connecting to power source and/or battery pack, picking up or carrying the tool. Carrying power tools with your finger on the switch or energising power tools that have the switch on invites accidents.
- d. **Remove any adjusting key or wrench before turning the power tool on.** A wrench or key left attached to a rotating part of the power tool may result in personal injury.
- e. **Do not overreach.** Keep proper footing and balance at all times. This enables better control of the power tool in unexpected situations.
- f. **Dress properly. Do not wear loose clothing or jewellery.** Keep your hair, clothing and gloves away from moving parts. Loose clothes, jewellery or long hair can be caught in moving parts.
- g. **If devices are provided for the connection of dust extraction and collection facilities, ensure these are connected and properly used.** Use of dust collection can reduce dust-related hazards.

General safety warnings

3. Power tool use and care

- a. **Do not force the power tools.** Use the correct power tool for your application. The correct power tool will do the job better and safer at the rate for which it was designed.
- b. **Do not use the power tool if the switch does not turn it “on” and “off”.** Any power tool that cannot be controlled with the switch is dangerous and must be repaired.
- c. **Store idle power tools out of the reach of children and do not allow persons unfamiliar with the power tool or these instructions to operate the power tool.** Power tools are dangerous in the hands of untrained users.
- d. **Maintain power tools with care.** Check for misalignment or binding of moving parts, breakage of parts and any other condition that may affect the power tool’s operation. If damaged, have the power tool repaired before use. Many accidents are caused by poorly maintained power tools.
- e. **Keep cutting tools sharp and clean.** Properly maintained cutting tools with sharp cutting edges are less likely to bind and are easier to control.
- f. **Use the power tool, accessories and tool bits etc. in accordance with these instructions, taking into account the working conditions and the work to be performed.** Use of the power tool for operations different from those intended could result in a hazardous situation.

Additional safety rules for Petrol Chainsaws

- Never cut into the ground.
- Never cut into wire fences.
- Never cut into saplings.
- Never cut into prepared wood.
- Use the chainsaw to cut only wood.
- It is advisable to provide a support for the chainsaw when cutting branches. Do not cut using the bar point and beware of branches under tension.
- Children under 18 must not use chainsaws.
- Keep people away from the chainsaw when in use.
- Check the following conditions before beginning work:
 - There should be no people in the felling area.
 - Make sure there is a second person within calling distance.
 - The working area should be free from obstacles.
- Wear suitable clothes which do not hinder movement.
- Use specific protection during operations involving head, hands, feet, eyes and ears.
- It is recommended the use of a helmet with a visor during felling, branch cutting and chopping operations.
- Wear gloves with an external protection when using the chainsaw.
- Use ear protection to prevent hearing injuries.
- Wear safety boots when using the chainsaw.
- During transport the brake must be applied to avoid accidental start-up.
- Do not use the chainsaw in rainy or windy conditions or in poor light.
- Find a suitable position before beginning work.
- When working on slopes, the saw operator must stand beside or above the wood to cut, i.e. felled trees.
- Use the chainsaw holding it firmly with both hands.

- Make a wedge-shaped cut before felling the tree, then the felling cut leaving a hinge for the felling direction.
 - Beware of any falling branches after felling operations.
 - Beware of wood splinters when cutting chopped wood.
 - Ensure your chainsaw is suitable for the job.
 - Never work above shoulder level or reach out to cut a branch: ensure you have stable footing at all times.
 - Do not operate in a hazardous location. Such areas include where there is a risk of explosion of petrol fumes, leaking gas or explosive dust.
 - Do not operate in a confined area. Exhaust gases, smoke or fumes could reach dangerous concentrations.
 - Protect your tool. This chainsaw is NOT WEATHERPROOF and should not be left stored for periods of time where it is exposed to direct sunlight, high ambient temperature and damp, wet or high humidity conditions.
 - Take care not to spill fuel. When refuelling the chainsaw ensure that the motor has been switched off. Prevent the spilling of fuel as this may also ignite with the hot motor. Never refuel whilst the engine is running.
 - Be careful where you store the chainsaw. Store the tool in a dry area away from flammable liquids.
 - Ensure you keep a safe distance from bystanders. The chainsaw emits exhaust fumes.
 - Operating instructions and instructions for common cutting tasks, including the use of personal protection equipment, the need for adequate training and the risks involved when operating the unit should not be undertaken while tired, ill or under the influence of alcohol or other drugs.
- NOTE:** Tree felling should not be attempted by un-trained operators. Ensure you are familiar with the instructions in the manual before undertaking this task.
- Ensure you use a 2-stroke oil / unleaded fuel mix making sure that you mix 40 parts unleaded fuel to 1 part 2-stroke oil. If not, the engine will overheat and cause damage to your chainsaw.
 - Never fill fuel tank indoors. Never fill fuel tank when engine is running or hot. Do not smoke when filling fuel tank.

Kickback safety precautions

- Kickback may occur when the tip of the guide bar touches an object, or when the wood closes in and pinches the saw chain.
- If the bar tip or point contacts, it can produce a rapid reverse reaction, kicking the guide bar up and back towards the operator. This is known as rotational kickback.
- Pinching the saw chain along the top of the guide bar may push the guide bar rapidly back towards the operator. This is known as pinch kickback.
- Either of these reactions can cause loss of control of the saw, resulting in serious personal injury.
- Do not rely exclusively on the safety devices built into your saw. Take the following steps to help avoid accident or injury:
 - Reduce the element of surprise by understanding what causes kickback.
 - Keep a firm grip on the chainsaw using both hands, the right hand on the rear handle and the left hand on the front handle when the motor is running. A firm grip will help maintain control. Do not let go whilst the motor is running.
 - Make sure that the area of operation is free of obstructions. Do not let the point of the guide bar contact a log, branch or any other object.
 - Use high speeds when cutting.
 - Do not overreach or cut above shoulder height.
 - Carefully follow the sharpening and maintenance instructions given in this manual.
 - Use only replacement bars and chains specified by the manufacturer.

DANGER! BEWARE OF KICKBACK!

WARNING! Kickback can lead to dangerous loss of control of the chainsaw and result in serious or fatal injury to the saw operator or to anyone standing close by. Always be alert. Rotational kickback and pinch kickback are major chainsaw operational dangers and the leading cause of most accidents.








- Wear goggles
- Wear earmuffs
- Wear a breathing mask

Parts List

1. Rear handle
2. Safety lever
3. Throttle trigger
4. On/Off switch
5. Oil tank
6. Oil tank cap
7. Fuel tank
8. Fuel tank cap
9. Choke control
10. Recoil starter
11. Top handle
12. Front guard / chain brake
13. Air filter
14. Air filter cover
15. Air filter cover knob
16. Spark plug / Spark plug cover
17. Bucking Spike / Spike Bumper
18. Guide bar
19. Chain
20. Muffler
21. Chain tensioning screw
22. Chain drive side cover
23. Chain drive side cover nut/s (x2)
24. Idling adjustment screw
25. HIGH (Fast) run adjustment screw
26. LOW (Slow) run adjustment screw
27. Chain catcher
28. Drive sprocket
29. Chain tensioner pin
30. Bar cover

31. Fuel mix container
32. Spark plug / Screwdriver wrench
33. Screwdriver
34. Sharpening File
35. Clutch / Brake assembly (internal)





Assembly

Before using your chainsaw, the following assembly is required to be undertaken including assembling the guide bar (18) and chain (19), and fitting the chain drive side cover (22).

Assembly / Installation of the Guide Bar and Chain




WARNING: The chain has sharp edges. Use work gloves for safety.

WARNING: Ensure the engine is switched off when making any adjustments to the chain and bar.


IMPORTANT: The front guard / chain brake (12) must be disengaged when installing the guide bar (18) and chain (19).

NOTE: The chain drive side cover (22) is not assembled on the chainsaw for first use. The instructions below detail the assembly based on the chain drive side cover being assembled on the chainsaw (for replacement in future). For **FIRST** time assembly, start at point 6.

1. Fully loosen the chain (19) tensioning screw (21) by turning in an anticlockwise direction. This loosens the fit of the chain (19) on the guide bar (18) for easier removal. (Fig A)
2. Remove the chain drive side cover by using the supplied spark plug / screwdriver wrench (32) to loosen the chain drive side cover nuts (23). Remove the chain drive side cover nuts (23) and remove the chain drive side cover (22). (Fig B) Ensure the chain brake (12) is NOT engaged.
3. Raise the guide bar (18) and chain (19) slightly in an upwards angle, of approximately 15°, releasing the chain tensioning pin from the bottom hole in the guide bar (18). (Fig C)



4. Push the guide bar (18) down towards the drive sprocket (28), which will result in the chain (19) loosening around the guide bar (18). (Fig D)
5. Remove the chain (19) from the guide bar (18). Once the chain (19) is removed from the guide bar (18), the guide bar (18) can be easily removed by continuing to lift it up and over the 2 threaded studs holding it in position.




First Time Assembly, start here:

6. Place the chain (19) around the drive sprocket (28) loosely with the chain links in the direction shown on the guide bar (18). (Fig E)
7. Insert the guide bar (18) into position over the 2 threaded studs, and on a slight angle upwards, and push the guide bar (18) towards the drive sprocket (28) to easily place the chain (19) around the guide bar (18). (Fig F)

NOTE: AT this point, the chain tensioning pin (29) is NOT engaged on the guide bar (18).




8. Once the chain (19) is loosely in position around the guide bar (18), and ensuring the links are located within the bar guide channel (Fig G), locate the chain tensioning pin (29) in the bottom hole in the guide bar (18) by moving the bar inward or outwards.



NOTE: If the chain tensioning pin (29) does not locate with the bottom hole in the bar guide (18), adjust the chain tensioning screw (21) until the chain tensioning pin (29) is in the correct position to locate. (Fig H)




9. Tighten the chain (19) onto the guide bar (18) by adjusting the chain tension screw (21) in a clockwise direction until the chain (19) just touches the bottom edges of the guide bar (18). (Fig I)




10. Fit the chain drive side cover (22) over the clutch / brake assembly (35) whilst aligning the 2 threaded studs with the 2 hole recesses in the chain drive side cover (22) (Fig J).

NOTE: Check the position of the front guard /brake lever (12) and ensure it is in the full forward position. (Fig K)

11. Secure the chain drive side cover nut/s (23) finger tight. Check again the cover is flat on the surface of the bar.




12. Rotate the chain (19) a few times to ensure the chain (19) is free to rotate the drive sprocket (28) and is correctly engaged on the sprocket. Check the tension of the chain. The chain should be fully seated in the bar channel. DO NOT over tighten. The chain (19) should be able to be lifted at least 5mm in the centre of the bar. (Fig L)



13. Using the supplied spark plug / screwdriver wrench (32), firmly tighten the chain drive side cover nut/s (23) on the chain drive side cover (22) in a clockwise direction. (Fig M)

CAUTION: A new chain (19) will stretch after just a few minutes of use. Check and, if necessary, re-adjust the chain tensioning screw (21). A loose chain causes rapid wear to both the chain (19) and the guide bar (18) and could derail causing a major safety hazard.



NOTE: Do not make ANY adjustments with the chainsaw engine running.

To tighten a loose chain (19), loosen the chain drive side cover lock nuts (23), then using the supplied screwdriver (33), turn the chain tensioning screw (21) clockwise to tighten the chain (19).

Do not over tighten, the chain (19) should be able to lift 5 mm from the middle of the bar.

Retighten the chain drive side cover nuts (23) firmly using the supplied spark plug / screwdriver wrench (32).

Run the chainsaw for approximately 30 sec and then turn the chainsaw off. Retest the chain.

Filling up with Fuel and Oil



WARNING: Fuel is very flammable. Avoid smoking or causing any sparks or flames near fuel. Make sure that you stop the engine and allow it to cool before refuelling the machine. Select outdoor bare ground for fuelling and move at least 9m (30ft) metres away from the fuelling point before starting the engine.

It is suggested to wear safety glasses when mixing fuel.

- Only use oil that is expressly labelled for use with air-cooled 2-stroke engines. DO NOT use BIA or TCW (2-stroke water-cooling type) mixed oil.

The recommended mixing ratio is PETROL 40: OIL 1

- Use fresh unleaded fuel. Do not use ethanol based fuels.
- Poor quality fuel or oil may damage sealing rings, fuel lines or the fuel tank.
- Do not use waste or regenerated oil, it can damage the oil pump.

CAUTION. To maximise the lifetime of the engine, avoid the following:

- Do not use raw fuel, it will severely damage the engine very quickly.
- Do not run the tank dry, as this may cause damage to the engine.
- Do not use oil meant for 4-stroke engines, it will cause spark plug fouling, exhaust blocking and piston ring sticking.
- Do not use fuel mixtures that have been left standing for one month or more, they can cause clogging of the carburettor.
- Before storing the chainsaw for an extended period, empty the fuel tank (7), clean it then run the engine to empty the carburettor.

NOTE: Do not discard an unwanted fuel container with household waste. It must be taken to an authorised repository site.

Mixing Fuel (40:1 mixing ratio)

Mixing ratio is 40:1

IMPORTANT. Use good quality air cooled 2-stroke engine oil.

This product is powered by a 2-stroke engine and requires pre-mixing fuel with 2-stroke oil.

1 litre of petrol and 25 mls of 2-stroke oil OR

5 litres of petrol and 125 mls of 2-stroke oil

1. Use fresh unleaded fuel. Do not use ethanol based fuels . You must use 2-stroke oil specifically made for heavily stressed two-stroke engines.
2. Mix the fuel and oil in an approved container. Never mix fuel and oil directly into the fuel tank (7). Use the supplied fuel mixing container (31) included with this product. (Fig N)
3. Using the supplied fuel mixing container (31), fill with fuel to the 1:40 mark, then fill with 2 stroke oil to the 600ml marking. (Fig O)




WARNING. Never use any type of pre-mixed fuel/oil direct from fuel stations. This may include special blends intended for use in mopeds, motorcycles, etc.

4. Mix the fuel and oil thoroughly and also each time before fuelling.
5. Always pre-mix in small quantities. Never mix quantities larger than what will be used in a 30-day period.

NOTE: The fuel mixing container (31) provided is NOT for the storage of fuel.

This container is solely for mixing of fuel and oil only. Ensure to keep this container in a safe storage location, empty of fuel and out of reach of children.



Fuelling the Chainsaw



WARNING: Always ensure the engine is turned off before undertaking this task.


Never add fuel to a machine with a running or hot engine. Move at least 9m (30 ft.) away from the refuelling site before starting engine.

Do not smoke when refuelling or operating the chainsaw.

1. Rest the chainsaw on the ground or a secure surface and wipe any debris from around the fuel tank (7).
2. Unscrew the fuel tank cap (8) and pour the fuel and oil mixture into the tank with the aid of a funnel, to about 80% of its capacity. (Fig P)

NOTE: Be careful not to spill any mixture. If this happens, wipe the spill with a clean rag.

3. Secure fuel tank cap (8).



Adding Chain Oil





WARNING: Always ensure the engine is turned off before undertaking this task.




WARNING: Never start work unless the chain (19) and guide bar (18) are lubricated.

1. Place the chainsaw on its side with the oil tank cap (6) facing up. Unscrew and remove the oil tank cap (6).
2. Using a funnel, fill the oil tank (5) to 80% capacity with chain oil. (Fig P)
3. Fasten the oil tank cap (6) and wipe up any oil spillage. (Fig Q)
4. Release the front guard / chain brake (12) by pulling it firmly towards the back of the chainsaw until a click is heard. (Fig K)

To check the front guard / chain brake (12) has been released, you should be able to move the chain (19) by hand. (Fig S)



Starting the Chainsaw



WARNING: Do not start the engine whilst the chainsaw hangs from one hand. This is very dangerous as the chain (19) may come in contact with your body.

1. Fill the fuel and oil tanks respectively per previous instructions and ensure both caps are secure. Remove the bar cover (30).
2. Press the on/off switch (4) to the "On" position as indicated by an "I" (Fig T). Make sure the front guard / chain brake (12) is on when starting for safety by pulling it firmly towards the front of the chainsaw until a click is heard. (Some generous force can be used as this is a firm operation and will require the operator to pull back firmly). (Fig U)
3. When the machine is cold, first pull out the choke control (9) to the fully extended "CHOKE" position (also as indicated by the picture on the chainsaw above the choke control (9)). (Fig V).



CHOKE

NOTE: Once the choke control (9) has been pulled out, it cannot be pushed back to the run position. The choke control (9) returns automatically when the throttle trigger (3) is operated.

NOTE: Point 3 is not required if the engine is warm or is being restarted.

4. Hold the chainsaw securely on the ground and pull vigorously on the recoil starter (10). (Fig W)
Repeat (up to 15 times for first time operation) until the engine "kicks" (attempts to start).



5. Depress the safety lever (2) and slightly press on the throttle trigger (3) so the choke moves to the run position. (Fig X).
6. Pull the recoil starter (10) again and restart the engine. Allow the engine to warm up.
7. When restarting the engine when it is still warm, set the choke control (9) to the "RUN" position by depressing the safety lever (2) and depressing the throttle trigger (3). Hold the chainsaw securely on the ground and pull vigorously on the recoil starter (10). Allow the engine to run for a few moments with the throttle trigger (3) pressed in slightly.
9. When ready to start cutting, release the front guard / chain brake (12), by pulling it firmly towards the back of the chainsaw until a click is heard. Some generous force can be used as this is a firm operation and will require the operator to pull back firmly. (Fig U)



RUN

Stopping the Chainsaw

1. Release the throttle trigger (3).
 2. Press the on/off switch (4) to the "Off" position as indicated by the "O" (Fig T).
- NOTE:** Especially after the first starting of the chainsaw, the tension of the chain should be checked.

The chain will become loose on the first start up and will require adjustment. Refer to the "Assembly / Installation of the Guide Bar and Chain" section.

Checking the Oil supply

Run the engine at medium speed and check that the chain splatters a thin line of oil which can be seen on the ground when the guide bar (18) is pointed downwards (Fig Y). **DO NOT ALLOW THE TIP OF THE BAR touch ANY surface when checking the oil flow.** Keep the chain (19) and guide bar (18) well clear of ANY surface. This is normal. If there is no line of chain oil, stop the engine immediately and investigate the cause. The oil tank (5) could be empty or the oil supply to the chain blocked. This may require removal of the guide bar (18) and checking that the upper oil hole in the bar is clear of any blockages.



Adjusting the Carburettor

NOTE: It is preferred the above operation is performed by a service centre to ensure the correct setting for both safety and performance.

The carburettor is factory set and should not require adjustment.



Changes in operating conditions may require fine tuning of the carburettor. Proceed as follows.

H = HIGH (Fast) run adjustment screw (25). (Fig Z)

L = LOW (Slow) run adjustment screw (26). (Fig AA)

T = Idling adjusting screw (24). (Fig AB)

1. Stop the engine and screw in both the H and L screws (25 and 26) using the supplied screwdriver (33). Do not force.
2. Turn the H screw (25) back 3/4 of a turn.
3. Turn the L screw (26) back 1-1/2 turns.
4. Start the engine and let it warm up with the throttle trigger (3) half pulled in. When the engine is warm, release the throttle trigger (3).
5. Turn the L screw (26) slowly clockwise until the idling speed is at its maximum then turn the screw back (anticlockwise) 1/4 of a turn.
6. Turn the "T" idling adjusting screw (24) anticlockwise until the chain does not turn.
7. If the idling speed is too slow, turn the "T" idling adjusting screw (24) clockwise.
8. Make a test cut and adjust the H screw (25) for best cutting power, not for maximum speed.



Checking the operation of the clutch.

Each time the chainsaw is started, the operation of the clutch (35) should be checked as per the following detail. The chain MUST first be checked to ensure correct tension adjustment before starting.

1. When attempting to start the chainsaw, the chain (19) should not be trying to move around the guide bar (18). If it is trying to rotate around the guide bar (18), STOP the starting process and take the saw to an authorised service centre.
2. If point 1 is correct and the chain (19) is not trying to rotate around the guide bar (18), start the chainsaw as per the section in the manual "Starting the Chainsaw".
3. With the chainsaw operating, and ensuring the chain (19) is in a safe position with respect of other persons and any objects, release the chain brake (12).
CHECK, the chain (19) should NOT be rotating around the guide bar (18).
4. Operate the safety lever (2) and then accelerate the throttle trigger (3). The chain (19) should start and rotate. The harder the throttle trigger (3) is pulled, the faster the chain (19) will rotate. RELEASE the throttle trigger (3) so the motor returns to the idle condition. The chain (19) MUST stop rotating around the guide bar (18) when the motor of the saw is at idle.
5. If the chain (19) is constantly rotating when the motor of the saw is at idle, the chainsaw should NOT be used and the chainsaw should be taken to an authorised service centre for repair.
6. DO NOT use the chainsaw if the clutch (35) does not totally disengage when the motor of the saw is at idle.

Re-setting the Chain Brake

The front guard / chain brake (12) operates automatically in the event of kickback. As the guide bar (18) kicks up, the wrist of the operator's hand on the top handle knocks against the front guard / chain brake (12) causing it to move forward thus activating the chain brake (12).

To reset the front guard / chain brake (12) this can be done manually by pulling it firmly towards the back of the chainsaw until a click is heard. Some generous force can be used as this is a firm operation and will require the operator to pull back firmly. (Fig U)

CAUTION: Check that the chain brake (12) is operating correctly each time the chainsaw is used.

Operation

WARNINGS:

- Always follow the safety instructions given at the front of this manual. This chainsaw must only be used for cutting wood. It must not be used for cutting other types of material. Do not use the chainsaw as a lever for lifting, moving or splitting objects.
- Do not attach the chainsaw to a fixed stand.
- Do not attach any devices to the chainsaw other than those specified by the manufacturer.
- Be aware of any local or national restrictions when using this appliance. This could include, but not restricted to, times of operation, location of operation, or work place operation.

Helpful Hints

- Do not force the chainsaw into the cut. Apply only light pressure whilst running the engine at full throttle.
- If the chain (19) gets caught in the cut, do not try to remove it by twisting the guide or pulling forcibly. Use a lever or wedge to open up the cut so that the chain is freed.

Vibration

Vibration white finger may occur in operators using hand held vibrating tools such as chainsaws. Continual vibration can cause both vascular damage and also Nerve Damage to the operator.

The following guidelines can reduce the risk:

- Limit the use of vibrating tools.
- Hold vibrating tools as loosely as possible and in varying positions.
- Ensure tools are well maintained; make sure cutting blades are kept sharp to maintain efficiency, and replace worn parts.
- Use tools correctly, and use the right tool for the job (to do the job more quickly and reduce exposure time).
- Store tools so that they do not have very cold handles when next used.
- Use anti-vibration gloves.
- Take regular breaks of at least 10 minutes every hour away from the tool.

While cutting, always:

- Run the chainsaw motor at full revs. This makes the job safer, as there is less chance of pull-in or kick-back.
- Position your body to the left of the chainsaw so if it kicks back uncontrollably, it goes over your right shoulder. Never stand in the cutting line of the chainsaw.
- Keep a firm grip with your left hand on the front handle, with your thumb securely below the handle.
- The swivel of your wrist in a kick-back situation will activate the chain brake.
- Make sure the chain is tensioned correctly.

Guard against Kickback

Check the operation of the front guard / chain brake (12) each time you use the chainsaw. Run the chainsaw at full throttle for 1-2 seconds then push the front guard / chain brake (12) forwards. The chain (19) should stop immediately. If the chain (19) is slow to stop or only slows down you must take the chainsaw to an authorised Service Agent. Disengage the front guard / chain brake (12) by pulling the front guard backwards until you hear a click. (Some generous force can be used as this is a firm operation and will require the operator to pull back firmly – Fig U).

Do not use the chainsaw if the front guard / chain brake (12) is not operating correctly.

- Be constantly aware of the position of the upper quadrant of the blade tip. This is the part that triggers a kickback when it hits resistance.
- Never engage the upper quadrant of the guide bar (18) with whatever you are cutting and avoid contact with any hidden branches or obstructions. Ensure there is a clear work area.
- Always clear away brush, vegetation and any obstructing debris before attempting a cut that might trigger a kickback.
- Avoid cuts that will cause the chainsaw to jam in a tree trunk or limb.
- Observe the size of wood shavings, if they become dusty your chain (19) could need sharpening.

Chainsaw Applications



WARNING: Do not use the chainsaw if you are tired or under the influence of drugs, alcohol or medication.

If you are unfamiliar with the following cutting procedures, ensure you fully read and understand the instructions before undertaking the task.

Bucking Spike (Fig AC)

This chainsaw is fitted with a spike bumper (17). When downward cutting, the bumper should be spiked into the surface of the timber being cut.


This point is then used as a pivot point ensuring the cutting action is in the 1st quadrant of the bar length.

The cutting action is then performed by lifting the rear handle (1) of the chainsaw while the bucking spike (17) is the pivot in the timber.

The cutting action at the bar is then downward and the cut is made.

The bucking spike (17) is reset to a new pivot point by reducing the speed of the chainsaw to idle, withdrawing the chainsaw slightly away from the timber being cut and lowering the rear handle (1) so the bucking spike (17) is in a lower position on the timber.

Apply the bucking spike (17) to the timber in the new lower position and continue the cut in the above action.




Felling a Tree (Fig AD)

WARNING. Felling a tree should only be done by trained operators.



Decide the direction in which you wish the tree to fall taking into account the direction of the wind, the position of branches, lean of the tree, ease of subsequent limbing and bucking and other factors prevalent at the time.



1. Clear the area around the tree and make sure that you have a good foothold and clear retreat path.
2. Ensure that others in the area are aware of the felling and ensure people and animals are well clear.
3. Make a notch cut one-third of the way into the tree on the felling side.
4. Make the felling cut on the opposite side to the initial notch and slightly higher than the notch. As the felling cut gets close to the notch cut, the tree will begin to fall.
5. Remove the chainsaw from the cut, and stop the engine with the on/off switch (4), put the chainsaw down and leave the area along the retreat path.

Limbing (Fig AE)

Limbing is the process of removing the branches from a fallen tree.


Check the direction in which a branch will bend before cutting it. Always cut on the opposite side to the bending direction so that the guide bar (18) is not pinched in the cut.

For large limbs that cannot be removed in one cut, make an initial cut from the bent side and finish by sawing from the opposite direction.

Do not remove limbs that are supporting the fallen tree on the ground until the tree has been cut into lengths.



WARNINGS: Always keep a balanced stance. Do not stand on the log. Be alert to the fact that the log may roll over. When working on a slope, always stand on the uphill side of the log.



Bucking (Fig AF)

Bucking is cutting a log into lengths for easier handling.

To saw a log lying on the ground, first saw halfway, then roll the log over and cut from the opposite side. To saw the end of a log supported off the ground, first saw up from the bottom one-third through the log then finish by sawing down from the top. To saw a log in the middle of two supports holding it off the ground, first saw down from the top one-third through the log then finish by sawing up from the bottom.

CAUTION: Avoid cutting into the ground as this will very quickly dull the saw chain.



Pruning (Fig AG)

Pruning is the removal of a limb or branch from a standing tree.



WARNINGS: Do not use an unstable foothold or ladder. Do not overreach.

Do not saw above shoulder height. Always use both hands to hold the chainsaw. First cut up from the bottom and finish down from the top.



Maintenance

NOTE: This product is not suitable for repair or maintenance work by the unskilled person. The following detail explains how the product is cleaned, and basic maintenance / safety checks.

All other maintenance work must be carried out by service agents who are experienced with both the mechanical and electrical aspects of this product.

NOTE: Before cleaning your chainsaw or carrying out any maintenance procedures, make sure that the engine is off and is cool.

NOTE: Failure to maintain the following parts may result in reduced engine performance.

Disconnect the Spark plug to prevent accidental starting. Maintenance should be performed before and after each use. If the chainsaw is dropped or appears to suffer any other significant impact, it is highly recommended to perform all maintenance tasks before operation, and if there appears to be an issue, refer to the troubleshooting chart, or take to an authorised service agent.

Changing/replacing the Spark Plug

Regularly check the spark plug (16) for wear and any build-up of carbon on the electrodes. Spark plugs should be replaced every 10-15 hours of use.

1. Remove the air filter cover (14) by turning the air filter cover knob (15) in an anti-clockwise direction. Once the cover has been removed pull off the black rubber cap from the spark plug. (Fig AH)



WARNING: To avoid damage to the spark plug lead, ensure you hold the rubber cap and not by the lead itself.

2. To remove spark plug (16) use the supplied spark plug / screwdriver wrench (32) and turn in an anti-clockwise direction to remove.
3. Check for oil on the electrodes and clean off any excess. This can typically indicate that the fuel mixture ratio maybe incorrect.
4. Use a soft wire brush to clean up and carbon build up on spark plug electrodes.

Replace the spark plug or reset the electrode gap to 0.6-0.7mm.

Replacement spark plugs can be purchased from your local Lawnmower or small engine store.

Chain Sharpening



WARNING: Always ensure the engine is turned off before undertaking this task.

Sharpen the chain regularly to maintain optimum performance of the chainsaw.

Signs of a dull chain are:


- The sawdust becomes powder-like
- Extra force is required to execute a cut
- The cut does not track in a straight line
- Increased vibration
- Increased fuel consumption



WARNING: Wear heavy gloves when handling the chain. Hold the guide bar (19) securely in a vice.

Sharpen each cutter using the supplied sharpening file (34). Always use outward strokes. (Fig A1)

After sharpening, the cutters must all have the same width and length. After every 3 - 4 times use a repair centre to professionally sharpen your saw chain. They have the special tools necessary to ensure the correct cutting angles and depths are even.




Guide Bar Wear

Reverse the guide bar (18) every 8 working hours to ensure uniform wear. Check the bar rails frequently and if necessary remove burrs and square-up the rails using a flat file.


Air Filter:

1. Loosen the air filter cover (14) by turning the air filter cover knob (15) in an anti-clockwise direction and remove the filter cover (13).
2. Split the air filter into its two parts (Fig AJ) and clean the mesh. Dry particles can be removed by tapping on a hard surface. More stubborn dirt may require washing out the air filter (13) with petrol or using an air compressor.
3. Re-assemble the two halves and replace the air filter (13), air filter cover (14) and secure the air filter knob (15).

**Guide Bar:**

1. Take off the guide bar (18) and maintain it by removing any sawdust from the groove in the guide bar. (Fig AK)
2. Make sure that the oil port is not clogged. Oil the nose sprocket at the tip of the guide bar (18). (Fig AL)
3. Check for fuel and oil leakage and loose fastenings, especially those securing the handles and the guide bar (18).

If any defects are found, take the tool to an authorised Service Agent.



4. A bar cover (30) is supplied with this chainsaw and should be fitted over the chain (19) and guide bar (18) whenever the chainsaw is not being used. This includes immediately after use, transportation and service where possible. The chain teeth are extremely sharp and could create a safety hazard if the bar cover (30) is not fitted. Furthermore, the bar cover (30) provides protection to the chain cutting edge when the saw is not in use. (Fig AM)



WARNING: The chain has sharp edges.
Use work gloves for safety.

Vents:

1. Clean any dust away from the cooling vents as clogged vents can cause overheating.

Servicing

- It is recommended once you first use your product to get it serviced after 15 hours of use.
- From thereafter, service the product every 2 years.

Transportation and Storage

Always fit the chain and bar cover (30) when the chainsaw is not in use. It is recommended to drain BOTH fuel and oil from the chainsaw on the completion of use, prior to storage or transportation.

Always sit the chainsaw on a surface where the leakage of oil will not be a problem. The chainsaw is fitted with an oil pump and there will be after use an amount of oil in the oil channels inside the chainsaw, and also in the chain and bar channel. This oil can spill on to the surface the chainsaw is sitting as it drains from the above points.

Always store the chainsaw in a area safe away from the elements of the environments, ie high humidity, wet locations, hot environments etc.

Storage area should also be out of reach of children of both the chainsaw, mixing bottle and all accessories.

The chainsaw should always be stored with the On/Off switch (4) in the 'Off' position and the chain brake (12) ON.

If the chainsaw is to be stored for a long period of time it is advisable to apply a thin spray of oil over the chain (19), guide bar (18) and all exposed metal parts.

If storing the chainsaw back in the box after use, remove the side chain drive side cover (22), and disassemble the chain (19) and guide bar (18) from the chainsaw and secure it inside the box.

The chainsaw should be thoroughly cleaned of all wood chips, dirt etc prior to storage.

Warranty

Your new Gardenline® Chainsaw will more than satisfy your expectations. It has been manufactured under stringent Gardenline® Quality Standards to meet superior performance criteria.

You will find your new Chainsaw easy and safe to operate, and, with proper care, it will give you many years of dependable service.

CAUTION. Carefully read through this entire instruction manual before using your new Gardenline® Chainsaw .

Take special care to heed the Cautions and Warnings.

Your Gardenline® Chainsaw has many features that will make your job faster and easier. Safety, performance, and dependability have been given top priority in the development of this Chainsaw , making it easy to maintain and operate.

Use only Gardenline® replacement parts for your product. Non-conforming parts or modifications made to parts will void your warranty.

Environmental protection



Recycle unwanted materials instead of disposing of them as waste.

All tools, hoses and packaging should be sorted, taken to the local recycling centre and disposed of in an environmentally safe way.

Dispose of used motor oil in a manner that is compatible with the environment. We suggest you take it in a sealed container to your local service station for reclamation. Do not throw it in the trash or pour it into the earth.

What your 3 year warranty means

Great care has gone into the manufacture of this product and it should therefore provide you with years of good service when used properly.

In the event of product failure within its intended use over the course of the first 3 years after the date of purchase, we will remedy the problem as quickly as possible once it has been brought to our attention. In the unlikely event of such an occurrence, or if you require any information about the product please contact us via our after sales support services, details of which can be found in this manual and on the product itself. After Sales Support TEL: 1800 909 909

Service Support

If you are having difficulty in using your product, you can find instructional Know How videos on our website, www.powertoolsupport.com, by clicking on the Product Assistance tab > How To product Videos.

If you have any issues with the operation of your product, please take it with a copy of your receipt to one of our National Service Agents for repair or call us 1800 909 909 for advice.

A listing of our Service Agents is included with your product, however, you can also find our most updated listing on our website www.powertoolsupport.com, by clicking on the Service Agent link.

Accessories

The following accessories are available for purchase by visiting www.extrabattery.com.au or calling our customer service hotline on: 1800 909 909

- Replacement Bar (50712-BAR)
- Replacement Chain (50712-CH)

Troubleshooting

Problem	Possible Cause	Solution
Engine will not start	No spark in the spark plug (16). (Fig AN) Flooded engine	Clean the spark plug (16). Replace the old spark plug (16) with a new one. With the on/off switch (4) off , remove spark plug (16) from the engine. Move choke control (9) to the RUN position (pushed in completely), by depressing the safety lever (2) and depressing the throttle trigger (3), and pull the recoil starter (10) 15 to 20 times. This will clear excess fuel from engine. Clean and reinstall spark plug (16). Set on/off switch (4) to the On (I) position. Pull the recoil starter (10) three times with choke control (9) at RUN. If engine does not start, move choke control (9) to CHOKE and repeat normal starting procedure. If engine still fails to start, repeat procedure with a new spark plug (16).
Engine starts but will not accelerate properly.	Carburettor requires adjustment.	Refer to page 21 for adjustment, however, It is recommended this adjustment is performed by a Service Agent.
Engine does not reach full speed and/or emits excessive smoke	Check oil / fuel mixture Air filter (13) dirty. Carburettor requires adjustment	Use fresh fuel and the correct 2-stroke oil mix ratio. Clean air filter (13). Refer to page 19 for adjustment, however, It is recommended this adjustment is performed by a Service Agent.
Guide bar (18) and chain (19) running hot and smoking.	Chain brake (12) engaged. (Fig O) Chain tension too tight. Check guide bar (18) and chain (19) assembly. Guide bar (18) and chain (19) are damaged.	Release chain brake (12). Re-tension the chain (19). Refer to "Assembly / Installation of the Guide Bar and Chain" section in manual. Inspect guide bar (18) and chain (19) for damage.



For other issues not covered in this chart, please call Customer Service on 1800 909 909.

Specifications

Engine displacement:	37cc
Engine type:	Air cooled, single cylinder, 2-Stroke
Recommended maximum engine speed at idling:	2400-3200 min ⁻¹
Maximum engine speed with cutting attachment:	10000 min ⁻¹
Maximum engine power:	1.2KW @ 8000 min ⁻¹
Fuel type:	Unleaded petrol/2-stroke oil (40:1)
Fuel tank capacity:	310 cm ³
Bar oil tank capacity:	210 cm ³
Bar and chain lubricant:	Standard bar and chain oil
Bar oil feed system:	Mechanical pump
Chain and Guide Bar Type:	6" Sprocket Nose AE16-57-509P
Guide bar length:	40cm
Guide Bar length (cutting capacity):	38cm
Chain pitch:	0.375"
Chain drive link thickness:	0.05"
Maximum chain speed:	19 m/s
Drive Sprocket # of teeth:	6 teeth
Drive Sprocket pitch:	0.375"
Weight (including guide bar and chain with empty full tank):	5.1 kg
(without bar and chain with empty fuel tank):	4.2kg
Spark plug:	LD/L7T
Product Dimensions:	73cm x 25cm x 25cm (L x W x H)
Noise label rating 85 dBA (taken at 7.5 metres)	
you must wear ear protection at all times.	
A-weighted sound pressure level:	99.7 dB(A)
A-weighted sound power level:	109.8 dB(A)
Vibration levels (for each handle):	Front: hv,eq:7,87 m/s ² , Rear: hv,eq:9.44 m/s ²
This product complies with:	Safety ISO11681-1 2011, EMC EN ISO14982:2009



ALDI guarantees that our exclusive brand products are developed to our stringent quality specifications. If you are not entirely satisfied with this product, please return it to your nearest ALDI store, within 60 days from the date of purchase, for a full refund or replacement, or take advantage of our after sales support by calling the supplier's Customer Service Hotline.



Made in China

Gardenline® is a registered trademark of ALDI Stores

DISTRIBUTED BY:

ALDI STORES

1 SARGENTS ROAD

MINCHINBURY NSW 2770

www.aldi.com.au

AFTER SALES SUPPORT



1800 909 909 (toll free)

e-mail: help@powertoolsupport.com

MODEL: 50712 • 11/2015 • WLCS38A-375

3

YEAR WARRANTY