

Concept2 Oar Order Form - Sweep

Name / Organisation: _____

Address: _____

Phone: _____ Email: _____

Order Number: _____

Use this guide to select the oar specifications that meet your needs. The choices in bold represent universal oar specs that meet the needs of most crews. There is additional oar information on our website: concept2.com.au/oars. When you are ready to place your order, give us a call on (03) 5221 3655.

Quantity _____ Number of Stroke: _____ Number of Bow _____ Set ID: _____

Shaft The ultralight shaft offers a balance of light weight and good durability. The Original Shaft has the greatest impact resistance, but is heavier.

- Ultralight** Skinny

Stiffness Most people order medium stiffness unless they have a clear personal preference for soft or stiff. Smaller rowers ordering Fat Blades might consider soft shafts.

- Medium** Stiff Soft Extra Soft (skinny only)

Blade The Comp blade is our latest design, and has produced the fastest results in our on-water testing. The Smoothie2 Vortex blade has produced the best on-water testing results for a standard-width blade (not comp or Fat2).

Note: The Smoothie2/Fat2 mould introduced in late 2006 is based on the same ideas as the original Smoothie, but with changes in curvature to improve the handling of the blade on both drive and recovery.

In addition, we continue to offer the older blade designs for those who prefer them for replacement purposes.

- Comp 26x43.5** Vortex Edge Big Blade 25x55 Vortex Edge
 Smoothie 2 25x54 Vortex Edge Big Blade 25x55 Plain
 Smoothie 2 25x54 Plain Fat2 27x54 Vortex Edge

Handle Adjustable length oars must have composite handles. Fixed length oars may have wood or composite handles. Fixed length composite handles are not held in stock (order only).

- Composite Adjustable** Timber (fixed length only) 39mm handle diameter
 Composite Narrow (fixed length only) Timber (fixed length only) 42mm handle diameter
 Composite Medium (fixed length only) Timber (fixed length only) 45mm handle diameter

Grips The green rubber grip is more durable and easier to keep clean. The blue cellular grip is easier on the hands with a suede like texture, but requires more frequent cleaning to maintain its properties and is not as durable as the green rubber. (*Ranges for outer to inner hand grips).

- | | |
|---|---|
| <input type="radio"/> Timber Veneer (39 – 41.5mm*) | <input type="radio"/> Blue Cellular (40.4 – 46mm*) |
| <input type="radio"/> Black Suede (37 – 40mm*) | <input type="radio"/> Green Rubber (37.5 – 41.5mm*) |
| | <input type="radio"/> Timber (fixed length oars) |

Oar Length Most rowers choose the versatility of adjustable length oars. The optimal oar length will depend on the type of blade you are using. Shown below are length ranges we recommend for oars with different blade types. The adjustable lengths in bold will suit a wide variety of situations. Other factors that should be considered are rig, rowing style and size of crew. For example, faster crews should consider the longer range; slower crews should consider the shorter range.

NOTE: All Fat blades should be rowed about 5-6cm shorter than Smoothies to be most effective.

- | | | |
|--|--|--|
| <p>For Fat2 Blades:</p> <p><input type="radio"/> 362 - 367 cm</p> <p><input type="radio"/> 365 - 370 cm</p> <p><input type="radio"/> 368 - 373 cm</p> | <p>For Comp, Big Blade, and Smoothie2 blades:</p> <p><input type="radio"/> 367 - 372 cm</p> <p><input type="radio"/> 370 – 375 cm</p> <p><input type="radio"/> 373 - 378 cm</p> | <p><input type="radio"/> Other (please specify)</p> <p>Fixed Length _____</p> <p>Other Adj Length: _____</p> |
|--|--|--|

Inboard The 107-119 cm range covers most applications with the 5cm adjustable length oars. The 111-123cm range is typical for fixed length oars.

- | | | |
|---|------------------------------------|--|
| <input type="radio"/> 107-119 cm (with the handle in the shortest adjustable length setting) | <input type="radio"/> 111 - 123 cm | <input type="radio"/> Other (please specify) |
| | | Other: _____ |

Pitch Most users prefer 0 degrees in the oar and work with 4 +/- 1 degree in the oarlock

- | | | |
|---------------------------------|--|--------------|
| <input type="radio"/> 0 Degrees | <input type="radio"/> Other (please specify) | Other: _____ |
|---------------------------------|--|--------------|

Additional Information / Requirements: Please list any detail or requirement discussed with Sales Team not itemised on the Specification sheet that may not be a Sykes / Concept2 Standard part.