

Specification Sheet for Rowing (Sweep) Boats - All Construction Types

Order Instructions

This form is used to provide Sykes with the specifications for your new boat. This form can be used for all boat construction types.

Dual use boats (pair/doubles or fours/quads) ordered using this form will be built as a rowing boat first. Please check the implications of this by referencing the boat weight section of the Sykes Boat Brochure. Please use the 'Specification Sheet for Sculling Boats' if you require the boat to be built as a sculling boat first.

Please complete the Specification by referencing the Sykes Boat Brochure and if you require any assistance in any aspect of your order, please do not hesitate to contact our office.

Customer Details:

Name:			
Address:			
Official Order Number:			
Contact Details:			
Name			
Phone	Mobile:	Fax:	
Email			
Type of boat:			
Eight Coxed Four	Coxless Four Coxless P	Pair Training Four	
Boat Size:			
Mould Number			
Average weight of Rower (kg)			
Construction Materials:			
Honeycomb Carbon / Kevlar Composite	Glass Honeycomb	Spheretex	
Coxswain Position:	Rudder Type:		Rudder Position:
Bow Coxed	Aluminium Fin Rudder		Stern Rudder (Spheretex only)
Stern Coxed	Other		
Seat:		Stretcher Details:	
Unisex carbon seat with bearing wheels		Carbon Stretcher board	
Unisex synthetic seat with bearing wheels		Timber Stretcher board	
		New Wave Shoes	Active Adjustable Shoes (UK6 - UK11) Active Adjustable Shoes (UK9 - UK14)
		Specify Shoes Sizes (New Wave))
		1 Seat:	5 Seat:
		2 Seat:	6 Seat:
		3 Seat:	7 Seat:
		4 Seat:	8 Seat:
		Clog Foot Stretcher	
		Steering stretcher for coxless	boats in seat



Jeff Sykes and Associates Pty. Ltd. 65-67 Tucker Street, Breakwater, Victoria, 3220 P: (03) 5221-3655 F: (03) 5221 2596 W: www.sykes.com.au E: sales@sykes.com.au

Riggers

Boats ordered using this specification sheet will be built as a sweep boat first.

Additional riggers to convert the boat to a double or quad scull are also available.

Rowing Riggers

Sculling Riggers

Rigger Type

Wing - Tubular Aluminium

Quick Release Option using Rowfit Fittings (Aluminium Wing only)

Rigger Finish (Default - Natural Silver)

Colour

(Limited Choice)

Biomechanical Setup

Heel Height (heel to lowest point on seat)	Biomechanical Setup Comments		
Rowing Rigging			
Spread (midpoint of adjustment)	(5 cm range)		
Oarlock Height (midpoint of adjustment)	(4 cm range)		
Sculling Rigging			
Span (midpoint of adjustment)	(6 cm range)		
Left Oarlock Height (midpoint of adjustment)	(3.5 cm range)		
Right Oarlock Height (midpoint of adjustment)	(3.5 cm range)		

Other Details

Pin Stripe and Name

Top Colour	6mm	12mm	Boat Name Require	ed? Yes	No
Middle Colour	6mm	12mm	Boat Name		
Bottom Colour	6mm	12mm	Colour		
Electronics - Wiring Harness			Font	Printed	Script
Supply and fit Coxmate wiring harness, speakers and seat sensor					
Supply and fit NK wiring harness, speakers and seat sensor					
Supply and fit NK SpeedCoach wiring harness and impeller					
Supply electronics Unit					
Unit Required					
Additional Information / Requirements					

Please list any detail or requirement discussed with Sales Team not itemised on the Specification sheet that may not be a Sykes Standard part.

On receipt of your completed specification, we will send you a confirmed Production Quotation based upon your requirements

Name and signature of person filling out specification sheet

Signature: