

STOCKGUARD



SAFETY // HELPFUL TIPS

- ALWAYS MAKE SURE GUN IS UNLOADED AND SAFETY IS ON
- NEVER POINT GUN AT YOURSELF OR ANYONE ELSE

- To ensure maximum product life and proper gun care, remove if subjected to moisture. Wipe off gunstock with dry towel and allow neoprene to dry completely before reinstalling.
- Do not install cover if an oil has recently been used on gunstock.
- This is a sewn product, some loose threads can be expected. Do not pull, simply cut with scissors at base of thread to remove and keep seam intact.



- 1 The neoprene is rubber backed, which helps keep the cover in place. To install, turn the cover completely inside out so the rubber is facing out.

* GUNS WITHOUT SCOPES GO TO STEP 2, THEN SKIP TO STEP 5
* GUNS WITH SCOPES GO TO STEPS 3



- 3 Pull the large opening over the butt plate first and begin to pull down towards pistol grip. The seam should be on bottom of stock (careful to help over the swivel stud to prevent snagging).



- 4 Once the cover is mostly pulled on (still inside out), you will need to "stretch" the small opening over the butt plate (this is the hardest step). Then continue pulling until the cover is gathered by the pistol grip.



- 2 With the seam on the bottom, pull the smaller opening over the barrel and continue pulling (and stretching where help is needed) until the cover is gathered by the pistol grip. Proceed to step 5.



- 5 Now that the cover is bunched by the pistol grip it is time to turn right-side out.



- 6 Curl the smaller end under to begin gripping the rubber to the stock.



- 7 Using both hands begin to "roll" the cover back until fully right-side out.



- 8 You may need to re-adjust cover for perfect fit.

HAPPY SHOOTING!



PROUDLY

SINCE 1996



To see the full line of Beartooth accessories, visit us at www.beartoothproducts.com