



US008695830B2

(12) **United States Patent**
Meyers et al.

(10) **Patent No.:** **US 8,695,830 B2**
(45) **Date of Patent:** ***Apr. 15, 2014**

(54) **CONTAINER LID HAVING INDEPENDENTLY PIVOTING FLIP TOP AND HANDLE**

(75) Inventors: **David O. Meyers**, Kaysville, UT (US);
Steven M. Sorensen, Alpine, UT (US);
Kim L. Sorensen, Alpine, UT (US)

(73) Assignee: **Runway Blue, LLC**, Pleasant Grove, UT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/610,445**

(22) Filed: **Sep. 11, 2012**

(65) **Prior Publication Data**

US 2014/0069918 A1 Mar. 13, 2014

(51) **Int. Cl.**
B65D 51/18 (2006.01)

(52) **U.S. Cl.**
USPC **220/254.3**; 220/845; 220/836; 220/814;
220/810; 215/306; 215/228; D9/449; D9/443

(58) **Field of Classification Search**
USPC 220/212, 212.5, 254.3–254.5, 710.5,
220/752, 810, 836–837, 840–841, 845–846,
220/814; 215/228, 306; 222/566; D9/443,
D9/449; 16/267, 365, 444–445
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,037,051 A * 8/1912 Ramsey 215/235
1,094,469 A 4/1914 Pick
1,389,732 A 9/1921 Baron

1,479,053 A * 1/1924 Brooks 220/263
1,573,620 A 2/1926 Allston
2,056,879 A 10/1936 Winterhalter et al.
2,272,867 A 2/1942 Cobel
2,514,573 A 7/1950 Harrison
2,573,378 A 10/1951 Zurlinden
2,574,876 A 11/1951 Lebus
2,575,299 A 11/1951 Scheel
2,638,253 A 5/1953 Mueller
2,748,997 A 6/1956 Richmond, Sr.
2,752,971 A 7/1956 Tupper
2,754,866 A 7/1956 Coltman
3,022,925 A * 2/1962 Daniell 222/517

(Continued)

FOREIGN PATENT DOCUMENTS

CN 201139196 10/2008
JP 2006103793 A 4/2004
JP 2008247404 10/2008

OTHER PUBLICATIONS

U.S. Appl. No. 12/762,292, filed Apr. 16, 2010, Meyers, et al.



(Continued)

Primary Examiner — Mickey Yu
Assistant Examiner — Brijesh V. Patel
(74) *Attorney, Agent, or Firm* — Maschoff Brennan

(57) **ABSTRACT**

A container lid for sealing an opening to a container may include a handle and a flip top that are each independently pivotable along the same axis. The handle can be secured to the container lid between a mount on the lid and the flip top. The handle supports the weight of the container and, because the handle is independently rotatable relative to the flip top, the handle will not inadvertently open the flip top.

20 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,091,361 A 5/1963 Gawron
 3,143,205 A 8/1964 Ruderian
 3,144,016 A 8/1964 Basci
 3,168,226 A 2/1965 Underwood
 3,369,691 A 2/1968 Wei
 3,552,548 A 1/1971 Wallestad et al.
 3,770,160 A * 11/1973 Flider 220/318
 3,820,692 A * 6/1974 Swett et al. 222/547
 D233,116 S 10/1974 Swett et al.
 4,022,352 A 5/1977 Pehr
 4,136,799 A 1/1979 Albert
 4,158,902 A 6/1979 Chernack et al.
 D261,088 S 10/1981 Akimov et al.
 4,399,926 A 8/1983 Eidels-Dubovoy
 4,457,458 A 7/1984 Heinol
 4,474,303 A 10/1984 Maccise
 4,519,518 A 5/1985 Wiles et al.
 4,537,044 A 8/1985 Putnam
 4,735,333 A 4/1988 Lay et al.
 4,776,501 A 10/1988 Ostrowsky
 4,805,790 A 2/1989 Leonetti et al.
 4,932,225 A 6/1990 Bighouse
 5,065,877 A * 11/1991 Karppinen et al. 215/239
 5,065,911 A 11/1991 Rohr et al.
 5,088,614 A 2/1992 Dumestre
 D330,862 S 11/1992 Shibley et al.
 5,228,584 A 7/1993 Williams, Jr.
 D342,898 S 1/1994 Cane
 5,289,930 A * 3/1994 Inouye 215/235
 D350,460 S 9/1994 Picozza et al.
 5,386,922 A 2/1995 Jordan
 D356,499 S 3/1995 Cautereels et al.
 5,547,111 A 8/1996 Geiger et al.
 5,609,277 A 3/1997 McDonald
 D382,968 S 8/1997 Giles et al.
 D404,305 S 1/1999 De Baschmakoff
 D405,654 S 2/1999 Moran
 D421,547 S 3/2000 Demers
 6,161,713 A 12/2000 Krich
 6,283,333 B1 9/2001 Knickerbocker et al.
 6,299,005 B1 10/2001 Higgins
 6,379,032 B1 4/2002 Sorensen
 D458,081 S 6/2002 Bodum
 D461,420 S 8/2002 Kerman
 D497,431 S 10/2004 Bentley
 6,832,412 B2 * 12/2004 Kim 16/354
 6,860,397 B1 3/2005 Walters, Jr.
 D504,273 S 4/2005 Ancona
 D508,185 S 8/2005 Gauss
 D510,235 S * 10/2005 Sorensen D7/510
 D518,336 S 4/2006 Hirani
 7,073,678 B1 7/2006 Dibdin et al.
 D526,827 S 8/2006 Allen et al.
 D528,862 S 9/2006 Li
 D529,339 S 10/2006 Carreno et al.
 D532,650 S 11/2006 de Groote
 D543,454 S 5/2007 Leoncavallo et al.
 D546,131 S 7/2007 Morales
 D547,607 S 7/2007 Forsman
 D565,353 S 4/2008 Roth et al.
 D574,190 S 8/2008 Homma
 D580,227 S * 11/2008 Roth et al. D7/510
 D586,184 S 2/2009 Miller et al.
 D587,069 S 2/2009 Bodum
 D589,751 S 4/2009 Liu et al.
 D592,913 S 5/2009 Pinelli et al.
 7,533,783 B2 5/2009 Choi et al.
 D593,811 S 6/2009 Carreno
 D599,664 S 9/2009 Fujinami et al.
 D604,103 S 11/2009 Alviar et al.
 D609,970 S 2/2010 Richau et al.
 D613,110 S 4/2010 Lane et al.
 D622,089 S 8/2010 Daniel et al.
 D622,554 S 8/2010 Carreno
 7,806,284 B2 10/2010 Mangano

D626,837 S 11/2010 Meyers et al.
 D626,838 S 11/2010 Meyers et al.
 D628,483 S 12/2010 McKinney et al.
 D629,657 S 12/2010 Carreno
 7,870,980 B2 1/2011 Wilson et al.
 D641,594 S 7/2011 Huang
 D644,065 S 8/2011 Llerena
 8,020,257 B2 9/2011 Merten et al.
 D646,546 S 10/2011 Robinson et al.
 D646,919 S 10/2011 Nilsson
 D647,760 S 11/2011 Pearson
 D652,256 S 1/2012 Eyal
 D655,131 S 3/2012 Nilsson
 D655,967 S 3/2012 Bodum
 D656,357 S 3/2012 Enghard
 D658,445 S * 5/2012 Carreno D7/510
 D661,551 S 6/2012 Gilbert
 D666,047 S 8/2012 Lin
 D666,061 S 8/2012 Ying
 D667,694 S 9/2012 Meyers et al.
 8,302,796 B1 11/2012 Johnson
 8,342,349 B2 1/2013 Lu
 D677,121 S 3/2013 Meyers et al.
 D686,885 S 7/2013 Meyers et al.
 D686,886 S 7/2013 Meyers et al.
 D686,887 S 7/2013 Meyers et al.
 D686,888 S 7/2013 Meyers et al.
 2002/0074334 A1 6/2002 Karp
 2003/0085228 A1 5/2003 Oakes
 2004/0217139 A1 * 11/2004 Roth et al. 224/148.7
 2004/0262306 A1 12/2004 Smith
 2005/0045634 A1 * 3/2005 Ward et al. 220/254.3
 2005/0045636 A1 3/2005 Lown et al.
 2007/0012693 A1 1/2007 Kummer
 2007/0175931 A1 8/2007 Leoncavallo et al.
 2008/0099514 A1 5/2008 Carter et al.
 2009/0178940 A1 7/2009 Said
 2009/0188884 A1 7/2009 Nelson et al.
 2009/0188933 A1 7/2009 Daams
 2009/0301990 A1 12/2009 Cresswell et al.
 2010/0187235 A1 7/2010 Chen
 2010/0200438 A1 8/2010 Davies
 2010/0206835 A1 8/2010 Yu
 2010/0224631 A1 * 9/2010 Roth et al. 220/288
 2010/0282703 A1 * 11/2010 Yang 215/228
 2011/0017760 A1 * 1/2011 Newman 220/836
 2011/0083300 A1 4/2011 Heger et al.
 2011/0253733 A1 * 10/2011 Meyers et al. 220/833

OTHER PUBLICATIONS

U.S. Appl. No. 13/232,891, filed Sep. 14, 2011, Meyers, et al.
 U.S. Appl. No. 13/232,935, filed Sep. 14, 2011, Meyers, et al.
 U.S. Appl. No. 29/430,882, filed Aug. 30, 2012, Meyers, et al.
 U.S. Appl. No. 29/431,544, filed Sep. 7, 2012, Meyers, et al.
 U.S. Appl. No. 13/609,238, filed Sep. 10, 2012, Meyers, et al.
 U.S. Appl. No. 13/633,864, filed Oct. 2, 2012, Meyers, et al.
 U.S. Appl. No. 29/457,097, filed Jun. 6, 2013, Sorensen, et al.
 U.S. Appl. No. 29/457,096, filed Jun. 6, 2013, Sorensen, et al.
 U.S. Appl. No. 61/832,085, filed Jun. 6, 2013, Sorensen, et al.
 Kor One, <http://www.korwater.com/buyONE>, accessed Apr. 21, 2010.
 Core 77, <http://www.core77.com/blog/materials/kor.sub.--one.sub.--water.sub.--b.--vessel.sub.--actual.sub.--size.sub.--10211.asp>, accessed Apr. 21, 2010.
 Koyono, <http://www.koyono.com/KOR-ONE-Green-Zen-Water-Hydration-Vessel.sub.--p/kor-one.htm>, accessed Apr. 21, 2010.
 Fit Sugar, www.fitsugar.com/2496788, accessed Apr. 21, 2010.
 Thermos, <http://www.shopthermos.com/detail/TMS+HP4000GR6>, accessed Apr. 21, 2010.
 Goodlifter, <http://www.goodlifter.com/2009/02/360-paper-water-bottle/>, accessed Apr. 21, 2010.
 Notice of Allowance from U.S. Appl. No. 29/430,882 dated Aug. 5, 2013.
 Advisory Action from U.S. Appl. No. 12/762,292 dated May 24, 2013.
 Office Action from U.S. Appl. No. 12/762,292 dated Jul. 1, 2013.

(56)

References Cited

OTHER PUBLICATIONS

Office Action from U.S. Appl. No. 12/762,292 dated Oct. 2, 2012.
Office Action from U.S. Appl. No. 12/762,292 dated Jul. 17, 2012.
Office Action from U.S. Appl. No. 12/762,292 dated Feb. 10, 2012.
Notice of Allowance from U.S. Appl. No. 29/431,544 dated Aug. 14, 2013.
Office Action from U.S. Appl. No. 29/431,544 dated Mar. 25, 2013.
Office Action from U.S. Appl. No. 13/232,891 dated Jul. 19, 2013.
Office Action from U.S. Appl. No. 13/609,238 dated May 30, 2013.
International Search Report from PCT Application No. PCT/US2011/026508 dated Sep. 29, 2011.

Written Opinion from PCT Application No. PCT/US2011/026508 dated Sep. 29, 2011.
International Preliminary Report on Patentability from PCT Application No. PCT/US2011/026508 dated Oct. 16, 2012.
International Search Report from PCT Application No. PCT/US2012/054483 dated Nov. 16, 2012.
International Search Report and Written Opinion from PCT Application No. PCT/US2012/054497 dated Nov. 20, 2012.
International Search Report and Written Opinion from PCT Application No. PCT/US2013/052132 dated Aug. 16, 2013.
International Search Report and Written Opinion from PCT Application No. PCT/US2013/047161 dated Nov. 20, 2013.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5

1

CONTAINER LID HAVING INDEPENDENTLY PIVOTING FLIP TOP AND HANDLE

CROSS-REFERENCE TO RELATED APPLICATIONS

Not Applicable.

BACKGROUND

Many containers such as bottles include lids having integrated handles. Some containers can also employ a flip top to facilitate quick access to the contents of the container. When including a handle on such lids, there is a trade-off between positioning the handle in a convenient and efficient location, and minimizing the risk that the flip top will be opened unintentionally due to forces on the handle.

BRIEF SUMMARY

The present invention is directed to a container lid that includes a handle and a flip top that are each independently pivotable along the same axis. In this manner, the container lid increases the efficiency of using a container to carry, store, or consume contents.

In one embodiment, a lid for a container comprises a lid base having an opening for dispensing contents of the container, and a mount. The lid also comprises a handle, and a flip top for sealing the opening. The flip top includes a flip top pivot that is positioned between the handle when the handle is inserted into the mount. The handle and the flip top are each independently pivotable within the mount.

In another embodiment, a container comprises a bottle and a lid for sealing an opening of the bottle. The lid comprises a lid base having an opening for dispensing contents of the bottle, and a mount. The lid further comprises a handle, and a flip top for sealing the opening. The flip top includes a flip top pivot that is positioned between the handle when the handle is inserted into the mount. The handle and the flip top each are independently pivotable within the mount.

In another embodiment, a container comprises a bottle, and a lid that connects to the top of the bottle to seal the bottle. The lid comprises a lid base that includes an opening for dispensing contents of the bottle, and a mount that secures a handle and a flip top to the lid base. The handle includes a handle pivot on both sides which insert into openings on posts of the mount, and the flip top includes a flip top pivot having a protrusion on both sides that insert into openings on each side of the handle to secure the handle between the flip top and the mount. The flip top remains independently pivotable within the openings in the handle, and the handle remains independently pivotable within the openings in the posts.

This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the invention. The features and advantages of the invention may be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims. These and other features of the present invention will become more fully apparent from the following

2

description and appended claims, or may be learned by the practice of the invention as set forth hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to describe the manner in which the above-recited and other advantages and features of the invention can be obtained, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

FIG. 1 illustrates an exploded view of an exemplary container lid according to one or more embodiments of the present invention;

FIG. 2 illustrates the assembled container lid of FIG. 1;

FIGS. 3-4 illustrate the container lid of FIG. 1 when attached to a bottle; and

FIG. 5 illustrates a locking slot for maintaining the position of the handle of the container lid of FIG. 1.

DETAILED DESCRIPTION

The present invention is directed to a container lid that includes a handle and a flip top that are each independently pivotable along the same axis. In this manner, the container lid increases the efficiency of using a container to carry, store, or consume contents.

In one embodiment, a lid for a container comprises a lid base having an opening for dispensing contents of the container, and a mount. The lid also comprises a handle, and a flip top for sealing the opening. The flip top includes a flip top pivot that is positioned between the handle when the handle is inserted into the mount. The handle and the flip top are each independently pivotable within the mount.

In another embodiment, a container comprises a bottle and a lid for sealing an opening of the bottle. The lid comprises a lid base having an opening for dispensing contents of the bottle, and a mount. The lid further comprises a handle, and a flip top for sealing the opening. The flip top includes a flip top pivot that is positioned between the handle when the handle is inserted into the mount. The handle and the flip top each are independently pivotable within the mount.

In another embodiment, a container comprises a bottle, and a lid that connects to the top of the bottle to seal the bottle. The lid comprises a lid base that includes an opening for dispensing contents of the bottle, and a mount that secures a handle and a flip top to the lid base. The handle includes a handle pivot on both sides which insert into openings on posts of the mount, and the flip top includes a flip top pivot having a protrusion on both sides that insert into openings on each side of the handle to secure the handle between the flip top and the mount. The flip top remains independently pivotable within the openings in the handle, and the handle remains independently pivotable within the openings in the posts.

FIG. 1 illustrates an exploded view of an exemplary container lid **100** according to one or more embodiments of the invention. Lid **100** comprises a base **103** having a spout (or opening) **105** and a mount **104**. A pivoting handle **102** and flip top **101** connect to mount **104** as is shown in FIG. 2.

Lid **100** can be attached to a container such as a bottle to seal the container. Although the Figures illustrate that spout **105** is sealed by pressing the protrusion **106** of flip top **101**

into spout **105**, other means of sealing a spout or opening in the lid using a flip top can equally be employed (e.g., a flip top that extends around a spout, a flip top that clips to base **103**, etc.).

Flip top **101** includes a flip top pivot **101a** having a protrusion **101b** on each side. As shown in FIGS. **1**, **2**, **4** and **5**, flip top pivot **101a** may comprise an at least substantially solid or continuous body and protrusions **101b** may extend outwardly from each side or end of the body. Handle **102** includes a loop **102a** and a handle pivot **102b** on each side. Flip top **101** and handle **102** are mounted within mount **104** such that flip top **101** and handle **102** can each independently pivot. Although the Figures illustrate a handle having a round loop, loops of other shapes could also be used. Further, handle **102** can also be formed in a shape other than a loop as long as the handle includes handle pivots **102b** on both sides (e.g., a hook, a clip, etc.).

As shown in FIG. **1**, mount **104** includes posts **104a** positioned on opposite sides of the mount. Each of posts **104a** includes an opening **104b** (only visible on one side) for receiving a corresponding handle pivot **102b**.

As shown in FIG. **2**, handle **102** is attached to mount **104** by inserting handle pivots **102b** into openings **104b** or receiving portions in posts **104a** of mount **104**. With handle **102** attached to mount **104**, flip top pivot **101a** can be inserted between handle **102** such that protrusions **101b** insert into openings **102c** or receiving portions in handle **102**.

In this manner, flip top **101** and handle **102** are securely attached to the lid while enabling flip top **101** and handle **102** to remain independently pivotable. For example, while flip top **101** remains inserted into spout **105**, handle **102** can be freely pivoted around the axis of mount **104**. Similarly, flip top **101** can be pivoted around the axis of mount **104** without pivoting handle **102**.

This configuration facilitates the storage and handling of a container having lid **100**. FIGS. **3** and **4** illustrate an exemplary bottle **107** on which lid **100** can be used. Such bottles **107** can be used to store, carry, and/or mix ingredients of a beverage or other food product. The position of handle **102** facilitates carrying a container while minimizing the likelihood that flip top **101** will separate from spout **105** inadvertently. Also, because handle **102** can be pivoted independently from flip top **101**, use of a container is further facilitated.

In some embodiments, such as is shown in FIG. **5**, handle **102** can include grooves **103c** that interlock with corresponding rails **104c** in mount **104**. When handle **102** is pivoted downward to the orientation shown in FIG. **2**, rails **104c** are positioned within grooves **103c** thereby holding handle **102** in the orientation. Maintaining the position of handle **102** can be desirable in many situations such as when drinking a beverage through spout **105**. Of course, more than one set of rails and grooves could be configured on handle **102** and mount **104** to provide more than one locking position for handle **102**.

As stated above, lid **100** can be assembled by first inserting handle pivots **102b** into openings **104b** in mount **104**. Handle **102** can be manufactured from materials that are sufficiently flexible to allow handle pivots **102b** to be inserted into openings **104b** (e.g. by squeezing handle pivots **102b** together). Because handle **102** can be squeezed together, handle pivots **102b** can therefore have a substantial length for insertion into openings **104b**.

To retain handle pivots **102b** within openings **104b** in posts **104a** of mount **104**, flip top pivot **101a** is then pressed into handle **102** to insert protrusions **101b** within openings **102c** in handle **102**. In this way, handle **102** is secured between flip top pivot **101a** and posts **104a** (i.e., flip top pivot **101a** pre-

vents handle **102** from being squeezed together) to allow handle **102** to support the weight of a container on which lid **100** is used.

Lid **100** can be manufactured from materials that are sufficiently flexible to allow posts **104a** to deflect slightly when flip top pivot **101a** is inserted, but sufficiently rigid to prevent handle **102** and flip top **101** from being removed from mount **104** without significant force.

In other words, while flip top pivot **101a** is inserted between handle **102**, handle **102** cannot be squeezed sufficiently to remove handle pivots **102b** from openings **104b**. Further, mount **104** can be sufficiently rigid such that flip top **101** cannot be removed without great force, thereby preventing the inadvertent removal of handle **102** even when substantial force is applied to handle **102** (e.g. when handle **102** supports a full container during rugged activities). In this manner, flip top **101**, handle **102**, and lid base **103** can be manufactured as separate components and easily assembled, thus simplifying the manufacture of lids **100**.

The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

What is claimed:

1. A lid for a container comprising:

- a lid base having an opening for dispensing contents of the container;
- a mount comprising a first post and a second post;
- a handle comprising a first end with a first handle pivot and a second end with a second handle pivot; and
- a flip top for sealing the opening, the flip top comprising an elongated body with a first end for opening the flip top and a second end including a flip top pivot,

wherein:

- the flip top pivot is disposed between and engages the first end of the handle and the second end of the handle,
- the first handle pivot is connected to a first receiving portion of the first post of the mount, the first handle pivot comprising a first protrusion that extends into the first receiving portion of the first post of the mount,
- the second handle pivot is connected to a second receiving portion of the second post of the mount, the second handle pivot comprising a second protrusion that extends into the second receiving portion of the second post of the mount,
- the first end of the handle is sandwiched between a first end of the flip top pivot and the first post of the mount and the second end of the handle is sandwiched between a second end of the flip top pivot and the second post of the mount,
- a first protrusion on the first end of the flip top pivot extends into a first opening in the first end of the handle and a second protrusion on the second end of the flip top pivot extends into a second opening in the second end of the handle,
- the handle and the flip top are each independently pivotable relative to the lid, and
- the handle and the flip top are each independently movable about a common axis.

2. The lid of claim **1**, wherein the first and second protrusions of the first and second handle pivots comprise cylindrical protrusions that extend in opposite directions.

5

3. The lid of claim 1, wherein the first protrusion on the first end of the flip top pivot is inserted into the first opening in the first end of the handle and the second protrusion on the second end of the flip top pivot is inserted into the second opening in the second end of the handle.

4. The lid of claim 3, wherein the first and second ends of the handle deflect inwardly to allow the first and second protrusions of the first and second handle pivots to be inserted into the first and second receiving portions in the first and second posts of the mount.

5. The lid of claim 1, wherein the handle comprises a loop, the first opening in the first end of the handle and the second opening in the second end of the handle comprise circular openings, and the first and second protrusions on the first and second ends of the flip top pivot comprise coaxial cylindrical protrusions that extend from the flip top pivot in opposite directions.

6. The lid of claim 1, wherein the handle is pivotable around an axis of the mount; and wherein the flip top is pivotable around the axis of the mount.

7. The lid of claim 1, wherein the flip top pivot comprises an at least substantially solid body and prevents the first and second ends of the handle from being squeezed together.

8. The lid of claim 1, wherein the mount includes at least one rail over which a groove in the handle is positioned to hold the handle in a particular orientation relative to the mount.

9. The lid of claim 8, wherein the at least one rail includes a first rail on an inside of the first post; and wherein the groove is positioned on a surface of the first end of the handle that faces the inside of the first post.

10. The lid of claim 8, wherein the at least one rail includes multiple rails on an inside of the first post; and wherein the handle includes multiple grooves positioned on a surface of the first end of the handle that faces the inside of the first post.

11. The lid of claim 1, wherein the opening in the lid base is a spout into which a downwardly extending protrusion of the flip top is inserted to seal the opening.

12. A container comprising:
a bottle; and

a lid for sealing an opening of the bottle, the lid comprising:
a lid base having an opening for dispensing contents of the bottle;

a handle comprising a first end with a first handle pivot and a second end with a second handle pivot; and

a flip top for sealing the opening in the lid base, the flip top including a flip top pivot comprising:

a first protrusion that is disposed in a first receiving portion of the first end of the handle; and

a second protrusion that is disposed in a second receiving portion of the second end of the handle, wherein the first and second protrusions extend from the flip top pivot away from each other; and

a mount connecting the handle and the flip top to the lid base, the mount comprising:

a first post including a first receiving portion, the first handle pivot disposed in the first receiving portion of the first post; and

a second post including a second receiving portion, the second handle pivot disposed in the second receiving portion of the second post;

wherein the handle and the flip top are each independently pivotable within the mount.

6

13. The container of claim 12, wherein the flip top pivot comprises an at least substantially solid structure that prevents the first and second ends of the handle from being squeezed together.

14. The container of claim 12, wherein the handle supports a weight of the container and allows the container to be carried without creating an opening force on the flip top.

15. The container of claim 14, wherein the first and second ends of the handle deflect inwardly to allow the first and second handle pivots to be inserted into the first and second receiving portions in the first and second posts of the mount.

16. The container of claim 12, wherein the handle comprises a loop.

17. The container of claim 12, wherein the handle is pivotable about an axis of the mount; and wherein the flip top is pivotable about the same axis of the mount.

18. The container of claim 17, wherein the flip top pivot comprises a substantially solid body with the first protrusion on a first end of the body and the second protrusion on a second end of the body.

19. The container of claim 12, wherein the first post of the mount includes at least one rail and the first end of the handle includes at least one groove.

20. A container comprising:

a bottle; and

a lid that connects to a top of the bottle to seal the bottle, the lid comprising:

a lid base comprising an opening for dispensing contents of the bottle and a mount that secures a handle and a flip top to the lid base;

the mount comprising:

a first post; and

a second post;

the handle comprising:

a loop;

a first handle pivot at a first end of the loop, the first handle pivot connected to the first post of the mount and disposed between the first and second posts of the mount; and

a second handle pivot at a second end of the loop, the second handle pivot connected to the second post of the mount and disposed between the first and second posts of the mount; and

the flip top comprising:

an elongated body with a first end for opening the flip top and a second end with a flip top pivot, the flip top pivot comprising a substantially solid structure with a first end and a second end;

a first protrusion extending outwardly from the first end of the flip top pivot, the first protrusion disposed in a receiving portion of the first handle pivot; and

a second protrusion extending outwardly from the second end of the flip top pivot, the second protrusion disposed in a receiving portion of the second handle pivot;

wherein the flip top pivot is disposed between the first and second handle pivots of the handle;

wherein the flip top is independently pivotable relative to the handle; and

wherein the handle is independently pivotable relative to the flip top.

* * * * *