


# 6" Round Trim LED Recessed Lights




A.



4 1/7" (L) X 3 1/2" (W)  
ENGINE FOR CRLC4




B.



4 1/7" (L) X 5" (W)  
ENGINE FOR CRLC4




C.



7 2/3" (L) X 5 1/2" (D)  
ROUND & OPEN RECESSED TRIM



D.



7 2/3" (L) X 5 1/2" (D)  
ROUND & OPEN RECESSED TRIM

## Wattage

10W / 15W / 20W / 27W / 34W / 40W

## Voltage Input

120-277VAC  
50/60Hz

## Efficacy

85-86 LPW

## Dimming

0-10V Dimmable

## Finish

6" Haze & White Finish Trim  
Recessed Mounting

## Color Temperatures



## Features



Catalog No.	Fig.	Catalog No.	Fig.
CRLC-EGN-15W-30K-D	A.	CRLC6-15W-MCT-D	C.
CRLC-EGN-15W-40K-D	A.	CRLC6-15W-MCT-D-WH	D.
CRLC-EGN-15W-50K-D	A.	CRLC6-20W-MCT-D	C.
CRLC-EGN-15W-MCT-D	A.	CRLC6-20W-MCT-D-WH	D.
CRLC-EGN-20W-50K-D	A.	CRLC6-20W-MCTP-D	C.
CRLC-EGN-20W-MCT-D	A.	CRLC6-20W-MCTP-D-WH	D.
CRLC-EGN-20W-MCTP-D	A.	CRLC6-40W-MCTP-D	C.
CRLC-EGN-40W-MCTP-D	B.	CRLC6-40W-MCTP-D-WH	D.

## Factory-Installed Options

Watts	EM Options	Description	Photocell	Description	Paint	Sensor	Description
CRLC	OPT-EM-HB1EXT	EXTERNAL	N/A	N/A	N/A	N/A	N/A