


LED 5CCT Cloud Fixtures

**Wattage**

20W

Voltage Input120V AC
60Hz**Efficacy**

75 LPW

DimmingDimmable Down to 10% Using Standard TRIAC
LED Dimmer**Finish**White Translucent Acrylic Lens
Spun Stainless Steel
Brushed Nickel Finish**Color Temperatures****Features****Factory-Installed Options**

Catalog No.	Fig.	Watts	EM Option	Description	Photocell	Description	Paint	Sensor	Description
FCRB-11HL-MCT5	A.	FCR-11	OPT-EM-FCR11	INTERNAL	OPT-PC-FM	BUTTON W/ AUXILIARY BASE	N/A	OPT-SEN-2US INTERNAL FOR ALL MODELS	ULTRASONIC BI-LEVEL DIMMING (REMOTE NOT NEEDED)
FCRB-14-MCT5	B.	FCR-14	OPT-EM-FCR14	INTERNAL	277V Option			OPT-SEN-2USRC	REMOTE CONTROL
FCRB-16-MCT5-SEN	C.	FCR11, FCS11HL	OPT-EM-FCS11	INTERNAL	OPT-277V-FCR-11	EXTERNAL BOX			
		FCS14	OPT-EM-FCS14	INTERNAL	OPT-277V-FCS-11	EXTERNAL BOX			
		FS13	OPT-EM-FCS13	INTERNAL	OPT-277V-FCS-11HL	EXTERNAL BOX			
					OPT-277V-FCS-13	EXTERNAL BOX			