


FLS SERIES Outdoor Lighting

FLS-10W-50K-WH
FLS-10W-30K-WH
120V LED WEATHERPROOF FLOOD HEADS

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!



Customer Name: _____
Project Name: _____
Note: _____ | Type: _____



2 4/5" (H) X 6" (W)

LED Security Head Suitable for Outdoor applications, Ideal for doorway, pathway and alleys and Great for use with optional motion sensors or photocell.

Features

- 7-Year Warranty
- Die-cast Aluminum, Powder Coated
- 1 Lamp Head
- Lifespan: 70000 Hrs.

Technical Specifications

Electrical:

- Voltage: 100~130VAC 50/60Hz
- Wattage: 10W
- Power factor: 0.95
- Efficacy: 95 LM/W

Lighting:

- LED: COB
- Color temperature: 3000K/ 5000K
- Total Lumens: 950LM
- Color Rendering index: >80
- Beam Angle: 100°
- Lifespan: 70000 Hrs.

Mechanical:

- Die-cast Aluminum With Powder Coat Finish
- White Reflector
- Cord type: 13" #18 AWG stranded wires
- Operating Temperature: -40°F~104°F
- Suitable for Wet Location
- IP Rating: IP65

Applications:

- Ideal for Ideal for doorway, pathway and alleys
- Great for use with optional motion sensors or photocell

Other Model:



- 10W | 1000LM | FLH-10W-50K-BR




Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com



Photometrics: FLS-10W-WH



BUG Rating: B1-U1-G0



10W, 5000K Area 30'x 30' Mounting Height: 9'

Other Views:



Side View



Front View



Back View

Performance Table: FLS-10W-WH

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
FLS-10W-30K-WH	10W	100-130V	1000LM	3000K	B1-U1-G0	95
FLS-10W-50K-WH	10W	100-130V	1000LM	5000K	B1-U1-G0	95

Sample Ordering

Model	Min. Watt	Color Temp.	Housing
FLS	10W	30K = 3000K 50K = 5000K	WH

Factory-Installed Options

Blank = No Option

Example:

1. FLS-10W-50K-WH

(For FLS 10W 5000K 50K fixture 100~130V)

