LCFH SERIES RESIDENTIAL LIGHTING



50" x 5"


INTEGRATED LED SQUARE HOLOGRAM GLASS PEDANT



Integrated LED glass pendant is a contemporary and stylish design that can be used by itself as an accent piece, or grouped together to light a kitchen island, bar, or pool table.

Customer Name:

Project Name:



-eatures

- Multi CCT (Selectable Switch on the LED Board under the lens)
- Brushed Nickel Finish

- 5-Year Warranty
- Polycarbonate lens

Technical Specifications

Electrical:

Voltage: 120V AC 50/60Hz

Wattage: 12W Power Factor: >0.90 Efficacy: 68 LPW

Mechanical:

- Brushed Nickel Finish
- Glass Material: 5/64" (2mm) thickness, Ultra Clear Glass
- Power Cord is 60" Long
- Maximum Ambient Temperature: -22°F to 104°F
- IP20 indoor only

Lighting:

- Dimming: TRIAC Dimming (Dimmable Down to 5% Compatible with Traic and ELV Dimmers)
- Total Lumens: 810LM
- Color Temperatures: 2700K/3000K/3500K/4000K/5000K
- Multi CCT (Selectable Switch on back of the fixture)
- Color Rendering Index: CRI ≥ 90
- Beam Angle: 120° Rated life: 50.000 Hrs

Applications:

Integrated LED glass pendant is a contemporary and stylish design that can be used by itself as an accent piece, or grouped together to light a kitchen island, bar, or pool table.

Other Models:

• 36W | 2430LM | LCFH-3LR-MCT5 36W | 2430LM | LCFH-3LS-MCT5















Photometrics: LCFH-1L-MCT5





25 15 16 0.5fc 0.1fc 0.1f

BUG Rating: B0-U3-G1

Other Views:







Top View

Glass Lens View

Performance Table: LCFH-1L-MCT5

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LCFH-1L-MCT5	12W	120V	810LM	2700K/ 3000K/ 3500K/ 4000K/ 5000K	B1-U1-G0	68

Sample Ordering

Model Light Color Temp.

LCFH = 1L = MCT5

Example:

1. LCFH-1L-MCT5

(FOR LCFH 12W MCT5 FIXTURE 120V)

Other Model: LCFH-3LR-MCT5







Top View



Phone: (877) 805-2252 | Fax: (877) 805-2252 www.westgatemfg.com

