

# 2Ft & 4Ft Adjustable Linear Corner Corridor



A.



24 1/2"(w) x 3 8/9"(H) x 3 3/4"(D)



B.



48"(w) x 3 8/9"(H) x 3 3/4"(D)

## Wattage

10W / 15W / 20W / 30W / 40W

## Voltage Input

120-277VAC 60Hz

## Efficacy

115 LPW


## Dimming

0~10V Dimmable

## Finish

Heavy Die-Formed Steel  
White Finish

## Color Temperatures



## Features



### Factory-Installed Options

| Catalog No.      | Fig. | Watts      | EM Options    | Description | Plug-In Cord     | Description                   | Paint | Sensor                                 | Description                                     |
|------------------|------|------------|---------------|-------------|------------------|-------------------------------|-------|--|---|
| LCL-2FT-20W-MCTP | A.   | ALL MODELS | OPT-EM-CM1INT | INTERNAL    | OPT-HBC-125TL-BK | 8FT, 15A, 125V, WHT           | N/A   | OPT-SEN-2US<br>INTERNAL FOR ALL MODELS | ULTRASONIC BI-LEVEL DIMMING (REMOTE NOT NEEDED) |
| LCL-4FT-40W-MCTP | B.   |            | OPT-EM-CM1INT | INTERNAL    | OPT-HBC-277TL-WH | 8FT, 15A, 277V, WHT           |       |  |   |
|                  |      |            | OPT-EM-CM1INT | INTERNAL    | OPT-HBC-1255B-WH | 10FT, 15A, 125V, 18/3STR, WHT |       | WEC-3RC                                | OPTIONAL RC                                     |