




LED 360° Rotatable Wall Pack




A.



5.4" (H) x 5.2" (W) x 9.1" (L)




B.



8.8" (H) x 5.2" (W) x 9.1" (L)




C.



5.4" (H) x 5.2" (W) x 9.1" (L)



D.



8.8" (H) x 5.2" (W) x 9.1" (L)

Wattage

25W / 40W / 60W / 80W / 120W

Voltage Input

120-277VAC 60Hz

Efficacy

135 LPW

Dimming

0~10V Dimmable


Finish

Die-Cast Aluminum with Powder Coat Finish
Dark Bronze / White

Beam Angles



Color Temperatures



Features



Adjustable Head



360° Rotatable Light Head

Shroud Accessory



Catalog No.	Fig.	Catalog No.	Fig.	Catalog No.	Fig.
LW360-25W-30K-G2	A	LW360-80W-MCT-G2	B	LW360-80W-30K	B
LW360-25W-40K-G2	A	LW360-80W-30K-G2	B	LW360-80W-40K	B
LW360-25W-50K-G2	A	LW360-80W-40K-G2	B	LW360-25W-30K-WH	C
LW360-25W-MCT-G2	C	LW360-80W-50K-G2	B	LW360-25W-50K-WH	C
LW360-40W-30K-G2	B	LW360-120W-30K-G2	B	LW360-40W-30K-WH	C
LW360-40W-40K-G2	B	LW360-120W-40K-G2	B	LW360-40W-50K-WH	C
LW360-40W-50K-G2	B	LW360-120W-50K-G2	B		
LW360-60W-30K-G2	B	LW360-25W-MCT-WH-G2	D		
LW360-60W-40K-G2	B	LW360-80W-MCT-WH-G2	D		
LW360-60W-50K-G2	B	LW360-60W-30K	B		

Factory-Installed Options

Watts	EM Options	Description	Photocell	Description	Paint	Sensor	Description
25W/40W/60W	OPT-EM-LW360	BACK BOX	OPT-LW360-PC-B	BUTTON	OPT-CLR-85(BK/GR/SR/WH)	OPT-SEN-LW460-3MRLV-5	PROGRAMMABLE MICROWAVE (B-L-LEVEL)
80W	OPT-EM-LW360-LG	BACK BOX	OPT-LW360-PC-B	BUTTON	OPT-CLR-95(BK/GR/SR/WH)	OPT-SEN-LW460-3MRLV-5	REMOTE CONTROL
					OPT-CLR-35-SHR(BK/GR/SR/WH)	WEC-8RC	