


Traditional Glass Lens Wall Pack




A.



5" (W) x 6" (H) x 4" (D)




B.



5" (W) x 6" (H) x 4" (D)




C.



7.6" (W) x 9" (H) x 4.5" (D)



D.



11" (W) x 13" (H) x 6" (D)

Wattage

12W / 30W / 20W / 40W / 50W / 80W
100W / 120W

Voltage Input

120-277V

Efficacy

75 LPW

Dimming

0~10V Dimmable

Finish

Die-Cast Aluminum with Powder Coat Finish
Bronze / White

Beam Angles

80°x100°

Color Temperatures

3000K 4000K 5000K
5700K

Features



Adjustable Head



Factory-Installed Options

Catalog No.	Fig.	Catalog No.	Fig.	Watts	EM Options	Description	Photocell	Description	Paint	Sensor	Description
LWAX-SM-12W-30K	A.	LWAX-MD-20-50W-MCTP	C.	12W	OPT-EM-FM10D	EXTERNAL BACK BOX	OPT-PC-B	BUTTON	OPT-CLR-85(BK/GR/SR/WH)	OPT-SEN-3MRLV-5	PROGRAMMABLE MICROWAVE (BI-LEVEL)
LWAX-SM-12W-40K	A.	LWAX-LG-50-120W-MCTP	D.	20W/30W/50W	OPT-EM-FM1INT	INTERNAL	OPT-PC-B	BUTTON	OPT-CLR-85(BK/GR/SR/WH)	WEC-8RC	REMOTE CONTROL
LWAX-SM-12W-50K	A.	LWAX-SM-12W-30K-WH	B.			Vandal Res.					
LWAX-MD-30W-30K	C.	LWAX-SM-12W-50K-WH	B.	80W/120W	OPT-EM-0D2INT	INTERNAL	OPT-TRS-T20	TAMPER RES. SCREW			
LWAX-MD-30W-50K	C.										