

T8-8FT

A/C Direct (Ballast Override)

B35



TECHNICAL SPECIFICATIONS:

- :: T8 LED lamp operates A/C Direct (Ballast override)
- :: Rated for use in open fixtures only. Not for use in enclosed fixtures
- :: Housing: 6063 extruded aluminum with heat dissipation ribs for superior thermal management
- :: Beam Spread: 120°
- :: Base: Fits standard T8 or T12 sockets (G13)
- :: Rated Life: 50,000 hrs, 5-year warranty
- :: Ambient Operating Temperature: 14°F to 80°F
- :: Requires no ballast. Existing ballast must be bypassed and sockets wired directly to line voltage.
- :: Ideal for offices, retail stores, showrooms, and residential applications. Especially suited for areas where accessing the fixture is challenging.
- :: 40 Support Clips & Screws included in a master carton of 20 pieces.
- :: UL-listed



4FT. & 8FT. LED T8 PLASTIC / ALUMINUM TUBE LAMPS

CATALOG NO.	WATTS	LUMENS	COLOR TEMP	CHIP	FINISH	LENGTH
T8-8FT-40W-50K-C	40W	4800LM	5000K	210 SMS2835	Clear	8FT.
T8-8FT-40W-50K-F	40W	4800LM	5000K	210 SMS2835	Frosted	
T8-8FT-40W-40K-C	40W	4800LM	4000K	210 SMS2835	Clear	
T8-8FT-40W-40K-F	40W	4800LM	4000K	210 SMS2835	Frosted	