


T8-EZ3

A/C Direct or Ballast Compatible LED Tube




Works 3 ways:


1) With existing electronic ballast



2) A/C direct one end



3) A/C direct 2 ends



TECHNICAL SPECIFICATIONS:

- ∴ T8 LED lamp, operates in the following manners:
 - 1 Existing electronic ballast.
 - 2 Ballast override AC direct, load and neutral on two sockets (Shunted), reverse polarity accepted.
 - 3 Ballast override AC direct, load and neutral on one socket (Non-Shunted), see label on lamp for the correct end to power.
- ∴ Works with most instant start electronic ballasts in North America
- ∴ Voltage: 120~277V AC input, or 100~347V AC with ballast
- ∴ Heat sink: 6063 extruded aluminum with heat dissipation ribs for superior thermal management
- ∴ Beam Spread: 120°
- ∴ CRI: 80
- ∴ Base: Fits standard G13 sockets
- ∴ Rated Life: 50,000 hrs, 5-year warranty
- ∴ Ambient Operating Temperature: -4°F to 104°F
- ∴ Not dimmable, unless it is used with dimmable electronic ballast
- ∴ Lumens per watt: 100LWP with ballast / 115LWP without ballast
- ∴ Power consumption is the same when using with or without ballast.
- ∴ Lumens per watt: 100LPW with ballast / 115LPW without ballast

APPLICATIONS:

- ∴ Avoid initial labor costs by replacing the fluorescent tube with this compatible tube. Once the fluorescent ballast fails, there is no need to install a new ballast. This tube can simply work with direct A/C power.
- ∴ Ideal for offices, showrooms, refrigerators, cove lighting, etc.



2FT. & 4FT. LED T8-EZ3 PLASTIC / ALUMINUM TUBE LAMPS

CATALOG NO.	WATTS	LUMENS	COLOR TEMP	CHIP	FINISH	LENGTH
T8-EZ3-4FT-18W-50K-C	18W	2212LM	5000K	110 SMD2835	Clear	4FT.
T8-EZ3-4FT-18W-50K-F	18W	2212LM	5000K	110 SMD2835	Frosted	
T8-EZ3-4FT-18W-40K-C	18W	2212LM	4000K	110 SMD2835	Clear	
T8-EZ3-4FT-18W-40K-F	18W	2212LM	4000K	110 SMD2835	Frosted	
T8-EZ3-4FT-18W-35K-C	18W	2212LM	3500K	110 SMD2835	Clear	
T8-EZ3-4FT-18W-30K-F	18W	2212LM	3000K	110 SMD2835	Frosted	
T8-EZ3-2FT-15W-30K-C	15W	2032LM	3000K	60 SMD2835	Clear	2FT.
T8-EZ3-2FT-15W-40K-C	15W	2032LM	4000K	60 SMD2835	Clear	
T8-EZ3-2FT-15W-50K-C	15W	2032LM	5000K	60 SMD2835	Clear	