

24-Volt Indoor LED Ribbon Lights High Output



A. 16.4"(L) x 0.4"(W)



B. 16.4"(L) x 0.4"(W)



C. 98.4"(L) x 0.4"(W)

Wattage

4.4W Per Ft.

Voltage Input

24VDC (LED Driver Required)

Efficacy

75-79 LM/W Per Ft.

Dimming

Dimmable Using a Magnetic Driver

Finish

Cutting Increment: Every 4 Inches
 1 Female Ribbon-to-Power Supply Connector & 1 Male Plug
 for Connection to Next Ribbon
 Max Run: 20Ft.

Color Temperatures



Beam Angles



Features



Catalog No.	Fig.	Catalog No.	Fig.	Catalog No.	Fig.
ULR-IN-16F-HO-27K	A.	ULR-IN-16F-HO-27K-BK	B.	ULR-IN-98F-HO-27K	C.
ULR-IN-16F-HO-30K	A.	ULR-IN-16F-HO-30K-BK	B.	ULR-IN-98F-HO-30K	C.
ULR-IN-16F-HO-40K	A.	ULR-IN-16F-HO-40K-BK	B.	ULR-IN-98F-HO-40K	C.
ULR-IN-16F-HO-50K	A.	ULR-IN-16F-HO-50K-BK	B.	ULR-IN-98F-HO-50K	C.