













Integrated Aluminum LED Well/Path Lights

<p>A.</p> 	 <p>3 1/2"(H) x 4"(W)</p>
<p>B.</p> 	 <p>3 1/2"(H) x 4"(W)</p>
<p>C.</p> 	 <p>3 1/2"(H) x 4"(W)</p>
<p>D.</p> 	 <p>5"(H) x 4"(W)</p>
<p>E.</p> 	 <p>4"(H) x 4"(W)</p>
<p>F.</p> 	 <p>5 1/5"(H) x 4"(W)</p>

Wattage

6W

Efficacy

33-96 LPW

Housing

Die-cast Aluminum Housing
Black / Oil-Rubbed Bronze Finish

Beam Angles



Color Temperatures



Features



Catalog No.	Fig.	Catalog No.	Fig.	Catalog No.	Fig.	Catalog No.	Fig.	Catalog No.	Fig.
WLL-105-30K-BK	A.	WLL-106-30K-BK	B.	WLL-152-30K-ORB	C.	WLL-157-RGBWW-BT-ORB	D.	WLL-181-30K-BK	F.
WLL-105-RGBWW-BT-ORB	A.	WLL-152-30K-BK	C.	WLL-157-30K-BK	D.	WLL-159-30K-BK	E.	WLL-181-RGBWW-BT-ORB	F.