

3" LED Outdoor Cylinder Lights



Wattage

9W
9W (Down Light); 18W (Up/Down Light per end)

Voltage Input

120V AC

Dimmable

TRIAC Dimming (Using Standard TRIAC LED Dimmers)


Finish

Die-Cast Aluminum & Glass

Beam Angles



Color Temperatures



Features



Catalog No.	Fig.	Catalog No.	Fig.
WMC3-DL-MCT-BR-DT	A.	WMC3-UDL-MCT-BR-DT	E.
WMC3-DL-MCT-BN-DT	B.	WMC3-UDL-MCT-BN-DT	F.
WMC3-DL-MCT-WH-DT	C.	WMC3-UDL-MCT-WH-DT	G.
WMC3-DL-MCT-BK-DT	D.	WMC3-UDL-MCT-BK-DT	H.

Factory-Installed Options

Watts	EM Options	Description	Photocell	Description	Paint	Sensor	Description
2" & 3"	OPT-EM-FM10D	EXTERNAL BACK BOX	OPT-PC-B	BUTTON	N/A	OPT-SEN-WMC	PROGRAMMABLE MICROWAVE (BI-LEVEL)
4" & UP	OPT-EM-FM2INT	INTERNAL	277V Option	Description	N/A	WEC-8RC	OPTIONAL REMOTE CONTROL
			OPT-277V				INTERNAL ONLY FOR WMC 3L LED