



4555 BN

|                         |                                                                                                                                                                                                                                                                                                         |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description             | 5-Light satin opal cylinder chandelier                                                                                                                                                                                                                                                                  |
| Dimensions              | 21Ø x 20H   Pendant cable allows for 72” max. extension                                                                                                                                                                                                                                                 |
| Finishes Available      | Black [BLK]   Brushed Nickel [BN]   Oil Rubbed Bronze [ORB]                                                                                                                                                                                                                                             |
| Listing & Certification | UL Certified for Dry Location, Standard 1598                                                                                                                                                                                                                                                            |
| Electrical              | <ul style="list-style-type: none"><li>E26-base   60W max.</li><li>120V/60Hz line voltage input</li><li>150°C-rated supply conduits</li></ul>                                                                                                                                                            |
| Features                | <ul style="list-style-type: none"><li>Satin opal cylinder glass [G555]   4Ø x 6H, 1.75” opening</li><li>6’-Length silver SVT pendant cable included</li><li>Tiered decorative cap</li><li>Chandelier arms can be adjusted upward or downward facing</li><li>Installation accessories included</li></ul> |

Alternative Models

| LED          | Lamp Included  | Lm/W | Lumens | CCT   | CCT Available |
|--------------|----------------|------|--------|-------|---------------|
| 4555/9W30 BN | [5] 9W LED A19 | 89   | 800    | 3000K | 3000K   4000K |

LED Lamping (included in LED model above)

| Base | Average Life | Beam Angle | Power Factor | Dimmable | IP Rating | RoHs |
|------|--------------|------------|--------------|----------|-----------|------|
| E26  | 15000        | 220        | 0.9          | Yes      | 20        | Yes  |



LED-A19FR/9W/30