



Iceberg Undersink Water Cooler (ICS-PILFLIC)



The Iceberg is our robust undersink water chiller, supplying cold water on demand. The compressor driven unit is extremely quiet and easily fits inside your base cupboard, protected from mains water pressure surges with a shock arrestor and pressure reducing valve.

Created especially to accommodate small spaces conventional dispensers are too large for. Measuring only 12" x 16.5" x 12", the Iceberg's compact design will easily fit under most sinks. An impressive output capacity of 3 gallons per hour, the

compressor driven chiller provides exceptional cooling performance. Simply connect the Iceberg to a countertop mounted faucet for cold water demand.



Water Out



Water In



Cold tank drain

Features

- #304 Stainless Steel cold water reservoir
- Copper evaporator
- Adjustable cold water thermostat
- Powder coated cold rolled steel casing

Performance & Specifications:

General

Undersink pressure tank water cooler, with a stainless steel cold tank

Performance

Cold water outlet temperature 4-10°C (39.2-50°F)

Units designed for and tested in extreme temperatures for robust performance in all climates





Power Consumption

0.2 kw.hr/24hr

Cooler Cabinet

Powder-coated painted 18SWG cold rolled steel

Compressor

Hermetically sealed, PTC started with overload protector

Refrigerant charge: 35.0g (1.2 oz) R134a (Ozone friendly)

(220-240VAC 50Hz) (100-115VAC 60Hz)

Product Dimension

300mm (D) x 410mm (W) x 300mm (H)

(13" x 16.9" x 13.5")

Product Weight

12.5kg (27.6 lb)

Product Boxed Dimension

330mm (D) x 430mm (W) x 340mm (H)

(13" x 16.9" x 13.5")

Product Boxed Weight

13.6kg (30.1 lb)

For further information, please contact hello@wa2.ca or call toll free 1 877 689 4009